

## **INVITATION TO BID**

**BERWICK BOROUGH** will accept sealed bids for a new fire engine. Specifications are available on line at [www.bewickborough.org](http://www.bewickborough.org)  
Sealed bids must be clearly marked “Bid – Fire Engine” on the outside envelope and delivered to the Borough of Berwick Administration Office by 1:00 p.m. local time on Monday, August 15th, 2016. At 7:00PM on this date bids will be opened at the public council meeting at 1800 N. Market Street, Berwick, Columbia County Pennsylvania. Questions regarding the bid can be directed to Debra Force, Borough Manager. The Borough of Berwick reserves the right to accept or reject any and all bids.

**Ranger Hose Company**

**Borough of Berwick**

**Berwick, Pennsylvania**

**June 22, 2016**

**INTRODUCTION**  
**PROPOSAL REQUIREMENTS**

**GENERAL INFORMATION**

It is the intent of these specifications to secure apparatus constructed to withstand the severe and continuous use encountered during emergency fire fighting services. The apparatus must be of the latest type, carefully designed and constructed with due consideration to the nature and distribution of the load to be sustained.

These specifications detail the requirements for general design criteria of cab and chassis components, aerial device, fire pump and related components, water tank, fire body, electrical components, painting, and equipment. In evaluating the bid proposals to determine which proposal is the most advantageous, these major items shall be considered.

Apparatus and equipment must meet the specific requirements and intent of the requirements as specified herein. All items of these specifications shall conform to the character of the proposed apparatus and the purpose for which it is intended. Criteria as specified by the National Fire Protection Association Pamphlet No. 1901, latest edition, entitled "Suggested Specifications for Motor Fire Apparatus", as approved by the American Insurance Association and International Association of Fire Chiefs, are hereby adopted and made a part of these specifications the same as if they were written out in full, insofar as they apply and are not specifically modified in the following detailed specifications. Each bidder shall provide only that equipment as required in the following specifications.

The fire apparatus and equipment to be furnished in meeting these specifications must be the products of an established, reputable fire apparatus and/or equipment manufacturer. Each bidder shall furnish satisfactory evidence of the manufacturer's ability to construct, supply service parts and technical assistance for the apparatus specified. Each bidder must state the location of the factory and location for post delivery service.

**BID COMPLIANCE INSTRUCTIONS**

Each bidder must indicate his compliance with these specifications by marking "YES" or "NO" in the appropriate column for each individual paragraph of this specification. Indicating "YES" to a paragraph shall mean full compliance; indicating "NO" shall mean an exception is being taken. Any deviation from the specification, no matter how small, must be so annotated. All exceptions must be fully explained on a separate page, titled "Exceptions", giving reference to the page and paragraph where the exception is being taken. Failure to comply with this requirement shall result in the bid proposal being rejected.

The Borough of Berwick shall be the sole arbiter as to what exceptions may be allowed or disallowed. In the event a bidder fails to make any indication of compliance for any or all provisions it will be assumed that the bidder is taking total exception to the specification and the bid shall be disallowed.

**FIRE APPARATUS DOCUMENTATION**

The contractor shall supply, at the time of delivery, at least one (1) copy of the following documents:

The manufacturer's record of apparatus construction details, including the following information:

- Owners name and address
- Apparatus manufacturer, model and serial number
- Chassis make, model and serial number
- Front tire size and total rated capacity in pounds
- Rear tire size and total rated capacity in pounds
- Chassis weight distribution in pounds with water and manufacturer mounted equipment, front and rear

**Header Title**

Bidder Complies	
YES	NO

- Engine make, model, serial number, rated horsepower, rated speed and governed speed
- Type of fuels and fuel tank capacity
- Electrical system voltage and alternator output in amps.
- Battery make, model and total capacity in cold crank amps (CCA)
- Transmission make, model and serial number. If so equipped chassis transmission PTO(s) make, model and gear ratio
- Pump make, model, rated capacity in gallons per minute (liters per minute where applicable) and serial number
- Pump transmission make, model, serial number and gear ratio
- Auxiliary pump make, model, rated capacity in gallons per minute (liters per minute where applicable) and serial number
- Water tank certified capacity in gallons or liters
- Paint manufacturer and paint number(s)
- Company name and signature of responsible company representative
- Certification of slip resistance of all stepping, standing and walking surfaces.

If the apparatus has a fire pump or an industrial supply pump, the pump manufacturer's certification of suction capability.

If the apparatus has a fire pump or an industrial supply pump, a copy of the apparatus manufacturer's approval for stationary pumping applications.

If the apparatus has a fire pump or an industrial supply pump, the engine manufacturers certified brake horsepower curve for the engine furnished, showing the maximum governed speed.

If the apparatus has a fire pump or an industrial supply pump, the pump manufacturers certification of hydrostatic test.

If the apparatus has a fire pump or an industrial supply pump, the Underwriters Laboratory certification of inspection and test for the fire pump (if applicable).

If the apparatus has an aerial device the Underwriters Laboratory certification of inspection and test for the aerial device.

If the apparatus has an aerial device, all the technical information required for inspections to comply with NFPA 1911, Standards for Testing Fire Department Aerial Devices.

If the apparatus has a fixed line voltage power source, the certification of the test for the fixed power source (if applicable).

If the apparatus is equipped with an air system, test results of the air quality, the SCBA fill station, and the air system installation.

Weight documents from certified scale - showing actual loading on the front axle, rear axle(s) and overall vehicle (with the water tank full but without personnel, equipment and hose) shall be supplied with the complete vehicle to determine compliance with NFPA-1901.

Written load analysis and results of electrical performance tests.

If the apparatus is equipped with a water tank, the certification of water tank capacity by the tank manufacturer.

The chassis shall be certified by the apparatus manufacturer as conforming to all applicable Federal Motor Vehicle Safety Standards in effect at the date of contract. This shall be attested to by the attachment of a FMVSS certification label on the vehicle by the contractor who shall be recognized as the responsible final manufacturer.

**VEHICLE RECORDS**

The successful bidder shall be responsible for preparing and maintaining a record file of parts and assemblies used to manufacture the apparatus. These records shall be maintained in the factory of the bidder for a minimum of twenty (20) years. File shall contain copies of any and all reported deficiencies, all replacement parts required to maintain the apparatus, and original purchase documents including specifications, contract, invoices, incomplete chassis certificates, quality control reports and final delivery acceptance documents. The Borough of Berwick shall have access to any and all documents contained in this file upon official written request.

**BIDDER INSTRUCTIONS**

Bids shall be addressed and submitted in accordance with the advertised "Bid Notice". The words "Fire Apparatus Bid", the date, and the bid opening time must be stated on the face of the bid envelope. It is the bidder's responsibility to see that their proposals arrive on time. Late proposals, telegram, facsimile or telephones bids shall not be considered.

Each bid shall be accompanied by a detailed description of the apparatus and equipment it proposes to furnish. It is the intent of these specifications to cover the furnishing and delivery of a complete and soundly engineered apparatus equipped as specified. Minor details of construction and materials, where not otherwise specified, are left to the discretion of the contractor, who shall be solely responsible for the design and construction of all features.

Brand names or model numbers have been specified for some items. These have been carefully selected because of their reliability and availability for replacement locally. In order to be most responsive, items named, or an item "equal to" the particular item specified by brand name or model, should be contained in the bid proposal. It is the bidder's responsibility to prove to the Borough of Berwick that an item bid as "equal to" a particular specified item, is truly of equal quality, design, and function. The Borough of Berwick maintains the right to make a final decision as to the acceptability of an item bid as "equal to" a particular specified item.

No exception shall be allowed for any of the aforementioned instructions. Bids not submitted in accordance with these instructions shall be rejected.

**"TOP OF THE LINE" CHASSIS**

Bidders shall propose a custom built chassis, which is "Top of the Line" and includes an integrated multiplexed electrical system. NO EXCEPTIONS!

**TIMELY PROPOSALS**

It is the bidder's responsibility to see that their proposals arrive on time. Late proposals, facsimiles, telegrams, or telephone bids shall not be considered.

Bidder Complies	
YES	NO

**GENERAL CONSTRUCTION**

The complete apparatus, assemblies, subassemblies, component parts, etc., shall be designed and constructed with the due consideration to the nature and distribution of the load to be sustained and to the general character of the service to which the apparatus is to be subject. All parts of the apparatus shall be designed with a factor of safety, which is equal to or greater than that which is considered standard and acceptable for this class of equipment in fire fighting service. All parts of the apparatus shall be strong enough to withstand general service under full load. The apparatus shall be so designed that the various parts and readily accessible for lubrication, inspection, adjustment and repair. Bidder's specifications must meet minimum requirements of N.F.P.A. Pamphlet #1901; Underwriters Laboratories, Inc.; and all State and Federal Department of Transportation vehicle regulations at time of sale of unit.

The apparatus shall be designed and constructed, and the equipment so mounted, with due consideration to distribution of the load between front and rear axles that all specified equipment, including a full complement of specified ground ladders, full water tank, loose equipment, and firefighters shall be carried without overloading or injuring the apparatus.

**PRODUCT LIABILITY INSURANCE**

Each bidder shall supply proof of product liability and facility insurance equal to or exceeding \$30,000,000.00. This shall be provided as part of the proposal.

**SINGLE-LINE RESPONSIBILITY**

Since the Borough of Berwick desires to eliminate divided responsibility on the part of the manufacturers, only manufacturers who build their own fire apparatus cab, chassis, body and aerial device shall be considered. The apparatus must be built and painted in a facility owned and operated by the bidder by a staff that is directly employed by the bidder. At least fifteen similar units must have been sold and delivered of the type described herein. The entire apparatus (to include cab, chassis, body, pump, water tank and aerial device) MUST be manufactured in the United States! NO EXCEPTION SHALL BE ALLOWED TO THIS REQUIREMENT!

The bidder shall state if single line responsibility is being proposed.

Yes/No: \_\_\_\_\_

**PAINT PERFORMANCE CERTIFICATION**

The finish paint shall be certified by the apparatus manufacturer as conforming to all applicable Commercial Vehicle Paint Standards in effect at the date of contract. This shall be attested to by the attachment of a PPG certification.

**SERVICE CENTER AND PARTS DEPOT**

The manufacturer shall have an authorized service center, with a staff of factory-trained mechanics, well versed in all aspects of service for all major components, of the apparatus within a 300-mile radius of the Purchaser. In addition, the manufacturer shall maintain a separate service facility at the manufacturing site, in order to satisfy the need for possible major emergency service work.

**SERVICE CENTER INFORMATION**

The center must provide a full time staff of experienced technicians with all of the required equipment to provide modern, accurate and efficient service. Bidders shall state the size of their shop and officer area in square feet. They shall state the location of the facility and provide photos of both the exterior and interior of the center. Accuracy of the description of the service center is of great importance.

**SPECIAL CONDITIONS**

No bid shall be considered unless the bidder can meet the special conditions stated herein.

The complete apparatus must be manufactured in the United States of America.

**PRICES AND PAYMENTS**

The bid price shall be F.O.B. Destination, on a delivered and accepted basis at the Fire Department.

Total price on bidder's proposal sheet must include all items listed in these specifications. Listing any items contained in the specification as an extra cost item, unless specifically requested to do so in these specifications, shall automatically be cause for rejection.

Bidder shall compute pricing less federal and state taxes. It is understood that any applicable taxes shall be added to the proposed prices, unless the purchaser furnishes appropriate tax-exempt forms.

**BID EVALUATION**

Purchaser, Fire Chief and Purchasing Agent shall evaluate bids received. This evaluation shall be based as a minimum on the following criteria:

- Commitment for expedient delivery.
- Commitment to the general conditions contained herein, including warranty.
- Completeness of the proposal, i.e. the degree that it responds to all requirements and requests for information contained herein.
- Manufacturing and delivery schedule.
- Contractor's demonstrated capabilities and qualifications.
- Equipment suppliers and/or local representative's demonstrated capabilities and qualifications.

**EXCEPTIONS TO SPECIFICATIONS**

Exceptions shall be referenced to the paragraph and page of these specifications where the item appears. Drawings, photographs, and technical information about the exception shall be included as necessary. Any exceptions may be considered during the evaluation process, and the decision shall be final.

Proposals taking total exceptions to specifications shall not be accepted.

**"OR APPROVED EQUAL" CLAUSE**

The mention in the specifications of apparatus, equipment or material by brand name or by such specified description of same as is hereby made, is intended to convey to the bidder's understanding, the degree of excellence required. Any article, equipment, or material, which shall conform to the standards and excellence so established, and is of equal merit, strength, durability and appearance to perform the desired function, is deemed eligible for offer as a substitute. The qualifications of the offering shall be judged as to their conformance with these specifications. Any equipment offered other than herein specified shall be subject to a competitive demonstration and evaluation shall be subject to a competitive demonstration and evaluation by the using department. Such demonstration to be provided on request within ten working days after the receipt of bids.

The result of that demonstration and evaluation shall be of prime importance in the recommendation to the governing body for the final contract award.

**TECHNICAL INFORMATION**

Bidder shall furnish free of charge, upon request, technical information, graphs, charts, photographs, engineering diagrams, steering geometry, drive train certifications, instruction guides, or other documentation as requested to show that the equipment offered fully complies with these specifications.

**PROPRIETARY PARTS**

It is the intention of the Purchaser for all bidder's to furnish the apparatus with major parts commonly used by the heavy-duty truck manufacturers and open market vendors where as replacement parts are more readily available and at reduced cost. The use of proprietary parts such as but not limited to axles, suspensions, engines, transmissions, frontal air bags, electronic controls, multiplexing systems, seats, pumps, gauges, foam systems, etc., may not be acceptable by the purchaser.

**DELIVERY TIME**

Each bidder shall state the completed apparatus delivery time based on the number of calendar days, starting from the date the sales contract is signed and accepted by the apparatus manufacturer.

Delivery Time: \_\_\_\_\_ Calendar days

**FAIR, ETHICAL AND LEGAL COMPETITION**

In order to ensure fair, ethical, and legal competition, neither original equipment manufacturer (O.E.M.) nor parent company of the O.E.M. shall have ever been fined or convicted of price fixing, bid rigging, or collusion in any domestic or international fire apparatus market.

**MATERIAL AND WORKMANSHIP**

All equipment furnished shall be guaranteed to be new and of current manufacture, to meet all requirements of these specifications.

All workmanship shall be of high quality and accomplished in a professional manner so as to insure a functional apparatus with a pleasing, aesthetic appearance.

**CONTRACT SPECIALIST**

The successful bidder shall designate a contract specialist to provide a single point interface between the purchaser and the contractor on all matters concerning the contract.

**APPROVAL DRAWING**

A detailed drawing of the apparatus shall be provided to the purchaser for approval before construction begins. A copy of this drawing shall also be provided to the manufacturer's representative. Upon purchaser's approval, the finalized drawing shall become a part of the total contract.

The drawing shall show, but is not limited to, such items as the chassis make and model, major components, location of lights, sirens, all compartment locations and dimensions, special suction, discharges, etc. The drawing shall be a visual interpretation of the apparatus as it is to be supplied.

**INSPECTION VISITS**

The successful bidder shall provide three (3) factory inspection trips to the apparatus manufacturer's facility. Transportation, meals, lodging, and other requisite expenses shall be the bidder's responsibility.

Accommodations shall be for one (1) Fire Department representative per trip.

The factory visits shall occur at the following stages of production of the apparatus:

- Pre-construction / blueprint review.
- Midpoint completion of entire apparatus.
- Final inspection upon completion.

Travel arrangements more than 1000 miles from the manufacturing facility shall be via commercial airline transportation.

The Borough of Berwick maintains the right to inspect the apparatus, within normal business hours, at any other point during construction. Expenses incurred during non-specified inspection visits shall be the responsibility of the Borough of Berwick.

During inspection visits, the Borough of Berwick reserves the right to conduct actual performance tests to evaluate completed portions of the unit. Testing shall be accomplished with the assistance and resources of the contractor.

**DELIVERY, DELIVERY ENGINEER, AND TESTING**

Delivery of the apparatus to the Borough of Berwick shall remain the bidder's responsibility.

On initial delivery of the fire apparatus, a qualified and responsible representative of the contractor shall demonstrate the apparatus and provide initial instruction to representatives of the customer regarding the operation, care, and maintenance of the apparatus and equipment supplied.

**INSTRUCTION MANUALS/DRAWINGS, SCHEMATIC**

In accordance with standard commercial practices, applicable to each vehicle (including body and special equipment) furnished under the contract, the following listed manuals and schematics, in the quantity specified, shall be provided at time of delivery of each vehicle.

The contractor shall supply at time of delivery, two (2) CD copies of a complete operation and service manual covering the complete apparatus as delivered and accepted.

The manual shall contain the following:

- Descriptions, specifications, and ratings of chassis, pump (if applicable), and aerial device.
- Wiring diagrams.
- Lubrication charts.
- Operating instructions for the chassis, any major components such as a pump and any auxiliary systems.
- Instructions regarding the frequency and procedures recommended for maintenance.
- Parts replacement information.

**"AS BUILT" WIRING SCHEMATICS**

In accordance with standard commercial practices, the manufacturer shall supply two (2) copies of "AS BUILT" wiring schematics/diagrams for the entire vehicle at the time of delivery.

**"AS BUILT" PLUMBING SCHEMATICS**

In accordance with standard commercial practices, the manufacturer shall supply two (2) copies of "AS BUILT" plumbing schematics/diagrams for the pumping system at the time of delivery.

**VEHICLE FLUIDS PLATE**

As required by NFPA-1901, the contractor shall affix a permanent plate in the driver's compartment specifying the quantity and type of the following fluids used in the vehicle:

A permanent plate in the driving compartment shall specify the quantity and type of the following fluids used in the vehicle:

- Engine oil
- Engine coolant
- Chassis transmission fluid
- Pump transmission lubrication fluid
- Pump primer fluid
- Drive axle(s) lubrication fluid
- Air-conditioning refrigerant
- Air-conditioning lubrication oil
- Power steering fluid
- Cab tilt mechanism
- Transfer case fluid
- Equipment rack fluid
- Air compressor system lubricant
- Generator system lubricant
- Aerial systems

**PENNSYLVANIA STATE VEHICLE INSPECTION**

The completed vehicle should include an annual safety inspection sticker on the windshield as required by the Pennsylvania Department of Transportation.

**PRIMARY PLANT CONSTRUCTION**

In order to insure top quality construction, maximum assembly line and engineering communication and the highest level of manufacturing supervision the entire apparatus shall be built at the bidders' primary (headquarters) manufacturing facility. Apparatus constructed at satellite plants will not be considered.

**REQUIRED PROPOSAL BLUEPRINT**

A scale drawing of the specific apparatus being proposed shall be submitted WITH THE BID. Drawings of similar units or demo units shall not be permitted. Bidders should be clear that this provision is requiring a SCALE drawing of the truck which is actually being bid. The drawing shall be done at the manufacturer's facility by the manufacturer's engineering department in order to guarantee the accuracy of the drawing. Failure to comply with this requirement shall be grounds for rejection of the bid!

**FAMA COMPLIANCE**

The apparatus manufacturer must be a current member of the Fire Apparatus Manufacturer's Association (FAMA).

**U.S.A. MANUFACTURER**

The entire apparatus shall be assembled within the borders of the Continental United States to insure more readily available parts (without added costs and delays caused by tariffs and customs) and service.

**QUALITY MANAGEMENT**

The manufacturer shall operate a Quality Management System that is certified to ISO 9001 by an organization that is accredited by the ANSI-ASQ National Accreditation Board (ANAB). This type of business management system shall allow the manufacturer to monitor processes to ensure they are effective; keep adequate records; check output for defects, with appropriate and corrective action where necessary; regularly review individual processes and the quality system itself for effectiveness; and facilitate continual improvement.

A copy of the registration certificate must be included in the proposal, NO EXCEPTIONS.

**TABLE OF CONTENTS**

As all manufacturers present their specifications in a different order, each manufacturer shall provide a table of contents for ease of bid comparison and to clearly locate all proposed items.

**STEPPING, STANDING, & WALKING SURFACES**

All stepping, standing, and walking surfaces on the body shall meet NFPA #1901 anti-slip standards. Aluminum tread plate utilized for stepping, standing, and walking surfaces shall be Alcoa No-Slip type. This material shall be a minimum 3/16 (0.1875") in thickness. Upon request by the purchaser, the manufacturer shall supply proof of compliance with this requirement. All vertical surfaces on the body, which incorporate aluminum tread plate material, will utilize the same material pattern to provide a consistent overall appearance.

**AMP DRAW REPORT**

The bidder shall provide with their bid proposal and at the time of delivery, an itemized print out of the expected amp draw of the entire vehicle's electrical system.

A written load analysis, which shall include the following:

- The rating of the alternator.
- The minimum continuous load of each component that is specified per: Applicable NFPA-1901.
- Additional loads that, when added to the minimum continuous load, determine the total connected load.
- Each individual intermittent load.

All of the above listed items shall be provided by the bidder per the applicable NFPA-1901.

**COOPERATIVE PURCHASING**

The Manufacturer shall be pleased to allow other public agencies to use the purchase agreement resulting from this invitation to bid unless the bidder expressly notes on the proposal form that prices are not available for tag-on. The condition of such use by other agencies shall be that any such agency must make and pursue contact, purchase order/contract, and all contractual remedies with the successful bidder. Such tag-ons shall be done so that the original purchasing agency has no responsibility for performance by either the manufacturer or the agency using the contract.

**BIDDERS AFFIDAVIT**

**Bidders Name:**

**Address:**

I, \_\_\_\_\_ as the authorized agent for \_\_\_\_\_ do hereby swear and affirm that the following information is true and that the proposal that our firm is submitting complies with all the General Instructions, Requirements, and Specifications contained in this Bid Package, except where indicated below.

1. The apparatus offered is manufactured in North America:
2. The apparatus proposed is not a prototype:
3. The performance tests shall be performed in compliance with the specifications:
4. All pages of the General Instructions, Requirements, and Specifications have been received and reviewed:
5. All questionnaires and blanks have been completed and filled in:
6. Bid Bond is enclosed:
7. Bidder complies with Specifications without Exception:
8. Bidder complies with Design Criteria:
9. Bidder has included Apparatus Drawings per Specifications:
10. Apparatus proposed complies with dimensional requirements:
11. Does the Manufacturer provide a program for the familiarization of the fire department:
12. Does the manufacturer meet the \$30,000,000.00 product liability insurance requirement:
13. Are all specified warranties included:
14. Are all proposed warranties in compliance with specifications:
15. Body structure covered by a \_\_\_\_\_ month warranty:
16. Body sub frame covered by a \_\_\_\_\_ month warranty:
17. Cab structure covered by a \_\_\_\_\_ month warranty:
18. Paint covered by a \_\_\_\_\_ month warranty:
19. Aerial device covered by a \_\_\_\_\_ month structural warranty:
20. Chassis frame rails and cross members covered by a "lifetime" warranty:
21. Are the proposed apparatus and equipment new in all respects:
22. Is a complete copy of the bidders detailed proposal included:
23. Is a separate sheet of exceptions attached:

24. Service Ability form completed and attached:

25. State the dimensions of the proposed apparatus:

- Overall Height: \_\_\_\_\_
- Overall Length: \_\_\_\_\_
- Overall width: \_\_\_\_\_

26. Is the proposed device proof load tested as required in these specifications:

27. Is the manufacturer a sole source manufacturer, including the entire; chassis, cab, body and aerial device:

Delivery of the apparatus shall take place within \_\_\_\_ calendar days after the execution and acceptance of a contract.

Manufacturers Name: \_\_\_\_\_

Address: \_\_\_\_\_

Contact Person for Questions Regarding Bid: \_\_\_\_\_

Phone Number: \_\_\_\_\_ Fax Number: \_\_\_\_\_

Name of Authorized Agent: \_\_\_\_\_

Signature of Authorized Agent: \_\_\_\_\_

Date: \_\_\_\_\_

**UNDERWRITERS LABORATORIES INC. (UL) EXAMINATION AND TEST PROPOSAL**

If required by the specific chapters of NFPA-1901, the proposed unit shall be tested and certified by Underwriters Laboratories Inc. (UL) Underwriters Laboratories Inc. (UL) is recognized worldwide as a leading third party product safety certification organization for over 100 years. UL has served on National Fire Protection Association (NFPA) technical committees for over thirty years.

**INDEPENDENT TESTING ORGANIZATION QUALIFICATIONS**

- UL is a nationally recognized testing laboratory recognized by OSHA.
- UL complies with the American Society for Testing and Materials (ASTM) Standard ASTM E543 "Determining the Qualifications for Nondestructive Testing Agencies."
- UL has more than 40 years of automotive fire apparatus safety testing experience and 16 years of factory aerial device testing and Certification experience. UL has more than 100 years of experience developing and implementing product safety standards.
- UL does not represent, is not associated with, nor is in the manufacture or repair of automotive fire apparatus.
- All test work for fire pumps outlined in NFPA 1901, Edition shall be conducted.
- UL has included a list of all factory aerial device manufacturers for whom testing is currently being conducted on a regular basis.
- UL carries ten million dollars in excess liability insurance for bodily injury and property damage combined.

UL provides the manufacturer a complete written examination and test report for each inspection performed at the manufacturer's facility. This report specifies the points of inspection and results of such examinations and tests.

The UL inspectors performing the test work on the units are certified to Level II in the required NDT methods, under the requirements outlined in ASNT document CP-189.

**Header Title**

Bidder Complies

YES

NO

The actual person(s) performing the inspection shall present for review proof of Level II Certification in the required NDT methods.

The apparatus manufacturer shall designate, in writing, who is qualified to witness and certify these test results.

Prior to submittal to the automotive fire apparatus manufacturer, the final Report shall be reviewed by the Supervisor of Fire Equipment Services and a Registered Professional Engineer, both of whom are directly involved with the aerial device certification program at UL.

When the unit successfully meets all the requirements outlined in NFPA 1901, 2016 Edition, UL shall issue a Certificate of Automotive Fire Apparatus Examination and Test stating the unit's compliance with NFPA- 1901.

**GENERAL APPARATUS DESCRIPTION "PUMPER"**

The unit shall be designed to conform fully to the "Pumper Fire Apparatus" requirements as stated in the NFPA 1901 Standard (2016 Revision), which shall include the following required chapters as stated in this revision:

- Chapter 1 Administration
- Chapter 2 Referenced Publications
- Chapter 3 Definitions
- Chapter 4 General Requirements
- Chapter 5 Pumper Fire Apparatus
- Chapter 12 Chassis and Vehicle Components
- Chapter 13 Low Voltage Electrical Systems and Warning Devices
- Chapter 14 Driving and Crew Areas
- Chapter 15 Body, Compartments and Equipment Mounting
- Chapter 16 Fire Pumps and Associated Equipment
- Chapter 18 Water Tanks

**CAB SAFETY SIGNS**

The following safety signs shall be provided in the cab:

- A label displaying the maximum number of personnel the vehicle is designed to carry shall be visible to the driver.
- "Occupants will be seated and belted when apparatus is in motion" signs shall be visible from each seat.
- "Do Not Move Apparatus When Light Is On" sign adjacent to the warning light indicating a hazard if the apparatus is moved (as described in subsequent section).
- A label displaying the height, length, and GVWR of the vehicle shall be visible to driver.
- This label shall indicate that the fire department will revise the dimension if vehicle height changes while vehicle is in service.

**CHASSIS DATA LABELS**

The following information shall be on labels affixed to the vehicle:

Fluid Data

- Engine Oil
- Engine Coolant
- Chassis Transmission Fluid
- Pump Transmission Lubrication Fluid
- Pump Primer Fluid (if applicable)
- Drive Axle(s) Lubrication Fluid
- Air Conditioning Refrigerant
- Air Conditioning Lubrication Oil
- Power Steering Fluid
- Cab Tilt Mechanism Fluid
- Transfer Case Fluid (if applicable)
- Equipment Rack Fluid (if applicable)
- Air Compressor System Lubricant
- Generator System Lubricant (if applicable)
- Front Tire Cold Pressure
- Rear Tire Cold Pressure
- Aerial Hydraulic Fluid (if applicable)
- Maximum Tire Speed Rating

Chassis Data

- Chassis Manufacturer
- Production Number
- Year Built
- Month Manufactured
- Vehicle Identification Number

Manufacturers weight certification:

- Gross Vehicle (or Combination) Weight Rating (GVWR or GCWR)
- Gross Axle Weight Rating, Front
- Gross Axle Weight Rating, Rear

**ROLLOVER STABILITY**

The apparatus shall meet the criteria defined in 4.13.1 for rollover stability as defined in the 2016 NFPA Standard for Automotive Fire Apparatus.

**PRINCIPAL APPARATUS DIMENSIONS & G.V.W.R.**

The bidder shall include the principal dimensions, front G.A.W.R., rear G.A.W.R., and total G.V.W.R. of the proposed apparatus. Additionally, the bidder shall provide a weight distribution of the fully loaded, completed vehicle; this shall include a filled water tank, specified hose load, miscellaneous equipment allowance in accordance with NFPA-1901 requirements, and an equivalent personnel load of 250 lbs. per seating position.

**BIDDER TO SUPPLY AND FILL- IN PROPOSED DIMENSIONS:**

- OVERALL LENGTH: \_\_\_\_\_ "
- OVERALL WIDTH: \_\_\_\_\_ "
- OVERALL HEIGHT: \_\_\_\_\_ "
- WHEELBASE: \_\_\_\_\_ "

The axle and total weight ratings of the completed apparatus shall not be less than the following minimum acceptable weight ratings:

- MINIMUM FRONT G.A.W.R.: \_\_\_\_\_ lbs.
- MINIMUM REAR G.A.W.R.: \_\_\_\_\_ lbs.
- MINIMUM TOTAL G.V.W.R.: \_\_\_\_\_ lbs.

**SEAT BELT ANCHOR TESTING**

Each seat belt anchor shall be tested to withstand 3,000lbs of pull on both the lap and shoulder belt in accordance with FMVSS 210 section 4.2.

**SEAT MOUNTING TESTING**

Each seat mounting position shall be tested to withstand 20G's of force in accordance with FMVSS 207 section 4.2(c).

Both tests shall be performed and verified at a third party testing and evaluation center.

\*\*\*\* CAB AND CHASSIS \*\*\*\*

**CUSTOM**

- FULL TILT
- CONTOUR WINDSHIELD

The cab shall be a custom tilt style, built specifically for fire service. The cab shall be a cab over engine design, with integral tilt mechanism and engine access from inside the cab.

Cab shall be designed, fabricated, assembled in its entirety, and installed on the frame rails in the manufacturer's factory. This requirement will eliminate any split responsibility in warranty and service.

**OPEN SPACE DESIGN**

The cab interior shall be the "Open-Space" design with no wall, window or vertical support posts between the front and rear crew areas to allow direct communication, better visibility and air circulation in the cab.

**CAB MATERIAL - ALUMINUM**

The cab shall be fabricated from 5052-H 32 aluminum alloy, utilizing the minimum material thickness as follows:

- Cab side panels 0.125 thick (1/8")
- Cab roof 0.125 thick (1/8")
- Forward cab front sheet 0.125 thick (1/8")
- Interior cab panels 0.125 thick (1/8")
- Other panels 0.125 thick (1/8")
- Cab doors 0.1875 thick (3/16")
- Engine enclosure side panels 0.250 thick (1/4")

**CAB - BASE CONSTRUCTION**

Cab sub-frame shall be a welded assembly fabricated of 6063 structural aluminum alloy. This frame shall extend the full length and width of the cab and be secured to the chassis frame through two (2) rear urethane self centering load cushions, two (2) forward pivot brackets, and two (2) cab locks. The cab shall be of entirely welded construction.

The front cab wall shall be of double wall type construction, featuring an inner and outer panel.

**CRASH TESTING CERTIFICATION**

To ensure the safety of the cab occupants and cab integrity, proof of third party testing shall be provided. The cab shall be certified for SAEJ2422 side impact, SAEJ2420 with ECER29 cab front impact, and ECER29 cab roof strength.

Furthermore, proof of testing and certification shall be provided that the cab, in accordance to SAE J2420 was front impact tested at 2.1 times the standard energy required in SAE J2420, thus exceeding the NFPA requirement.

This test shall be performed with no support immediately behind the cab, thus providing an authentic test result.

**ROOF AND SIDE LOAD TESTING**

The cab design will include additional third party testing to ensure the safety of the cab occupants and cab integrity, proof of third party testing shall be provided. The cab shall be certified for SAEJ2422 side impact, SAEJ2420 with ECER29 cab front impact, and ECER29 cab roof strength.

The manufacturer shall provide proof that third party testing has been conducted to prove a static roof and a static side-load test has been completed. In these tests, a 120,000 pound static load was first applied to the roof. This test was followed by applying the same 120,000 pound static load to the side of the cab.

These tests will be conducted per the SAE J2422, Cab Roof Strength Evaluation, protocol and the ECE R29, Uniform provisions concerning the approval of vehicles with regard to the protection of occupants of the cab of a commercial vehicle, protocol.

During both tests, the cab will withstand these loads without encroachment into the occupant survivable space and all doors remained closed during the test. The tests will be documented with photographs and real-time video in a report provided to the manufacturer.

**DIMENSIONS - LONG FOUR DOOR STYLE CAB**

Minimum Cab Dimensions:

- Overall width 100"
- Inside width across ceiling 92"
- Front area floor to ceiling 63"
- Top of front seat to ceiling 44" (depending upon seat type)
- Seat back to steering wheel 22" (depending upon seat type)
- Inside width (door to engine enclosure) 24" (driver's side, at floor)
- Inside width (door to engine enclosure) 20-1/2" (officer's side, at floor)
- Crew seat area width 92"
- Outer crew seat risers to rear wall 54"
- Centerline front axle to back of cab 74-1/2"
- Floor to top of engine enclosure 41-1/2"
- Centerline axle to front of cab 74"

Glass Area Dimensions:

- Windshield (Contour) 3,422 sq. in.
- Front door window, retractable 743 sq. in. each
- Rear door window, retractable 875 sq. in. each
- Fixed side windows 620 sq. in. each

Cab Entry Door Width Dimensions

- Forward door opening 40" wide
- Rear door opening 37" wide

Cab Entry Step Dimensions

- Forward door recessed step 32" wide x 9" deep
- Rear door recessed step 32" wide x 9" deep

Cab Entry Door Height Dimensions

- Forward door opening 76-1/4" high
- Rear door opening 91-1/4" high

**CAB ROOF**

The roof will be of a split level design with radius edges for an aesthetic, streamline appearance. The roof be constructed the same material as the main structure and be internally reinforced using framing which span the entire width and length of the cab for maximum structural integrity. This shall allow the roof to support personnel and roof mounted equipment without the need for additional reinforcement.

The cab roof over the rear crew area shall be raised sixteen (16) inches higher than the front driver and officer area. The front face of the raised roof section shall be sloped at a 45 degree angle, creating a streamlined interface with the standard, lower, forward roof section. This design shall allow for additional interior height in the rear crew area.

The rear crew area doors shall be "Vista-Style", extending full height to the radius edge of the raised roof.

Approximate dimensions:

- Crew area floor to ceiling 70"
- Top of crew seat to ceiling 52" (depending upon seat type)

**CAB ROOF DRIP RAIL**

For enhanced protection from inclement weather, an integral drip rail shall be furnished on each side of the cab roof. The drip rail shall extend the full length of the cab roof.

**STEPWELL BATTERY ACCESS DOOR**

The battery access door(s) shall be 1/8" aluminum tread plate, drop down door with lift and turn latches at the rear drivers side cab step well.

**CAB DOORS**

Four (4) side-opening doors shall be provided. The cab doors shall be totally aluminum construction with an extruded aluminum frame and an aluminum outer door skin. Doors shall be full height from the step to the cab roof extrusion and enclose the step area when the doors are closed.

The forward cab door opening shall be a minimum of 40" wide, and the rear cab door opening shall be a minimum of 37" wide. The rearward cab doors shall have a radius cutout allowing the door opening to protrude forward over the cab wheel well, while providing full access to the rear crew area.

There shall be a heavy duty piano type stainless steel hinge on each door with a minimum pin diameter of 5/16". Hinges shall be slotted for ease of horizontal and vertical adjustment. There shall be a cab door seal and the doors shall close flush with the side of the cab. A heavy-duty 2 1/2" wide reinforced rubber strap shall be utilized to prevent the cab doors from opening greater than 90 degrees.

**ENTRY STEP AREA**

Each of the forward entrance steps shall be a minimum of 8-1/2" deep with the floor board recessed a minimum of 5" to avoid "shin knocking". Each step shall be a bolt-in cast aluminum step.

Each of the rear entrance steps shall be a minimum of 8-1/2" deep. An intermediate step shall be provided between the lower entrance step and the crew area floor for ease of entry and egress. Each step shall be fabricated as an integral part of the cab construction. The cab step risers shall be painted to match the cab exterior color.

Each lower step shall be a bolt-in cast aluminum step.

**DOOR LATCHES**

A semi-recessed chrome plated pull handle, capable of operating with a gloved hand, shall be provided on the exterior of each cab door. Heavy-duty, bright finish cast paddle latches shall be provided on the interior of each cab door. Door latch mechanisms which utilize spring steel clamps shall not be considered due to their tendency to both rust and break. The interior door latch cables are to be designed to reduce adjustment or possible wear at the adjustment turnbuckles.

**LOCKING CAB DOORS**

Each exterior cab door shall be equipped with keyed locks. The cab doors shall be capable of being locked from the outside with a key and from the inside with a control in each interior paddle latch.

The specified door lock cylinder/s shall be equipped with #2001 key/s.

**DOOR WINDOWS**

Each side cab door shall have a tinted retractable window operated by a hand crank mechanism. The window track shall be designed into the door frame extrusion, which shall be extruded with a track groove to house a window track and seal. The window shall be capable of being removed from an access slot designed in the bottom of the door frame.

**DOOR WINDOW TRIM**

Each side cab door window shall be designed with a custom extruded trim plate, which shall conform to the perimeter of the window opening in each door. The trim plate shall extend from the edge of the door skin to the window and shall have a silver anodized finish.

**INNER DOOR PANELS**

The cab door interior panels shall be covered with an aluminum panel, full height. The panel shall be 1/8" aluminum and painted with Line-X and shall be designed to allow easy access to the inner door.

The Line-X shall be black in color.

Each interior cab door panel shall be equipped with reflective ScotchLite material that shall cover at least 96 in<sup>2</sup>. The material shall be applied to an aluminum plate that shall be fastened to the door panel.

**EXTERIOR CAB TRIM**

A high luster stainless steel trim band shall be provided along the cab sides at 11.5" in height. Black vinyl trim molding shall be installed along the top and bottom of the trim band.

**EXTERIOR CAB COMPARTMENTS**

Two (2) compartments shall be provided, to the rear of the crew cab doors. The compartments shall be approximately 38" high, 9" wide and 27 3/4" deep. Compartment door shall have a 3/16" aluminum exterior skin door with a one (1) inch box pan and a stainless steel "D" ring handle. Door shall be hinged on the forward edge with a stainless steel vertical piano hinge so it opens toward the rear cab door. The door shall be held in the open position by a gas shock stay arm.

Each compartment shall contain a light for illumination of the compartment and shall be wired to a door jamb switch to automatically come on when the door is opened. The light shall be the same style that is used in the body compartments.

**WINDSHIELD/GLASS**

A two piece, symmetrical, safety glass windshield shall be provided on the cab for the driver and officer providing a clear viewing area. The windshields shall be full width to the center of the front cab support for each side and provide the occupants with a panoramic view. To provide enhanced peripheral vision on each side of the cab, the windshield and cab structure shall be designed with radius corners, which provide a minimum of 8" of glass area, measured from the glass face to the side edge near the door post. The windshield shall consist of three (3) layers; the outer light, the middle safety laminate and the inner light. The thick outer light layer shall provide superior chip resistance, the middle safety laminate layer shall prevent the windshield glass pieces from detaching in the event of breakage and the inner light shall provide yet another chip resistant layer.

The windshield will be a contour design with 3422 sq. in. of area for improved visibility and style. The windshield glass shall be designed so it can be used on either the driver or officer side. Single piece windshields that utilize epoxy or that are bonded to the cab structure shall not be acceptable.

**WINDSHIELD WIPERS AND WASHER**

Dual, electric operated, pantographic type windshield wipers shall be provided. One (1) electric drive motor shall be provided for each wiper.

Wipers shall have "HI/LO" and "INTERMITTENT" operating speeds. "HI/LO" speeds shall be controlled by a steering column control, within the turn signal control stem. "INTERMITTENT" operation shall be controlled by a twist switch within the control on the steering column. The wipers shall be of the self-parking type.

Windshield washers shall be electric operated wet-arm type with a 3/4 gallon washer fluid reservoir, mounted inside the engine enclosure and readily accessible through the engine hatch at the rear of the engine enclosure. The washer control shall be integral with the intermittent wiper control switch.

There shall be individual removable panels on the front face of the cab for access to the wiper motor assemblies.

**WINDSHIELD WIPER DURABILITY CERTIFICATION**

Windshield wipers shall survive testing in excess of 3 million cycles in accordance with section 6.2 of SAE J198 "Windshield Wiper Systems – Trucks, Buses and Multipurpose Vehicles". The bidder shall certify that the wiper system design has been "Third party tested" and that the wiper system has met this criteria.

**CAB SIDE VIEWING WINDOWS**

A fixed, tinted window with 620 sq. in of glass area shall be provided on each side of the cab behind the forward cab doors. This window will be the same height as the window in the rear cab door for maximum visibility.

**DARK TINTED REAR WINDOW GLASS**

The windshield and the forward cab door glass shall be provided with standard DOT green automotive tint. The side cab windows to the rear of the front doors, the rear cab door windows and any rear viewing windows shall be equipped with a dark automotive tint.

**GRAB HANDLES**

Four (4) 1-1/4" diameter x 28" long, knurled bright anodized aluminum handrails shall be provided, one (1) at each cab door entrance. Grab rail stanchions shall be chrome plated and offset when necessary to prevent "hand-pinching" when opening or closing the doors. Formed rubber gaskets shall be provided between each stanchion base and the cab surface.

**INTERIOR GRAB RAILS**

Grab rails shall be provided to assist in entry and exiting of the cab. Each grab rail shall be a cast aluminum "D" style handle that shall have a wheelabrated finish and shall be located in the following locations:

- One (1) 11" long, horizontally mounted, on each front cab door on the upper interior door panel
- One (1) 12" long, vertically mounted, on the officer's side "A" post
- One (1) 11" long, horizontally mounted, on each rear cab door on the interior door panel
- One (1) 30" long, horizontally mounted, on each rear cab door, located approximately 8" above the bottom of the window opening
- Three (3) 12" long, vertically mounted, one (1) on the driver's side cab interior on the "A" post and one (1) each side of the cab interior on the "C" post in the crew area

**STAINLESS STEEL FRONT CAB GRILL**

There shall be a mirror finished stainless steel, custom formed grille assembly for maximum air flow to the charge air cooler and the radiator. The grille shall be designed with an aesthetic look, with large horizontal louvers that will be reinforced to provide integrity.

The grill shall be a modular design to allow the sides or the individual louvers to be replaced if damaged.

A mesh bug screen shall be provided behind the front grill assembly to protect the radiator from bugs and other debris. The screen shall be secured to the front of the cab, behind the main grill.

**AIR INTAKE/OUTLET**

Two (2) shaped, mirror finished stainless steel air inlets/outlets shall be provided horizontally above the wheel well opening, one on each side of the cab. The grilles shall be equipped with a mesh screen to serve as a secondary ember separator. The design shall permit proper ducting of air through the engine compartment and cooling system.

**ENGINE AIR INTAKE SYSTEM**

The left side inlet, used for the air intake to the air cleaner, shall be equipped with dual ember separators for separating burning embers from the air intake system. This system shall be such that particles larger than .039 inches (1 mm) in diameter cannot reach the air filter element.

No part of the air intake system for the engine shall be lower than the top of the frame rails to ensure the vehicle can navigate pooled water without any part of the air intake system being exposed to water when the vehicle is stopped or in motion. Chassis designs, which the engine air intake system is lower than the frame rails shall not be acceptable!

A mesh screen shall be provided behind the side grill assembly to protect the intake from debris.

**CAB WHEEL WELL LINERS**

The front cab wheel wells shall be equipped with fully removable, bolt-in, aluminum inner wheel well liners. The liners shall extend full depth into the truck frame. The completely washable wheel well liners shall be designed to protect the cab substructure, inner panels, and other miscellaneous installed components from road salts, debris, dirt accumulation and corrosion.

**CAB FENDERETTES**

The cab wheel well openings shall be trimmed with replaceable, bolt-in, polished aluminum fenderettes. The fenderettes shall be secured to the cab with stainless steel threaded fasteners along the internal perimeter of the wheel well. Dissimilar metal tape and black vinyl trim molding shall be used where the cab and fender meet.

**FRONT MUD FLAPS**

Heavy duty, black rubber type mud flaps shall be provided behind the front wheels.

**RETRAC MIRRORS, HEATED, REMOTE CONTROLLED W/ INTEGRAL CONVEX**

Two (2) Retrac 613305 mirrors shall be furnished, one on each front cab door. Each mirror shall have a 14-1/2 x 8 flat glass upper head and a 4-1/2 x 8 convex lower head mounted in a one piece chrome plated housing. All heads shall be electrically heated. The upper flat glass portion as well as the lower convex section shall be electrically controlled from the driver's seating position.

The stainless steel loop mounting bar shall be installed on the forward portion of each front door in front of the side windows with an upper and lower mounting bracket.

**MIRROR CONTROLS**

To minimize wire circuits roughed from the dash to the door, the mirror position and heat (if applicable) controls shall be programmed into and controlled from the multiplex control screen.

**INTERIOR TRIM**

The cab interior shall be constructed to create an ergonomically designed interior to be user friendly and functional for the driver and officer.

The forward overhead panel shall be a fabricated aluminum module painted to match the interior. This module shall contain the integrated windshield defroster/heater.

The headliner and rear cab wall shall utilize gray Durawear material, with padding underneath, to provide additional insulation.

The interior metal surfaces of the cab shall be finish painted with black Line-X material.

**INTERIOR REAR WALL**

The interior rear wall of the cab shall be covered with grey durawear for durability and shall match the other areas of the cab.

**UNDER SEAT STORAGE COMPARTMENTS**

There shall be a compartment provided under each front seat. Each compartment shall be accessible from the front of the seat riser when the door is opened.

**BARYFOL FLOORING**

The floor of the driver's compartment and the floor of the crew area shall be lined with BARYFOL vinyl composite flooring to comply with NFPA noise and heat requirements.

**ENGINE ENCLOSURE**

The forward portion of the engine enclosure shall be covered with a three (3) piece ABS plastic module that shall be coated with Line-X to match the balance of the cab interior. To allow maximum "elbow room" for the driver and officer, the forward portion of the engine enclosure shall feature a contour shape. The engine enclosure shall not significantly obstruct the driver's vision in any direction. The enclosure shall be an integral part of the cab structure, which shall be constructed from material providing adequate strength to support radio, map boxes, etc. The engine enclosure shall be insulated to protect from heat and sound. The noise insulation shall keep the DBA level within the limits stated in the current NFPA series 1900 pamphlet.

A, hinged access door shall be provided in the top rearward portion of the engine enclosure. The door shall allow access to the engine oil, transmission fluid, power steering fluid level dipsticks and the windshield washer fluid reservoir. The access door shall be provided with two (2) flush mounted latches and gas shock holders. There shall be an ABS cover, that shall be coated with Line-X, over the access door to give a cleaner look to the top of the engine enclosure and doghouse area.

The enclosure shall be an integral part of the cab structure, which shall be constructed from a minimum of .25" 5052-H32 aluminum. This material shall be welded to the floor subframe on each side of the cab and shall extend from the very front of the cab to the rear of the engine enclosure.

The rear section of the engine enclosure shall be reduced 8-1/2" in length to provide additional leg room for the forward facing seating position/s.

**SUN VISORS**

To provide maximum protection for the driver and officer, two (2) dark polycarbonate sun visors shall be mounted in the cab overhead on each side.

\*\*\*\*\* CAB SEATING & ACCESSORIES \*\*\*\*\*

**DRIVERS SEAT**

The driver's seat shall be a H. O. Bostrom Sierra EX8 high back bucket ABTS LH seat. The seat shall have a tapered and padded seat cushion with lumbar support. The seat shall have an eight inch fore and aft adjustment, a 2 inch height adjustment, front of seat tilt, rear of seat tilt and a reclining seat back. All seat movements shall be electrically controlled from a control panel on the forward lower edge of the seat.

The seat shall be equipped with a red integrated 3-point shoulder harness with lap belt and an automatic retractor built into the seat assembly.

**OFFICERS SEAT**

The officer's seat shall be a H. O. Bostrom Tanker 450 ABTS RH series fixed base SCBA seat. The seat shall have a tapered and padded seat cushion with lumbar support. The seat shall include a SCBA storage area with integral headrest.

The seat shall be equipped with a red integrated 3-point shoulder harness with lap belt and an automatic retractor built into the seat assembly.

The officer's seat shall include a H. O. BOSTROM Secure All™ SCBA Locking System. The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the tank in-place for a safe and comfortable fit in seat cavity. Fire fighters shall simply push the SCBA unit against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The standard release handle shall be integrated into the seat cushion for quick and easy release and shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

**REAR FACING, OUTBOARD, DRIVER SIDE SEAT**

The driver's side outboard rear facing crew seat shall be a H. O. Bostrom Tanker 450 ABTS RH series fixed base SCBA seat. The seat shall have a tapered and padded seat cushion with lumbar support. The seat shall include a SCBA storage area with integral headrest.

The seat shall be equipped with a red integrated 3-point shoulder harness with lap belt and an automatic retractor built into the seat assembly.

The driver's side rear facing outboard seat shall include a H. O. BOSTROM Secure All™ SCBA Locking System. The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the tank in-place for a safe and comfortable fit in seat cavity. Fire fighters shall simply push the SCBA unit against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The standard release handle shall be integrated into the seat cushion for quick and easy release and shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

**REAR FACING, OUTBOARD, OFFICER SIDE SEAT**

The officer's side outboard rear facing crew seat shall be a H. O. Bostrom Tanker 450 ABTS LH series fixed base SCBA seat. The seat shall have a tapered and padded seat cushion with lumbar support. The seat shall include a SCBA storage area with integral headrest.

The seat shall be equipped with a red integrated 3-point shoulder harness with lap belt and an automatic retractor built into the seat assembly.

The officer's side rear facing outboard seat shall include a H. O. BOSTROM Secure All™ SCBA Locking System. The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the tank in-place for a safe and comfortable fit in seat cavity. Fire fighters shall simply push the SCBA unit against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The standard release handle shall be integrated into the seat cushion for quick and easy release and shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

**CENTER REAR FACING CREW SEATS**

Two (2) center inboard rear facing crew seats shall be provided. Each seat shall be a H. O. Bostrom Tanker 450 ABTS series fixed base SCBA seat and shall have a tapered and padded seat cushion with lumbar support.

Each seat shall include a SCBA storage area with integral headrest.

Each seat shall be equipped with a red integrated 3-point shoulder harness with lap belt and an automatic retractor built into the seat assembly.

The (2) Rear facing center crew seats shall have a flip-up style seat.

The center rear facing seats shall include a H. O. BOSTROM Secure All™ SCBA Locking System. The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the tank in-place for a safe and comfortable fit in seat cavity. Fire fighters shall simply push the SCBA unit against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The standard release handle shall be integrated into the seat cushion for quick and easy release and shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

**FORWARD FACING, OUTBOARD, DRIVER SIDE SEAT**

The driver's side outboard forward facing crew seat shall be an H. O. Bostrom Tanker 450 ABTS LH series fixed SCBA seat. The seat shall have a tapered and padded seat cushion with lumbar support. The seat shall include an SCBA storage area with integral headrest.

The seat shall be equipped with a red integrated 3-point shoulder harness with lap belt and an automatic retractor built into the seat assembly.

The driver's side outboard forward facing crew seat shall have a flip-up style seat.

The driver's side forward facing outboard seat shall include a H. O. BOSTROM Secure All™ SCBA Locking System. The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the tank in-place for a safe and comfortable fit in seat cavity. Fire fighters shall simply push the SCBA unit against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The standard release handle shall be integrated into the seat cushion for quick and easy release and shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

**FORWARD FACING, OUTBOARD, OFFICER SIDE SEAT**

The officer's side outboard forward facing crew seat shall be an H. O. Bostrom Tanker 450 ABTS series SCBA seat. The seat shall have a tapered and padded seat cushion with lumbar support. The seat shall include an SCBA storage area with integral headrest.

The seat shall be equipped with a red integrated 3-point shoulder harness with lap belt and an automatic retractor built into the seat assembly.

The officer's side outboard forward facing crew seat shall have a flip-up style seat.

The officer's side forward facing outboard seat shall include a H. O. BOSTROM Secure All™ SCBA Locking System. The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the tank in-place for a safe and comfortable fit in seat cavity. Fire fighters shall simply push the SCBA unit against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The standard release handle shall be integrated into the seat cushion for quick and easy release and shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

**CENTER FORWARD FACING CREW SEATS**

Two (2) center inboard forward facing crew seats shall be provided. Each seat shall be H. O. Bostrom Tanker 450 ABTS series fixed SCBA seat and shall have a tapered and padded seat cushion with lumbar support.

Each seat shall include an SCBA storage area with integral headrest.

Each seat shall be equipped with a red integrated 3-point shoulder harness with lap belt and an automatic retractor built into the seat assembly.

The two (2) center inboard forward facing crew seats shall have a flip-up style seat.

Each center forward facing seat shall include a H. O. BOSTROM Secure All™ SCBA Locking System. The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the tank in-place for a safe and comfortable fit in seat cavity. Fire fighters shall simply push the SCBA unit against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The standard release handle shall be integrated into the seat cushion for quick and easy release and shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

**FORWARD FACING CREW SEAT RISER**

The forward facing seats shall be mounted on a full width aluminum riser that shall be welded into the cab during cab construction. The riser shall match the interior of the cab and shall have open compartments with no doors.

**SEAT UPHOLSTERY MATERIAL**

The seats shall be upholstered with heavy duty gray tweed Durawear material as provided by Bostrom.

**SEAT BELT CUSHION SENSORS AND BELT SENSORS**

The apparatus shall be equipped with a Class 1 seat belt warning system. The system shall consist of a Seat Belt module and shall display the seating positions through the main UltraView screen.

Seat belt and seat cushion sensors shall be provided on the ten (10) specified seating positions.

**VEHICLE DATA RECORDER**

A Class 1 Vehicle Data Recorder (VDR) system shall be provided. The system shall include an NFPA compliant "Black Box" with reporting software that shall be capable of data storage to coincide with the NFPA requirements.

Data storage capabilities shall include interfaces with the following systems:

- Display module (Master Optical Warning Device)
- VDR, date & time stamp
- Max Vehicle speed (MPH)
- Vehicle acceleration / deceleration (MPH/Sec.)
- Engine Speed (RPM)
- ABS event
- Data password protected
- Data sampled once per second, in 48-hour loop
- Data sampled min by min for 100 engine hours
- Throttle position (% of Throttle)
- Data software
- PC / Mac Compatible
- Data summary reports

The VDR data shall be downloadable by USB cable to a computer using either Microsoft or Apple operating systems.

\*\*\*\*\* CAB INSTRUMENTATION & CONTROLS \*\*\*\*\*

**DASH & CENTER CONSOLE**

The driver and officer side dash, along with the center dash, shall be covered with a custom formed ABS overlay that shall be coated with Line-X. The Line-X color shall match the interior color of the cab to create an ergonomically designed interior to be user friendly and functional for the driver and officer.

The dash gauge panel shall be a custom formed ABS pewter gray wrap-around design for improved visibility. A full complement of gauges shall be provided in custom formed bezels. The starter and ignition switches shall also be integrated into the upper left portion of the gauge panel for easier access.

All warning lights and indicators shall be located in the gauge itself or in the lower center portion. Each gauge shall be equipped with an international symbol that is easily recognizable, denoting the system being monitored. Instrumentation shall be backlit for easy identification when activated.

The transmission gear selector shall be located on the left side of the center dash assembly, toward the driver for easy access.

There shall be provisions for mounting a switch panel in the center of the dash between the driver and officer. The top center of the dash assembly shall contain one (1) removable panel to access the main chassis wiring circuits and breaker panels.

**DRIVER'S DASHBOARD PANEL**

The main instrument panel shall be centered in front of the driver and shall be mechanically fastened to the main dash assembly. The panel shall be made of custom formed ABS that shall contain the primary gauges, an instrument warning light cluster and the ignition and engine start switches.

The main instrument panel shall contain the primary gauges. An ignition and engine start switch shall be located on a panel to the left upper portion of the driver's side dash panel.

Each gauge shall have a raised glass lens with a black matte finish trim ring and be backlit by integral white LED's. Each gauge shall also possess an integral red warning light with a pre-programmed warning light set point. Each gauge warning indicator shall be capable of activating an audible alarm inside the dashboard.

The primary gauges shall consist of:

- Vehicle speedometer (0-80 mph)
- Engine tachometer (0-3000 rpm)
- Engine oil pressure (0-100 psi); low oil pressure warning
- Engine coolant temperature (100-250 °F); high engine temp warning
- Transmission oil temperature (100-350 °F); high transmission fluid temp warning
- Vehicle battery voltage (9-18 VDC); low voltage warning
- Front air system gauge (0-150 psi); low air pressure warning at 65 psi
- Rear air system gauge (0-150 psi); low air pressure warning at 65 psi
- Fuel level (E - 1/2 - F); low fuel level warning
- Air cleaner restriction gauge (0-40), warning at 25"

Additional auxiliary control switches and instruments (if applicable) shall be located within the dash panel and overhead panel located near the driver's position.

- Diesel Exhaust Fluid level (E-1/2-F); low fuel level warning @ 1/8 tank
- Engine Compression Brake Controls

**CLASS 1 DISPLAY**

An UltraView 450 4.3" display shall be provided on the dash for the electrical Class One ES-Key multiplex system. The exact location shall determined by the totality of instruments and switches on the cab dash. The display shall be in easy reach of the officer to view information.

**INDICATOR CLUSTER**

The driver's dashboard panel shall consist of Ametek gauges, an 18 item instrument warning light cluster and a 16 item, dead front type alarm panel.

This display shall contain the system control unit that collects data from the vehicle data bus (J1939), analog sensors, and switches throughout the vehicle. This data shall be presented using gauges, telltales and the two (2) display panels. The warning light display shall include a 2 x 20 dot matrix display, 18 telltales and 2 buttons to navigate through the screen menus.

The LCD dot matrix display shall be a 2 line by 20-character display with each character being 7 dot by 5 dot configuration. FSTN technology shall be used on the display for wide viewing capability. The module shall be backlit with amber LED's. The unit shall also be supplied with a heater to ensure proper operation over the entire 40 to +85 deg. C.

This display contains a series of two (2) screens to provide information about the vehicle. To control the display of that information, the screens are divided into two (2) menus; one that can be displayed while the vehicle is in motion and one that can only be accessed when the parking brake is set.

On the Road displays include:

- Two (2) configurable displays that can show any of the parameters the unit collects. This includes odometer, trip information, fuel economy information; all gauge data, and virtually any other data available on the vehicle that the display has access to, either through the data bus or via analog inputs.
- Two (2) trip displays for miles and hours that are capable of being reset.
- Two (2) fuel data screens: shall be provided; one for fuel remaining until empty and one for fuel economy. The fuel economy display shall be capable of being reset so that average economy over a predetermined period can be displayed.

The displays that can be accessed when the parking brake is set include:

- Engine hours as maintained by the engine ECU
- Service Alarm screens to report miles to next service or miles past required service. These screens shall allow the operator to choose the length of the service interval and shall have the ability to reset it.
- Message screens with warning messages the display has collected during the current ignition cycle. These screens shall be divided into configured warnings such as "Low Air Pressure" and the data bus faults reported by ECU's on the vehicle. Both lists shall allow the operator to review the last 12 events that occurred on the vehicle for maintenance and troubleshooting purposes.
- Diagnostic screens shall test the instrumentation system to verify it is working correctly.
- Setup screens shall be used to select either English or metric display. They shall also allow the operator to choose the data that shall be displayed by the configurable on-the-road screens.

The system shall be configured with user defined warning messages such as Low Air Pressure or High Coolant Temperature. When these events occur the warning message shall

come up on the screen and can be accompanied by a buzzer. The messages shall be prioritized so the most important messages are always displayed. Whether the message can be dismissed by pressing a button shall be configurable. Messages that have been dismissed but are still active shall be retained in the message screens for review until the ignition is turned off. Listed below are the defined telltales and their indicators.

- "Right And Left Directional" arrows (green in color)
- "Ignition ON" Indicator (amber in color)
- "Hi Beam" indicator (blue in color)
- "Battery ON" indicator (green in color)
- "Parking Brake ON" indicator (red in color)
- "Check Transmission" indicator (amber in color)
- "Cab Not Latched" indicator (red in color)
- "Stop Engine" indicator (red in color)
- "Check Engine" indicator (amber in color)
- "ABS Warning" indicator (red in color)
- "Low Coolant Level" (red in color)
- "Fuel Restriction" indicator (amber in color)
- "Water In Fuel" indicator (amber in color)
- "Fasten Seat Belts" indicator (red in color)
- "Fast Idle" Indicator (amber in color)
- "Do Not Move Truck" indicator (red in color)
- "DPF Regeneration" (amber in color)
- "Exhaust High Temperature" (amber in color)
- "Engine Diagnostic Fault" (amber in color)
- "Retarder On" (green in color)

Listed below are indicators that may be included, depending upon the vehicle configuration:

- "Wait To Start" indicator (amber in color)
- "Exhaust System Fault" (amber in color)
- "Topps System Fault" (amber in color)
- "Lube System Active" (amber in color)
- "Jacks Not Stowed" (red in color)
- "PTO Engaged" (green in color)
- "Inter Axle Lock" (amber in color)
- "Driver Controlled Diff Lock" (green in color)
- "Ok to Pump" (green in color)
- "Auto Traction Control" (amber in color)
- "Retarder Active" (amber in color)
- "Auxiliary Brake Active" (amber in color).
  
- "ATC Disabled" indicator (red in color)
  
- "ATC Active" indicator (yellow in color)

**AUXILIARY SWITCH PANEL - LOWER DASH AREA**

An auxiliary lower dash panel shall be capable of housing five (5) guarded type rocker switches. Examples of the switches that shall be installed in this area are automatic chains, fan clutch override, ATC, inter-axle diff lock, electric fuel pump, all wheel drive, etc

This panel location shall take the pump shift panel location into consideration for optimum location of both.

**PUMP SHIFT CONTROL**

The pump shift control and pump engaged indicator light shall be mounted in the driver's lower left panel.

The pump shift control (will/shall) be a Mil Spec toggle switch with mechanical detents mounted in a fully backlit panel that (will/shall) have indicators for "Pump Engage" and "Ok To Pump". The mode of the transfer solenoids (will/shall) be controlled by remotely mounted air solenoids which (will/shall) be activated and monitored through the chassis control logic of the multiplex system.

**OFFICER DASH**

There shall be a flat surface area in front of the officer for use with such items as a lap top computer.

**CAB HEATER/DEFROSTER**

A SGM heater/defroster, rated at 45,200 BTU/HR shall be provided, with a minimum 350 CFM total air flow. The unit shall supply heat to the cab and provide windshield defrosting through adjustable louvers. The heater/defroster shall be mounted in the center overhead console area near the windshield. Controls shall be located on the front of the heater/defroster unit.

**PANTHER OVERHEAD AIR CONDITIONING SYSTEM**

A climate-control system shall be provided for total cab environmental comfort. This system shall be able to provide heat and cooling capabilities to various areas in the cab. The system shall consist of one (1) evaporator unit mounted in the center overhead of the cab and a roof mounted condenser. This system shall provide conditioned air for the front and rear area of the cab.

The ceiling mounted evaporator/heater unit shall include the following:

- Dual high output blower.
- High efficiency coil that includes "rifled" tubing and oversized header tubes for maximum refrigerant distribution.
- Eight (8) adjustable 3" diameter louvers shall be furnished; four (4) louvers located in the forward area of the cover and four (4) louvers located in the rear for the crew area.
- An electric water valve in the heat mode controls temperature.
- Unit housing is fully insulated.
- Heating BTU: 50,000
- Air Conditioning BTU: 34,000
- CFM: 410 @ 13.8 volts.

**ROOF MOUNT CONDENSER**

A 12-volt, roof top, single condenser shall be strategically positioned on the cab roof so as not to interfere with any emergency lighting systems and shall include the following:

- High performance, long life fan assemblies. Fan motors are sealed around housing and shaft areas.
- Condenser and coil design includes rifled tubing for maximum efficiency. Coil is painted black.
- Condenser unit includes receiver drier with hi/lo pressure switch.
- Wire harness includes necessary wiring for clutch circuit as well as a separate power relay circuit.
- 14-gauge mounting brackets
- 16-gauge condenser frame and fan shroud
- 16-gauge aluminum cover, E-coated white.

Mounting design shall enable easy servicing of all components and unit replacement if necessary. The evaporator unit shall be covered with an ergonomically designed painted aluminum cover to provide maximum headroom and a pleasing appearance.

**CLIMATE CONTROL SWITCHES**

The multiplex system control screen shall contain all controls for the cab HVAC system. The following controls shall be programmed into the control/display: mode selector switch, front fan speed switch, rear fan speed switch, air conditioning on/off switch, and temperature control dial.

**CAB TILT ASSEMBLY**

A hydraulic cab lift system shall be provided, consisting of an electric-powered hydraulic pump, fluid reservoir, dual lift cylinders, remote cab lift controls and all necessary hoses and valves.

The cab tilt mechanism shall be custom designed for ease of maintenance and consist of two (2) hydraulic cylinders. Hydraulic lines shall be rated at 20,000 PSI burst pressure. The hydraulic cylinders shall be equipped with a velocity fuse that protects the cab from accidentally descending when the cab is in the tilt position.

Hydraulic cylinders shall be detachable to allow removal of the engine for major service. A remote cable operated mechanical cylinder stay bar and release shall be provided to insure a positive lock in the tilted position.

The two (2) rear outboard cab latches shall be of the hydraulic pressure release, automatic re-latching type, and provide an automatic positive lock when the cab is lowered. The latch shall not disengage or experience any damage when subjected to a pull apart tensile load of 6,000 lbs. The hydraulic pressure required to unlock the latch shall not exceed 550 PSI. The latch shall withstand 5,000 PSI without leaks or damage and withstand 1,000 continuous cycles of operation under a load of 1,000 lbs at liftoff. The tilt pump shall be electric over hydraulic type, with a pressure rating of not less than 4,000 PSI. Additionally, the cab tilt device shall be both electrically and hydraulically interlocked to prevent inadvertent activation of the cab tilt system.

- A "CAB NOT LATCHED" indicator shall be provided in the cab dash-warning cluster.
- A dual switch control system shall be provided for the cab tilt, located on the passenger side of the vehicle or on the optional tether control. System shall consist of a three (3) position toggle switch along with a rubber covered push button switch.

**AUXILIARY MANUAL CAB LIFT**

An auxiliary manual cab lift backup system shall be furnished inside the passenger side of the pump enclosure or front compartment for use in the event of total electrical shutdown.

The cab tilt control shall be equipped with an interlock that shall disable the cab tilt system in the event the parking brake is not applied.

**CHASSIS FRAME ASSEMBLY**

The chassis frame shall be fabricated in its entirety at the manufacturer's facility. This will prevent any split responsibility in warranty or service.

The frame shall consist of two (2) channels fastened together by cross members. All structural fasteners used in the frame shall be Grade 8 hardware. Hardened steel washers shall be used under all bolt heads and nuts to avoid stress concentrations. Top flange shall

be free of bolt heads. All spring hangers shall be machined steel castings. Frame assemblies that are welded or assembled with "Huck" type fasteners are not acceptable."

Each main frame rail shall be 10-1/4" x 4" x 3/8", fabricated from Domex™ 110,000 PSI minimum yield steel, with a minimum section modulus of 18.396 cu in and a resisting bending moment (RBM) of 2,023,560 inch pounds. The frame rails shall be drilled "together" (back to back) on a frame drilling machine with an internally cooled drill bit in order to minimize the deviation in hole diameter or location. Frames are built for the specific apparatus under construction so that no unnecessary holes or modifications are made to the frame assembly.

The chassis frame assembly, consisting of frame rails, cross members, axles and steering gear(s), shall be finish painted before installation of any electrical wiring, fuel system components, or air system components. All components or brackets fastened to the frame rails shall be cleaned, primed and painted prior to being attached to the frame rails.

**\*\*\* FRONT BUMPER, EXTENSION & ACCESSORIES \*\*\***

**FRONT BUMPER**

A 12" high, 101" wide, two (2) ribbed, bright finish stainless steel front bumper shall be provided. The bumper shall be a wrapped design to match the contour of the front cab sheet.

**BUMPER EXTENSION**

The bumper shall be extended 16" with a polished aluminum tread plate gravel shield enclosing the top and ends.

**STORAGE WELL - CENTER**

One (1) storage well constructed of 1/8" aluminum shall be installed in the gravel shield. This storage well shall be center mounted between the chassis frame rails. The bottom of the storage well shall have a minimum of four (4) drain holes.

One (1) hinged, latched, aluminum tread plate cover shall be installed on the storage well located in the center of the bumper extension.

The tread plate hose well cover shall have a notch cut out to allow pre-connection of suction/discharge hose.

**CENTER WELL - GENERAL STORAGE**

The center storage well shall be utilized for general storage of tools or equipment, the well shall be as large as space allows.

**FRONT TOW HOOKS**

Two (2) front painted tow hooks shall be fastened directly to the frame, below the front bumper. The tow hooks shall be fastened with grade 8 bolts and nuts.

**FRONT AXLE**

Front axle shall be a Meritor MFS-20-133 A-N, includes low friction "Easy Steer" bushing technology for maximum steering ease and longer life.

The front axle shall be rated at 21,500 lbs.

**FRONT DISC BRAKES**

Meritor EX-225 H, 17" disc brakes shall be provided for the front axle. The front brakes shall be full air actuated with automatic slack adjustment.

Premium Stemco oil seals with viewer glass shall be provided on the front axle.

**FRONT SUSPENSION**

Front suspension shall be progressive rate front leaf springs. The spring shall be permanently pinned at the front and have a shackle double pinned mounting at the rear.

The front leaf springs shall have a minimum of 10 leaves, a minimum length of 51", and a minimum width of 3-1/2". The capacity at ground shall be 21,500 lbs. All springs shall be of center bolt design. All spring pins shall be positively restrained from rotating in brackets and shackles.

**FRONT SHOCK ABSORBERS**

The front suspension system shall be equipped with Monroe, model "Magnum - 70", double acting hydraulic shock absorbers. Shock absorbers to have a minimum bore of 1.38" and an outside diameter of approximately 3-1/4".

**REAR AXLE**

Rear axle shall be a single, Meritor RS-26-185 with a capacity of 27,000 lbs. (Minimum). Axle shall be a single reduction axle with hypoid gearing and oil-lubricated wheel bearings. Oil seals shall be provided as standard equipment.

**REAR BRAKES**

Meritor EX-225 H, 17" disc brakes shall be provided for the rear axle. The rear brakes will be full air actuated with automatic slack adjustment.

**REAR AXLE TOP SPEED**

The rear axle/s shall be geared for a vehicle top speed in accordance with NFPA sections 4.15.2 and 4.15.3.

Units with GVWR over 26,000 pounds shall be limited to 68 mph. If the combined tank capacity is over 1250 gallons of foam and water or the GVWR is over 50,000 pounds, the vehicle top speed shall be limited to 60 mph or the fire service rating of the tires, whichever is lower.

**REAR SUSPENSION**

The rear suspension shall be leaf type, variable rate with a 31,000 lb. rating. The main spring assembly shall consist of 14 leaves with the main spring measuring 60.5" L x 3" W.

There shall be a rubber block helper mounted above the leaf springs, rated at 4,500 lbs. Two (2) fully wrapped leaves shall transmit driving and braking torque. The rating shall be designed to match or exceed the rear axle. Designs allowing the main pack to float are not acceptable.

\*\*\*\*\* AIR & BRAKE SYSTEM \*\*\*\*\*

**BRAKE SYSTEM**

A dual circuit, air operated braking system, meeting the design and performance requirements of FMVSS -121 and the operating test requirements of NFPA 1901 current edition shall be installed. It shall be direct air type with dual air treadle in the cab. The system shall be powered by an engine mounted, gear driven air compressor protected by a heated air dryer.

The air system shall be plumbed with reinforced, air brake tubing/hose in conformance to SAE J 844-94, Type B and U.S.D.O.T. standards. The compressor discharge shall be plumbed with stainless steel braided hose lines with a Teflon lining. Eaton Synflex Eclipse Air Brake tubing shall be run along the inside frame rails and connected with push to connect type fittings that meet or exceed all industry standards. All Synflex shall be secured with non-conductive, corrosion resistant strapping mounted with standoff fasteners.

Cord reinforced rubber hose lines with brass fittings shall be installed from the frame rails to axle mounted air connections.

The air system shall provide a rapid air build-up feature and low-pressure protection valve with light and buzzer, designed to meet the requirements of NFPA 1901, current edition.

**ABS SYSTEM**

An Anti-Skid Braking System (ABS) shall be provided to improve braking control and reduce stopping distance. This braking system shall be fitted to all of the axles. All electrical connections shall be environmentally sealed, water, weatherproof, and vibration resistant.

The system shall constantly monitor wheel behavior during braking. Sensors on each wheel shall transmit wheel speed data to an electronic processor which shall sense approaching wheel lock causing instant brake pressure modulation up to 5 times per second in order to prevent wheel lockup. Each wheel shall be individually controlled.

To improve service trouble shooting, provisions in the system for an optional diagnostic tester shall be provided. The system shall test itself each time the vehicle is started. A dash-mounted light shall go out once the vehicle has attained 4 mph after successful ABS start-up. To improve field performance; the system shall be equipped with a dual circuit design. The system circuits shall be configured in a diagonal pattern. Should a malfunction occur, the defective circuit shall revert to normal braking action. A warning light shall signal malfunction to the operator. The system shall consist of a wheel mounted toothed ring, sensor, sensor clip, electronic control unit and solenoid control valve.

The sensor clip shall hold the sensor in close proximity to the toothed ring. An inductive sensor consisting of a permanent magnet with a round pole pin and coil shall produce an alternating current with a frequency proportional to wheel speed. The unit shall be sealed, corrosion resistant and protected from electromagnetic interference. The electronic control unit shall monitor the speed of each wheel. A deviation shall be corrected by cyclical brake application and release. If a malfunction occurs, the defective circuit shall signal the operator and the malfunctioning portion of the system shall shut down. The system shall be installed in a diagonal pattern for side-to-side control. The system shall insure that each wheel is braking to optimum efficiency up to 5 times a second.

The system shall also control application of the auxiliary engine exhaust or drive line brakes to prevent wheel lock.

This system shall have a three (3) year or 300,000 mile parts and labor warranty as provided by Meritor Wabco Vehicle Control Systems.

**AUTOMATIC TRACTION CONTROL (ATC)**



**BRAKE TREADLE VALVE**

A Bendix dual brake treadle valve shall be mounted on the floor in front of the driver. The brake control shall be positioned to provide unobstructed access and comfort for the driver.

**PARKING BRAKE**

Parking brake shall be of the spring-actuated type, mounted on the rear axle brake chambers. The parking brake control shall be mounted on the cab center instrument panel, offset toward the driver. A red indicator light shall be provided in the driver dash panel that shall illuminate when the parking brake is applied.

**FRONT WHEELS & TIRES**

The front wheels shall be 22.5" x 12.25" ten stud, hub piloted, DuraBright aluminum disc type.

The front wheels shall be provided with bright nut covers and hub caps.

The front tires shall be Goodyear 425/65R22.5 "20 Ply" tubeless radial G296 MSA on/off road tread. The tires shall be fire service rated up to 24,400 lbs and shall have a top speed of 68 mph when inflated to 120 psi.

Fire Service Rating defined as no more than 50 miles of continuous operation at maximum load, or without stopping for at least 20 minutes. Emergency vehicle will reduce its speed to no more than 50 mph after the first 50 miles of travel.

Industry load and inflation standards are in a constant state of change. Printed material may not reflect the latest load and inflation standards.

**REAR WHEELS & TIRES**

The single rear axle wheels shall be 22.5" x 9" ten stud, hub piloted, DuraBright aluminum disc type.

The single rear axle aluminum disc wheels shall be provided with bright nut covers and hub caps.

The rear tires shall be Goodyear 12R22.5 "16 Ply" tubeless radial G622 RSD traction tread. The tires shall be fire service rated up to 29,020 lbs and shall have a top speed of 75 mph when inflated to 120 psi.

Fire Service Rating defined as no more than 50 miles of continuous operation at maximum load, or without stopping for at least 20 minutes. Emergency vehicle will reduce its speed to no more than 50 mph after the first 50 miles of travel.

Industry load and inflation standards are in a constant state of change. Printed material may not reflect the latest load and inflation standards.

**TIRE PRESSURE MONITORING DEVICES**

Each tire shall be equipped with an LED tire alert pressure management system (Vecsafe equal) that shall monitor tire pressure. A chrome plated brass sensor shall be provided on the valve stem of each tire.

The sensor shall calibrate to the tire pressure when installed on the valve stem for pressures between 10 and 200 psi. The sensor shall activate an integral battery operated LED when the pressure of that tire drops 8 psi.

**\*\*\*\*\* ENGINE, TRANSMISSION & ACCESSORIES \*\*\*\*\***

**ENGINE**

Engine shall be a Cummins, Model ISL9 450, diesel, turbo-charged, electronically controlled, per the following specifications.

- Max. Horsepower 450 HP @ 2100 RPM
- Governed Speed 2200 RPM
- Peak Torque 1250 lb. ft. @ 1400 RPM
- Cylinders Six (6)
- Operating Cycles Four (4)
- Bore & Stroke 4.49 x 5.69 in.
- Displacement 543 cu. in.
- Compression Ratio 16.6:1
- Governor Type Limiting Speed
- Drive line Size 1710.

Engine oil filters shall be engine manufacturers branded or approved equal. Engine oil filters shall be accessible for ease of service and replacement.

A fuel/water separator shall be provided.

**ENGINE CHASSIS CERTIFICATION**

The engine shall be installed in accordance with engine manufacturer's instructions. The apparatus manufacturer shall be able to furnish proof of engine installation approval by the engine manufacturer.

**COOLING/RADIATOR**

The radiator and the complete cooling system shall meet or exceed NFPA and engine manufacturer cooling system standards.

To provide maximum corrosion resistance and cooling performance, the entire radiator core shall be constructed using long life aluminum alloy. The core shall be made of aluminum fins, having a serpentine design, brazed to aluminum tubes. The tubes shall be brazed to aluminum headers. No solder joints or leaded material of any kind shall be acceptable in the core assembly.

The radiator core shall have a height of 35.92" x a width of 37.62". Supply and return tanks made of glass-reinforced nylon shall be crimped on to the core assembly using header tabs and a compression gasket to complete the radiator core assembly. The radiator shall be compatible with commercial antifreeze solutions.

There shall be a full steel frame around the entire radiator core assembly. The radiator core assembly shall be isolated within the steel frame by rubber inserts to enhance cooling system durability and reliability. The radiator shall be mounted in such a manner as to prevent the development of leaks caused by twisting or straining when the apparatus operates over uneven ground. The radiator assembly shall be isolated from the chassis frame rails with rubber isolators.

The cooling system shall include a surge tank mounted to the top of the radiator framework that shall remove air in the system. The surge tank shall be equipped with a sight glass to monitor the level of coolant. The radiator shall be equipped with a dual seal cap that shall allow for expansion and recovery of coolant into a separate integral chamber.

The cooling system shall be designed for a maximum of fifteen (15) PSI operation.

A drain port shall be located at the lowest point of the cooling system and/or the bottom of the radiator to permit complete flushing of the coolant from the system.

Extended life engine coolant shall provide anti-freeze protection to -30° F. The mixture shall be per the engine manufacture's specifications.

The engine cooling system shall have an inline coolant filter that shall have a shut off valve for ease of maintenance.

The engine cooling system shall be certified by the engine manufacturer to meet cooling index requirements for a minimum ambient temperature or 110-degrees Fahrenheit.

**TRANSMISSION COOLER**

A shell and tube transmission oil cooler shall be provided using engine coolant to control the transmission oil temperature. The cooler shall have an aluminum shell and copper tubes. The cooler shall be assembled using pressed in rubber tube sheets to mechanically create a reliable seal between the coolant and the oil. No brazed, soldered, or welded connections shall be used to separate the coolant from the oil.

**RADIATOR SKID PLATE**

The radiator installation shall include a heavy-duty radiator skid plate to protect the radiator from debris or obstructions under the chassis. The skid plate shall be designed so the angle of approach is not effected.

**CHARGE AIR COOLER**

The charge air cooler shall be constructed of aluminum with cast aluminum side tanks. To not restrict air flow to the radiator, the charge air cooler shall designed to be an integral part of the radiator assembly, mounted directly on top of the radiator. Rubber isolators shall be used at the mounting points to reduce transmission of vibrations.

Where applicable, the charge air cooler pipes shall be constructed of appropriately sized aluminized steel tubing with 0.06" wall thickness and formed hose barbs. The connections between these pipes, the engine and charged air cooler, shall be made using high temperature silicone hoses rated for use in temperature up to 500°F, and heavy duty constant tension T-Bolt spring hose clamps. These connections shall adequately allow for movement of the engine relative to the charged air cooler.

Charge air coolers that are located in front of the radiator, that block or restrict air flow into the engine radiator or introduce above ambient temperature air into the radiator in any way shall not be used.

**COOLING SYSTEM FAN**

The engine cooling system shall incorporate a heavy duty fan, installed on the engine and include a shroud.

The fan shall be equipped with an air operated clutch fan, which shall activate at a pre-determined temperature range.

Recirculation shields shall be installed to ensure that air which has passed through the radiator is not drawn through it again.

**COOLANT HOSE AND PIPING**

All coolant piping shall be constructed of appropriately sized powder coated steel tubing with 0.06" wall thickness and formed hose barbs. All connections between coolant pipes and chassis components shall be made using appropriately sized silicone hoses or elbows, rated for use in temperatures ranging from -60°F to +350°F, and appropriately sized constant torque hose clamps. These connections shall be minimal in number to reduce the number potential leak points, and shall adequately allow for movement of the engine relative to chassis mounted components. All integral hoses supplied with the engine shall be as supplied by the engine manufacturer.

**HEATER HOSES**

Premium Goodyear Hi-Miler® blue heater hoses shall be furnished for the heater system. The Hi-Miler® hose shall have a core of black Versigard (EPDM) with spiral Flextan reinforcement and blue Versigard coating. All heater hoses shall be equipped with constant torque type hose clamps. All integral hoses supplied with the engine shall be as supplied by the engine manufacturer.

**ENGINE BRAKE**

An engine compression brake shall be furnished for increased braking capabilities. Controls shall be as provided by the engine manufacturer and shall be activated by releasing the throttle pedal to the idle position.

The engine compression brake shall have dash mounted control switches to turn the brake on or off as well as to control the operational level of the brake.

The engine brake shall be wired in such a manner so as to illuminate the chassis brake lights when the engine brake is engaged and operating.

The engine brake shall be interlocked with the PTO operation and shall automatically disengage any time the apparatus is operating with the PTO active.

**ENGINE FAST IDLE**

A fast idle for the electronic controlled engine shall be provided. The fast idle shall be controlled by switches located on the smart wheel.

An electronic interlock system shall prevent the fast idle from operating unless the transmission is in "Neutral" and the parking brake is fully engaged. If the fast idle control is used in conjunction with a specified engine/transmission driven component or accessory, the fast idle control shall be properly interlocked with the engagement of the specified component or accessory.

**AIR CLEANER**

An engine air cleaner shall be provided. The air cleaner shall include a dry type element and shall be installed in accordance with the engine manufacturer's recommendations. The air cleaner shall be located to the rear of the engine, with streamline air pipes and hump hose connections from the inlet to the air cleaner and from the air cleaner to the turbo. The air cleaner shall be easily accessible when the cab is tilted. The air cleaner shall be plumbed to the air intake system that shall include a self sealing connection between the cab and air cleaner assembly to allow the cab to be tilted.

To draw fresh clean air, the intake for the air cleaner shall be on the side of the cab on the driver's side. The inlet shall be a minimum of 41" above the ground to allow the vehicle to navigate through water without any part of the air intake system being below the frame rail, preventing any type of water intake.

**SPARK ARRESTOR**

A spark arrestor shall be installed in the chassis air intake system. This arrestor shall be mounted behind the intake grille to filter out airborne embers. The spark arrestor housing must be easily accessible when the cab is tilted.

**ACCELERATOR CONTROL**

A floor mount accelerator pedal shall be installed on the floor in front of the driver. The pedal shall be positioned for comfort with ample space for fire boots and adequate clearance from the brake pedal control.

**REMOTE THROTTLE CONTROL HARNESS**

An apparatus interface wiring harness for the engine shall be supplied with the chassis. The harness shall include a connector for connection to the chassis harness which shall terminate in the left frame rail behind the cab for reconnection to required throttle control harnesses. The harness shall contain necessary connectors for a pressure governor and a multiplexed gauge. Separate circuits shall be included for pump controls, "Pump Engaged" and "OK to Pump" indicator lights, open compartment ground, start signal, park brake ground, ignition signal, master power, customer ignition, air horn solenoid switch, high idle switch and high idle indication light.

An apparatus interface wiring harness shall also be included which shall be wired to the cab harness interface connectors and shall incorporate circuits with relays to control pump functions. This harness shall control the inputs for the transmission lock up circuits, governor/hand throttle controls and dash display which shall incorporate "Pump Engaged" and "OK to Pump" indicator lights. The harness shall contain circuits for the apparatus builder to wire in a pump switch.

**ENGINE PROGRAMMING REMOTE THROTTLE**

The engine ECM (Electronic Control Module) discreet wire remote throttle circuit shall be turned off for use with a J1939 based pump controller or when the discreet wire remote throttle controls are not required.

**TRANSMISSION**

An Allison World Transmission, Model 3000 EVS electronically controlled, automatic transmission shall be provided. Transmission specifications shall be as follows:

- Max. Gross Input Power            450 HP
- Max. Gross Input Torque            1250 lb. ft.
- Input Speed (Range)                2000- 2800 RPM
- Direct Gear (Pumping)              4th (Lock-up)

Transmission installation shall be in accordance with the transmission manufacturer's specification. The transmission shall be readily and easily removable for repairs or replacement.

One (1) PTO opening shall be provided on both the left and right side of the converter housing (positions four (4) o'clock and eight (8) o'clock).

The transmission shall be calibrated for five (5) forward gears and one (1) reverse gear. Each gear shall have the following ratios:

- First 3.49:1
- Second 1.86:1
- Third 1.41:1
- Fourth 1.00:1
- Fifth 0.75:1
- Reverse -5.03:1

**TRANSMISSION SHIFT SELECTOR**

An illuminated, touch-pad type shift control shall be mounted in the cab, convenient to the driver. Shift control shall be approved by the transmission manufacturer.

**TRANSMISSION OIL LEVEL SENSOR**

The transmission shall be equipped with the oil level sensor (OLS); this sensor shall allow the operator to obtain an indication of the fluid level from the shift selector. The sensor display shall provide the following checks, correct fluid level, low fluid level and high fluid level.

**PARK TO NEUTRAL**

The transmission, upon application of the parking brake, shall automatically shift into neutral.

**PRESELECT PROGRAMMING**

The transmission shall have Allison Preselect enabled to automatically downshift when the secondary engine brake is active.

The transmission shall be programmed at the factory to automatically downshift to 4th gear.

This feature shall be enabled/disabled with the main on/off switch for the engine brake.

**TRANSMISSION FLUID**

TES-389 transmission fluid shall be utilized to fill the 3000 EVS transmission.

**DRIVE LINES**

Drive lines shall be Dana (Spicer) 1710 heavy duty series or equal, with "glide coat" splines on all slip shafts. The chassis manufacturer shall utilize an electronic type balancing machine to statically and dynamically balance all drive shafts. The manufacturer shall provide proof of compliance with all drive shaft manufacturer's standards and specifications.

**DIESEL EXHAUST FLUID TANK**

A five (5) gallon diesel exhaust fluid (DEF) tank shall be provided and installed. The tank shall be mounted in the area of the battery box and shall be accessible through a door in the crew area step well.

The tank shall include an internal heater that will be fed by engine coolant directly from the engine block to ensure it is always kept at the proper temperature per EPA requirements. The tank shall include a temperature sensor to control the flow of the engine coolant from the heater valve to the DEF tank.

A DEF fluid level sensor shall be provided with the DEF tank and connected to the level gauge on the dashboard.

**EXHAUST SYSTEM**

The exhaust system shall be installed in accordance with the engine manufacturer's requirements and meet all Environmental Protection Agency and State noise level requirements. Exhaust system components shall be securely mounted and easily removable.

The diesel particulate filter/muffler shall be fabricated from stainless steel and of a size compatible with the engine exhaust discharge.

Exhaust tubing shall be a minimum of 16 gauge stainless steel from the turbocharger on the engine to the inlet of the diesel particulate filter. Any flexible exhaust tubing shall be HDT stainless steel type. To minimize heat build-up, exhaust tubing within the engine compartment shall be wrapped with an insulating material. Exhaust shall be wrapped from the turbocharger to the entrance of the muffler. Material shall be held in place with worm gear type clamps.

An exhaust diffuser shall be provided to reduce the temperature of the exhaust as it exits the tailpipe.

Separate "regeneration" enable and prohibit switches shall be provided under the dash board on the driver's side. Each switch shall be provided with a spring loaded protective cover and shall be clearly marked as to function.

**SELECTIVE CATALYTIC REDUCTION (SCR)**

The vehicle shall be equipped with SCR technology that uses a urea based diesel exhaust fluid (DEF) and a catalytic converter to significantly reduce oxides of nitrogen (NOx) emissions.

The SCR system shall reduce levels of NOx (oxides of nitrogen emitted from engines) by injecting small quantities of diesel exhaust fluid (DEF) into the exhaust upstream of a catalyst, where it vaporizes and decomposes to form ammonia and carbon dioxide. The ammonia (NH3), in conjunction to the SCR catalyst, converts the NOx to harmless nitrogen (N2) and water (H2O).

The exhaust tailpipe extending from the SCR catalyst to the side of the vehicle shall be constructed from 16-gauge aluminized steel tubing. The exhaust discharge shall be on the officer side of the apparatus forward of the rear axle.

**\*\*\*\* FUEL SYSTEM \*\*\*\***

**FUEL TANK**

Fuel tank shall be a minimum of fifty (50) gallon capacity. It shall have a minimum fuel filler neck of 2" ID and 1/4 turn fill cap. A 1/2" minimum diameter drain plug shall be provided. The tank shall be fabricated from hot rolled, pickled and oiled steel. Provisions for an additional feed line and fuel level float shall be provided for future use.

The fuel tank shall be installed behind the rear wheels between the frame rails.

The fuel tank shall meet all FHWA 393.67 requirements including a fill capacity of 95% of tank volume.

The fuel tank shall be able to withstand a longitudinal acceleration of -23.0g at 0.166 seconds in accordance to SAE J211 standards using a channel frequency class 600 filter. Testing shall be performed at and verified by a third party testing and evaluation center.

All fuel lines shall be provided as recommended by the engine manufacturer. The lines shall be sized to meet engine manufacture's requirements, and shall be carefully routed and secured along the inside of the frame rails.

**FUEL FILTER/WATER SEPARATOR**

A Racor 400 series heated fuel filter/water separator shall be provided in the fuel system. A "water in fuel" indicator shall be provided on the dash.

**SECONDARY ELECTRIC FUEL PUMP**

In addition to the primary fuel pump, a secondary electric fuel pump for re-priming shall be furnished in the main fuel line. A labeled control switch shall be provided on the main dash panel.

**FUEL POCKET**

A fuel fill shall be provided in the left side rear wheel well area. A Cast Products heavy duty cast aluminum spring loaded hinged fill door shall be provided.

A label indicating "Ultra Low Sulfur Diesel Fuel Only" shall be provided adjacent to the fuel fill.

**DUAL POWER STEERING**

A dual power steering system shall be provided utilizing a Sheppard model #M110 main steering gear on the driver side of the chassis and a Sheppard model #M90 steering gear on the officer side of the chassis.

The power steering gear on the officer side of the chassis shall increase performance in turning the officer side wheel assembly, reducing loads and forces on the main gear and components.

The steering system shall be designed to maximize the turning capabilities of the front axle no matter the rating and tire size. The use of a power assist cylinder on the officer side of the chassis is NOT ACCEPTABLE on front axles of this capacity.

The system shall be designed utilizing an engine driven hydraulic pump, with a maximum operating pressure of 2000 PSI. Steering design shall permit a maximum of 5.6 turns from stop to stop. Steering system components shall be mounted in accordance with the steering gear manufacturer's instructions.

**STEERING COLUMN**

The steering column shall be a "Douglas Autotech" tilt and telescope column. A lever mounted on the side of the column shall control the tilt and telescope features.

The steering shaft from the column to the miter box shall have a rubber boot to cover the shaft slip and a second rubber boot to seal the passage hole in the floor.

There shall be a ergonomically designed, self-canceling lever, that shall control the following functions:

- Left and right turn signals
- High beam activation
- Hazard warning switch
- Two speed with intermittent windshield wiper control
- Windshield washer control

**STEERING WHEEL**

The steering wheel shall be a four (4) spoke, vinyl padded, minimum 18" diameter, with a center hub mounted horn button.

**4FRONT® - FRONTAL AIR BAG PROTECTION**

The cab will be equipped with a frontal impact protection system consisting of one (1) air bag in front of the driver in the steering wheel. The steering wheel air bag shall be designed to protect the driver in the event of a frontal or oblique impact.

The driver seat shall be equipped with a S4 pretensioner for suspension seat (if required) and a seat belt pretensioner.

**4FRONT® - FRONTAL AIR BAG PROTECTION FOR OFFICER SIDE KNEE BOLSTER**

Frontal impact protection system consisting of one (1) knee bolster air bag, in front of the officer mounted in the firewall panel below the dash panel. The officer seat will be equipped with a S4 pretensioner for a suspension seat (if required) and a seat belt pretensioner.

The officer side knee bolster air bag shall be designed to protect the legs of the occupant, when used in combination with the 3 point seat belt, in the event of a frontal or oblique impact.

The frontal air bag system shall be designed specifically for the cab configurations they are used in. The cab and chassis design shall have been subjected, via third party test facility, to a 21 MPH crash impact during frontal and oblique impact testing. Testing shall include all major chassis and cab components such as mounting straps for fuel and air tanks, suspension mounts, front suspension components, rear suspension components, frame rail cross members, engine and transmission and their mounts, pump house and mounts, frame extensions and body mounts. The testing shall provide configuration specific information used to optimize the timing for firing the air bags.

The driver side air bag shall be mounted in the steering wheel and will be designed to protect the head and upper torso of the occupant, when used in combination with the 3 point seat belt, in the event of a frontal or oblique impact. The passenger side knee bolster air bag shall be mounted in the modesty panel below the dash panel and shall be designed to protect the legs of the occupant, when used in combination with the 3 point seat belt, in the event of a frontal or oblique impact.

In the event of a frontal or oblique impact, the system shall deploy air bag/s, and activate the following components integrated into seating position equipped with an air bag:

Suspension seats will be retracted to lowest travel position. Seat belts will be pretensioned to firmly hold the occupants in place.

**ROAD SAFETY KIT**

A road safety kit shall be furnished with the following equipment:

- 2 1/2 lb. B-C fire extinguisher
- Triangle safety reflectors.

\*\*\*\*\* CHASSIS/BODY ELECTRICAL & ACCESSORIES \*\*\*\*\*

**CHASSIS ELECTRICAL SYSTEM**

All electrical wiring in the chassis shall be GXL cross link insulated type. Wiring is to be color coded and include function codes every three (3) inches on both sides. Wiring harnesses shall be routed in protective, heat resistant loom, securely and neatly installed. Two (2) power distribution centers shall be provided in central locations for greater accessibility. The power distribution centers shall contain thermal automatic reset breakers, power control relays, flashers, diode modules, daytime driving light module, and engine and transmission data links. All breakers and relays shall have a capacity substantially greater than the expected load on the related circuit, thus ensuring long component life. Power distribution centers shall be composed of a system of interlocking plastic modules for ease in custom construction.

The power distribution centers are function oriented. The first is to control major truck function. The second shall control center to overhead switching and interior operations. Each module is single function coded and labeled to aid in troubleshooting. The centers will also have accessory breakers and relays for future installations. All harnesses and power distribution centers shall be electrically tested prior to installation to ensure the highest system reliability.

All external harness interfaces shall be of a triple seal type connection to ensure a proper connection. The cab/chassis and the chassis/body connection points shall be mounted in accessible locations. Complete chassis wiring schematics shall be supplied with the apparatus.

**WIRING HARNESS DESCRIPTION**

The wiring harness contained on the chassis shall be designed to utilize wires of stranded copper or copper alloy of a gauge rated to carry 125% of maximum current for which the circuit is protected without exceeding 10% voltage drop across the circuit. Wiring shall be uniquely identified by color code or circuit function code, labeled at a minimum of every three (3) inches. The identification of the wiring shall be referenced on a wiring diagram. All wires conform to SAEJ1127 (Battery Cable), SAEJ1128 (Low Tension Primary Cable), SAEJ1560 (Low Tension Thin Wall Primary Cable).

The covering of harnesses shall be moisture resistant loom with a minimum rating of 289° Fahrenheit and a flammability rating of VW-1 as defined in UL62. The covering of jacketed cable shall have a minimum rating of 289° Fahrenheit.

All circuits shall conform to SAEJ1292. All circuits must be provided with low voltage over current protective devices.

All exposed electrical connections will be coated with "Z-Guard" to prevent corrosion.

**DIRECT GROUNDING STRAPS**

Direct grounding straps shall be mounted to the following areas; frame to cab, frame to body and frame to pump enclosure.

All exposed electrical connections shall be coated with "Z-Guard 8000" to prevent corrosion.

**EMI/RFI PROTECTION**

The apparatus shall incorporate the latest designs in the electrical system with state of the art components to insure that radiated and conducted electromagnetic interference (EMI) and radio frequency interference (RFI) emissions are suppressed at the source.

The apparatus proposed shall have the ability to operate in the environment typically found in fire ground operations with no adverse effects from EMI/RFI.

EMI/RFI susceptibility is controlled by utilizing components that are fully protected and wiring that utilizes shielding and loop back grounds where required. The apparatus shall be bonded through wire braided ground straps. Relays and solenoids that are suspect to generating spurious electromagnetic radiation are diode protected to prevent transient voltage spikes.

In order to fully prevent the radio frequency interference the purchaser may be requested to provide a listing of the type, power output, and frequencies of all radio and bio medical equipment that is proposed to be used on the apparatus.

**12 VOLT ELECTRICAL SYSTEM TESTING**

The apparatus low voltage electrical system shall be tested and certified by the manufacturer. The certification shall be provided with the apparatus. All tests shall be performed with air temperature between 0°F and 100°F.

The following three (3) tests shall be performed in order. Before each test, the batteries shall be fully charged.

**TEST #1-RESERVE CAPACITY TEST**

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged. The engine shall be shut off and the minimum continuous electrical load shall be activated for 10 minutes. All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test failure.

**TEST #2-ALTERNATOR PERFORMANCE TEST AT IDLE**

The minimum continuous electrical load shall be activated with the engine running at idle speed. The engine temperature shall be stabilized at normal operating temperature. The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

**TEST #3-ALTERNATOR PERFORMANCE TEST AT FULL LOAD**

The total continuous electrical load shall be activated with the engine running up to the engine manufacturers governed speed. The test duration shall be a minimum of 2 hours. Activation of the load management system shall be permitted during this test. However, an alarm sounded due to excessive battery discharge, as detected by the system, or a system voltage of less than 11.7 volts DC for a 12 volt system, for more than 120 seconds, shall be considered a test failure.

**LOW VOLTAGE ALARM TEST**

Following completion of the preceding tests, the engine shall be shut off. The total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm is activated.

The battery voltage shall be measured at the battery terminals. With the load still applied, a reading of less than 11.7 volts shall be considered a test failure. The battery system shall then be able to restart the engine.

At time of delivery, documentation shall be provided with the following information:

- Documentation of the electrical system performance test
- A written load analysis of the following;

- Nameplate rating of the alternator
- Alternator rating at idle while meeting the minimum continuous electrical load
- Each component load comprising the minimum continuous electrical load.
- Additional loads that, when added to the minimum continuous load, determine the total connected load.
- Each individual intermittent load.

**ELECTRICAL MANAGEMENT SYSTEM**

A Class 1 ES-Key Electrical Management System shall be utilized on the chassis for all functions applicable. The system shall consist of the following components:

A Modem with a RS232 computer interface and standard telephone jack used to not only program the multiplex system but also serve as a factory direct gateway into the vehicle from any Class 1 multiplex authorized service facility.

A Universal System Manager (USM), which acts as the main controlling component of the multiplexing system shall be provided and factory programmed to DOT, NFPA, SAE, the manufacturer and Borough of Berwick specifications. The programming shall be done by the manufacturer's engineering department. The ES-Key system installation shall comply with SAE J 551 requirements regarding Electromagnetic and Radio Frequency interference (EMI, RFI), as well as utilize components and wiring practices that insure the system is protected against corrosion, excessive temperatures, water, excessive physical, and vibration damage by any equipment installed on the vehicle at the time of delivery.

A series of Multiplexing Input/Output Modules shall be installed. The Input/Output modules shall permit the multiplexing system to reduce the amount of wiring and components used as compared to non-multiplexed apparatus. These modules shall vary in I/O configuration, be waterproof allowing installation outside of enclosed areas and shall possess individual output internal circuit protection. The modules shall also have three status indicators visible from a service persons vantage point that shall indicate the status of the module. In the event a load requires more than 7.5 AMPS of operating current, the module shall activate a simple relay circuit integral to any of the 3 dillbox assemblies installed in the cab.

Diagnostic software shall be provided to download data from the on board ES-KEY system. This software shall have the ability to view system input/output (I/O) information, and include a connection from a computer to the vehicle.

A Class1 UltraView # UV450 4.3" color transmissive TFT display for monitoring critical apparatus and engine information shall be provided an installed. The displays shall be CAN based utilizing J1939 message protocol. The display shall utilize a bonded LCD display screen for optimal visibility in direct sunlight.

The display shall be fully configurable and when used in conjunction with the Class 1 ES-Key system and shall be custom programmed to control multiple apparatus functions and perform onboard apparatus and engine diagnostics.

**INTERLOCK INTERFACE MODULE**

A Vocation Module, which is the interface between the multiplexing system and the pump system shall be provided. This module shall serve as the interface between the operator, engine, transmission and pumping system. The module shall be installed under the driver's side dash, in a sealed enclosure that shall possess green indicating LED's that shall indicate to service personnel the interlock state of the apparatus. In the event of a multiplexing error involving pump operation can be activated to ensure reliable pumping operations at ALL times. In addition to controlling pump function, this vocation module shall be able to provide automatic and/or manual activation of engine "Fast Idle", to maintain adequate alternator output and thus, chassis voltage.

**CHASSIS DIAGNOSTICS SYSTEM**

Diagnostic ports shall be accessible while standing on the ground and located inside the driver's side door left of the steering column. The diagnostic panel shall allow diagnostic tools such as computers to connect to various vehicle systems for improved troubleshooting providing a lower cost of ownership. Diagnostic switches shall allow engine and ABS systems to provide blink codes should a problem exist.

The diagnostic system shall include the following:

- A single port to monitor the engine, transmission and ABS system and diagnostics of the roll sensor (if applicable)
- Engine diagnostic switch (blink codes)
- ABS diagnostic switch (blink codes)
- Allison Transmission Codes (through touch pad shifter)

**VOLTAGE MONITOR SYSTEM**

A voltage monitoring system shall be provided to indicate the status of the battery system connected to the vehicle's electrical load. The system shall provide visual and audible warning when the system voltage is below or above optimum levels.

The alarm shall activate if the system falls below 11.8 volts DC for more than two (2) minutes.

**INDICATOR LIGHT AND ALARM PROVE-OUT SYSTEM**

A system shall be provided which automatically tests basic indicator lights and alarms located on the cab instrument panel.

**12 VOLT SEQUENCER**

A sequencer shall be provided that automatically activates and deactivates vehicle loads in a preset sequence thereby protecting the alternator from power surges. This sequencer operation shall allow a gradual increase or decrease in alternator output, rather than loading or dumping the entire 12 volt load to prolong the life of the alternator.

Emergency light sequencing shall operate in conjunction with the emergency master light switch. When the emergency master switch is activated, the emergency lights shall be activated one by one at half second intervals. Sequenced emergency light switch indicators shall flash while waiting for activation.

When the emergency master switch is deactivated, the sequencer shall deactivate the warning light loads in the reverse order.

Rear of cab Air-Conditioning and Heat shall be load managed.

**ELECTRICAL HARNESS REQUIREMENT**

To ensure dependability, all 12-volt wiring harnesses installed by the manufacturer shall conform to the following specifications:

- SAE J 1128 - Low tension primary cable
- SAE J 1292 - Automobile, truck, truck-tractor, trailer and motor coach wiring
- SAE J 163 - Low tension wiring and cable terminals and splice clips
- SAE J 2202 - Heavy duty wiring systems for on-highway trucks
- NFPA 1901 - Standard for automotive fire apparatus
- FMVSS 302 - Flammability of interior materials for passenger cars, multipurpose passenger vehicles, trucks and buses
- SAE J 1939 - Serial communications protocol
- SAE J 2030 - Heavy-duty electrical connector performance standard
- SAE J 2223 - Connections for on board vehicle electrical wiring harnesses
- NEC - National Electrical Code
- SAE J 561 - Electrical terminals - Eyelet and spade type
- SAE J 928 - Electrical terminals - Pin and receptacle type A.

For increased reliability and harness integrity, harnesses shall be routed throughout the cab and chassis in a manner which allows the harnessing to be laid into its mounting location. Routing of harnessing which requires pulling of wires through tubes is never allowed at the manufacturer.

Wiring shall be run in loom or conduit where exposed, and have grommets or other edge protection where wires pass through metal. Wire colors shall be integral to each wire insulator and run the entire length of each wire. Harnessing containing multiple wires and uses a single wire color for all wires shall not be allowed. Function and number codes shall be continuously imprinted on all wiring harness conductors at 3.00" intervals. All wiring installed between the cab and into doors shall be protected by a wire conduit to protect the wiring. Exterior exposed wire connectors shall be positive locking, and environmentally sealed to withstand elements such as temperature extremes, moisture and automotive fluids. Electrical wiring and equipment shall be installed utilizing the following guidelines:

- All holes made in the roof shall be caulked with silicon. Large fender washers, liberally caulked, shall be used when fastening equipment to the underside of the cab roof.
- Any electrical component that is installed in an exposed area shall be mounted in a manner that shall not allow moisture to accumulate in it. Exposed area shall be defined as any location outside of the cab or body.
- For low cost of ownership, electrical components designed to be removed for maintenance shall be quickly accessible. For ease of use, a coil of wire shall be provided behind the appliance to allow them to be pulled away from the mounting area for inspection and service work.
- Corrosion preventative compound shall be applied to non-waterproof electrical connectors located outside of the cab or body. All non-waterproof connections shall require this compound in the plug to prevent corrosion and for easy separation of the plug.
- Any lights containing non-waterproof sockets in a weather-exposed area shall have corrosion preventative compound added to the socket terminal area.
- All electrical terminals in exposed areas shall have protective coating applied completely over the metal portion of the terminal.
- Rubber coated metal clamps shall be used to support wire harnessing and battery cables routed along the chassis frame rails.
- Heat shields shall be used to protect harnessing in areas where high temperatures exist. Harnessing passing near the engine exhaust shall be protected by a heat shield.
- Cab and crew cab harnessing shall not be routed through enclosed metal tubing. Dedicated wire routing channels shall be used to protect harnessing therefore improving the overall integrity of the vehicle electrical system. The

design of the cab shall allow for easy routing of additional wiring and easy access to existing wiring.

- All standard wiring entering or exiting the cab shall be routed through sealed bulkhead connectors to protect against water intrusion into the cab.

**BATTERY CABLE INSTALLATION**

All 12-volt battery cables and battery cable harnessing installed by the apparatus manufacturer shall conform to the following requirements:

- SAE J 1127 - Battery Cable
- SAE J 561 - Electrical terminals, eyelets and spade type
- SAE J 562 - Nonmetallic loom
- SAE J 836 A - Automotive metallurgical joining
- SAE J 1292 - Automotive truck, truck-tractor, trailer and motor coach wiring
- NFPA 1901 - Standard for automotive fire apparatus.

Battery cables and battery cable harnessing shall be installed utilizing the following guidelines:

- Splices shall not be allowed on battery cables or battery cable harnesses.
- For ease of identification and simplified use, battery cables shall be color coded. All positive battery cables shall be marked red in color. All negative battery cables shall be black in color.
- For ease of identification, all positive battery cable isolated studs throughout the cab and chassis shall be red in color.
- For increased reliability and reduced maintenance, all electrical buss bars located on the exterior of the apparatus shall be coated to prevent corrosion.
- An operational test shall be conducted to ensure that any equipment that is permanently attached to the electrical system is properly connected and in working order.

**ALTERNATOR**

There shall be a Delco Remy Model 40SI, 320 amp brushless, serpentine belt driven alternator. The brushless design of the 40SI transfers magnetic fields between the rotor and stator air-gap without brushes.

The alternator installation shall be designed to provide maximum output at engine idle speed, by using "Remote Sense" in order to meet the minimum continuous electrical load of the apparatus as required.

The alternator shall carry a 3 Year/Unlimited Mile warranty.

**BATTERY SYSTEM**

Three (3) Exide #HP-31D, maintenance free batteries shall be provided. These batteries shall be wired in parallel to the master disconnect switch. Each battery shall be rated at 925 CCA at 0° F and shall have a reserve capacity of 180 minutes.

Wiring for the batteries shall be 4/0 welding type dual path starting cables per SAEJ541.

**BATTERY STORAGE**

Batteries shall be securely mounted in a fixed 3/16" GR50 steel tray, located on the driver's side of the chassis frame. Complete access shall be provided when the cab is fully tilted. Batteries shall be mounted on non-corrosive matting material.

The battery tray shall be able to withstand a longitudinal acceleration of -46.5g at 0.246 seconds in accordance to SAE J211 standards using a channel frequency class 600 filter. Testing shall be performed at and verified by a third party testing and evaluation center.

**BATTERY DISCONNECT SWITCH**

The chassis batteries shall be wired in parallel to a single 12 volt electrical system, controlled through a heavy duty master disconnect switch. The master disconnect switch shall be located within easy access of the driver upon entering or exiting the cab.

**BATTERY JUMPER STUDS**

A set of Cole Hersee battery jumper studs, model #46210-02 (red) and #46210-03 (black) shall be provided to allow the battery system to be jump started or charged from an external source. The studs shall be located on the bottom of the battery box on the driver's side of the chassis. Each stud shall be equipped with both a rubber protector cap and a 2" square non-conductive plate to prevent accidental shorting.

**120 VOLT SHORELINE CONNECTION - "SUPER" AUTO EJECT**

One (1) Kussmaul "Super" Auto Eject model 091-55-20-120, automatic, 120 volt, 20 amp shoreline disconnect shall be provided for the on board, 110 volt battery charging systems.

The disconnect shall be equipped with a NEMA 5-20 P male receptacle, which shall automatically eject the shoreline when the vehicle starter is energized. The mating connector shall be included with the auto eject and shall be provided as loose equipment. A label shall be provided indicating voltage and amperage ratings.

**SHORELINE POWER INLET PLATE**

A shoreline power receptacle information plate shall be permanently affixed at or near the power inlet. The plate shall indicate the following:

- Type of Line Voltage
- Current Rating in Amps Power Inlet Type (DC or AC).

The Kussmaul auto-eject connection shall be equipped with a Red weatherproof cover.

The shoreline receptacle shall be located in the area directly adjacent to the driver's side cab door.

**BATTERY CHARGER / AIR COMPRESSOR SYSTEM**

A Kussmaul model #091-187-12-REMOTE, "Auto Charge 1200" high output, fully automatic battery charger shall be provided for maintaining the vehicle battery system. Unique electronic sensing circuits sense the true battery voltage while eliminating the need for external sense wires. Output current shall be 40 amperes @ 12 volt DC.

A Kussmaul 091-9HP air compressor shall maintain the air pressure in the chassis air brake system while the vehicle is not in use. The air compressor shall have a rated input at 120 volts AC @ 3.5 amps and a maximum of 125 psi.

**Header Title**

Bidder Complies

YES

NO

A LED bar graph display shall be located near the shoreline connection to monitor the battery status.

A Kussmaul # 091-9-090 Auto Drain ACHP shall be installed to protect the Auto Pump from built up moisture.

**SHORELINE RECEPTACLE**

One (1) 120 volt 5-15 R household type receptacle(s) shall be located in the specified body compartment as directed. The receptacle(s) shall be wired into the shoreline receptacle to provide a 120 volt power source for fire department equipment.

**SHORELINE POWER STRIP**

A 120 volt household type power strip shall be located as directed in the rear crew area of the cab. The power strip shall be equipped with a minimum of six (6) outlets. The power strip shall be wired into the shoreline receptacle to provide a 120 volt power source for fire department equipment.

**EMERGENCY/AUXILIARY SWITCHES**

The cab shall be designed with multiple areas for component switching within easy reach of the driver and or officer. This switch package shall separate the emergency / auxiliary electrical functions from the regular chassis functions. A minimum of twenty one (21) programmable CAN Bus Eaton model #E33 switches with integral indicator lights shall be provided.

Twelve (12) of switches shall be located on a sloped panel above the above the driver's position for warning lights and auxiliary controls. A master warning switch shall be provided, which shall allow pre-setting of emergency light switches and shall have a red integral indicator light.

Nine (9) additional switches shall be located on the lower switch panel between the driver and officer for auxiliary controls.

All switches, (other than the master switch), shall have switch function labeling and an integral indicator light.

**"LED" CAB INTERIOR LIGHTING**

Four (4) Akron 8080-8000-13 interior LED combination red/white dome lights shall be furnished in the cab, two (2) in the forward section and two (2) in the rear crew section. Each dome light shall have an integral selector switch. Each dome light shall also activate when the respective, adjacent cab door is opened.

**INNER CAB DOOR LED FLASHERS**

One (1) Weldon 16" LED door warning lamp shall be provided on the inside door panel of each cab door. The light shall be mounted on the door's lower scuff plate and shall be activated when the respective door is opened. Each light shall be furnished with a clear lens and amber led's.

**"DO NOT MOVE APPARATUS" WARNING LIGHT**

A 1" round, red flashing warning light with an integral audible alarm shall be functionally located in the cab to signal when an unsafe condition is present; such as an open cab or body compartment door, an extended ladder rack, a deployed stabilizer, an extended light tower or any other device that may be opened, extended or deployed and might cause damage to the apparatus if it is moved.

**Header Title**

Bidder Complies

YES

NO

This light shall be activated through the parking brake switch to signal when the parking brake is released. This light shall be labeled "DO NOT MOVE TRUCK".

**12 VOLT POWER PORT NEAR DRIVER**

One (1) 12 volt power port accessory outlet(s) shall be installed in the cab of the truck for the fire departments accessory devices. The port(s) shall be located as directed near the driver's seating position for devices such as cellular phones.

**12 VOLT POWER PORT NEAR OFFICER**

One (1) 12 volt power port accessory outlet(s) shall be installed in the cab of the truck for the fire departments accessory devices. The port(s) shall be located as directed near the officer's seating position for devices such as cellular phones.

**USB CHARGING PORT NEAR DRIVER**

One (1) round USB charging port(s) shall be installed in the cab of the truck for the fire departments accessory devices. Each port shall have two (2) USB connections and shall have a 5 volt, 2.1 amp max output. The port(s) shall be located as directed near the driver's seating position for devices such as cellular phones.

**USB CHARGING PORT NEAR OFFICER**

One (1) round USB charging port(s) shall be installed in the cab of the truck for the fire departments accessory devices. Each port shall have two (2) USB connections and shall have a 5 volt, 2.1 amp max output. The port(s) shall be located as directed near the officer's seating position for devices such as cellular phones.

**12 VOLT ACCESSORY CIRCUIT - CAB DASH**

One (1) dedicated circuit; 12 volt, 40 Amp, power and ground on 3/8 stud and fused at battery shall be provided in the cab dash. The circuit shall be for future installation of radios or accessories.

**12 VOLT ACCESSORY CIRCUIT - BEHIND OFFICERS SEAT**

One (1) dedicated circuit; 12 volt, 40 Amp, power and ground on 3/8 stud and fused at battery shall be behind the officer seat. The circuit shall be for future installation of radios or accessories.

**12 VOLT ACCESSORY CIRCUIT - BEHIND OFFICERS SEAT**

One (1) dedicated circuit; 12 volt, 40 amp, power and ground on 3/8 stud and fused at battery shall be provided behind the officer seat.

An additional 12 volt, 20 amp, power stud shall be installed next to the studs above and shall be switched with the ignition circuit.

The circuit shall be for future installation of radios or accessories.

**REAR VISION CAMERA/GPS SYSTEM**

An Optimo rear vision camera/GPS system model # GPS-7101 shall be provided to allow the driver to visually see the rear of the apparatus while in the cab. The system shall include a high resolution 7" touch screen with LED Backlight and anti glare system with an auto dimmer. The system shall include audio transmission from the camera.

A Sygic premium turn by turn navigation system with maps and a robust set of features shall be included as standard equipment.

**Header Title**

Bidder Complies

YES

NO

The system shall have 3 viewing modes, navigation, picture in picture (camera and navigation), and full back-up camera mode.

The rear vision camera shall be wired to automatically activate when the chassis transmission is placed in reverse.

The system shall carry a two (2) year warranty from Optimo.

The monitor for the rear vision system shall be mounted ceiling of the cab in easy view of the driver.

**HEADLIGHTS CLUSTER**

Two (2) dual, Peterson LED headlight modules with a bright finish bezel shall be furnished, one (1) each side, on the front of the cab. Each head light module shall incorporate an individual LED low beam and a LED high beam headlight. High beam actuation shall be controlled on the turn signal lever.

**DAYTIME RUNNING LIGHTS**

The chassis head lights shall have integrated circuitry to actuate the low beam headlights at a maximum of 80 percent of capacity whenever the chassis engine is running.

The daytime running lights shall be interlocked with the parking brake.

**SECONDARY DUAL LIGHT MODULE**

Two (2) Code 3 65STA arrow shaped, amber LED turn signals shall be provided, one (1) in each side of the dual light module above the headlights.

The NFPA required, Zone "A" lower warning lights shall be incorporated into each side dual light module noted above.

**DOT MARKER LIGHTS AND REFLECTORS**

Five (5) DOT approved Whelen (or equal) Light Emitting Diode (LED) cab marker lamps shall mounted on the top front edge of the cab roof.

Amber LED marker lights with integral reflectors shall be provided on the side of the cab adjacent to the driver's door, one (1) each side.

Truck-Lite Model # 18 red LED marker lights with integral reflectors shall be provided at the lower side rear, one (1) each side.

Truck-Lite # 60115Y yellow LED side marker and turn lights shall be provided on the apparatus lower side, forward of rear axle, one (1) each side if the apparatus is 30' long or longer.

Truck-Lite Model #19 red LED clearance lights shall be provided on the apparatus rear upper, one (1) each side at the outermost practical location.

Truck-Lite Model # 33740R LED 3-lamp identification bar will be provided on the apparatus rear center. The lights shall be red in color.

Truck-Lite # 98034Y yellow reflectors shall be provided on the apparatus body lower side, as far forward and low as practical, one (1) each side if the apparatus is 30' long or longer.

Truck-Lite # 98034R red reflectors shall be provided on the apparatus rear, one (1) each side at the outermost practical location.

**LED LICENSE PLATE LIGHT - REAR**

One (1) Tecniq model #L10 LED license plate light shall be provided above the mounting position of the license plate. The light shall be clear in color and shall have a chrome finish.

**TAIL, STOP, TURN AND BACK-UP LIGHTS**

Two (2) Code 3, 65STR 4" x 6", red LED combination tail and stop lights, shall be mounted one each side at the rear of the body.

Two (2) Code 3, 65STA 4" x 6", amber LED arrow turn signal lights, shall be mounted one each side, on a vertical plane with the tail/stop lights.

Two (2) Code 3, 65RV 4" x 6", white LED backup lights, shall be mounted one each side, on a vertical plane with the turn/tail/stop signals. These lights shall activate when the transmission is placed in reverse gear.

Two (2) Code 3 65STK4 mounting flanges, installed one (1) on each side, shall be provided to mount the lights described above in one common mounting flange. The fourth opening shall be for the lower rear warning lights.

The lights shall be mounted in order, from top to bottom, as described above.

**CAB STEP LIGHTS**

Polished stainless steel, TecNiq Eon 3-LED horizontal surface mounted chassis step lights shall be provided and controlled with marker light actuation. Step lights shall be located to properly illuminate all chassis access steps and walkway areas and shall include a mounting gasket to provide a watertight seal.

**BODY STEP LIGHTS**

Polished stainless steel, TecNiq Eon 3-LED horizontal surface mounted body step lights shall be provided and controlled with marker light actuation. Step lights shall be located to properly illuminate all body access steps and walkway areas and shall include a mounting gasket to provide a watertight seal.

**DUNNAGE AREA LIGHTING**

Two (2) stainless steel, TecNiq Eon 3-LED horizontal surface mounted lights shall be provided in the dunnage area to provide adequate illumination of this area.

**HOSE BED LIGHTS**

Two (2) 6" Unity model AG chrome plated deck lights shall be mounted on each side of the hose bed. The light shall illuminate the hose bed area. Control switches shall be provided on the light heads.

**HOSEBED WORKLIGHT SWITCH- RECESSED**

The hose bed work light switch shall be installed in a recessed pocket.

**HOSE BED WORK LIGHT - SWITCH**

The hose bed work light shall have a protected 12-volt switch at the rear body panel. The switch will be labeled "HOSE BED WORK LIGHTS".

**SCENE LIGHTS - BEHIND FRONT CAB DOORS**

Two (2) Fire Research Spectra 900 LED scene lights shall be provided, one on each side of the cab, directly behind the front cab entrance door in a chrome plated flange. Each light shall be 9" wide by 6 3/4" high by 1 3/4" deep and produce 7,000 lumens. The scene lights shall be wired through the load management system.

**SCENE LIGHTS - REAR OF BODY**

Two (2) Fire Research Spectra 900 LED scene lights shall be provided, one on each side of the rear body panel in a chrome plated flange. Each light shall be 9" wide by 6 3/4" high by 1 3/4" deep and produce 7,000 lumens. The scene lights shall be wired through the load management system.

**SCENE LIGHTS - DRIVER SIDE OF BODY**

Two (2) Fire Research Spectra 900 LED scene lights shall be provided. The scene lights shall be installed one rearward and one forward on the driver side of the body in a chrome plated flange. Each light shall be 9" wide by 6 3/4" high by 1 3/4" deep and produce 7,000 lumens. The scene lights shall be wired through the load management system.

**SCENE LIGHTS - OFFICER SIDE OF BODY**

Two (2) Fire Research Spectra 900 LED scene lights shall be provided. The scene lights shall be installed one rearward and one forward on the officer side of the body in a chrome plated flange. Each light shall be 9" wide by 6 3/4" high by 1 3/4" deep and produce 7,000 lumens. The scene lights shall be wired through the load management system.

**CAB DOOR LIGHT SWITCHING - CAB**

Two (2) switches shall be provided in the cab warning light switch console to turn the lights at the cab doors on and off. One (1) switch shall control the driver side light and one (1) switch shall control the officer side light.

**REAR OF BODY LIGHT SWITCHING - CAB**

A switch shall be provided in the cab warning light switch console to turn the rear of body lights on and off.

**REAR OF BODY LIGHT SWITCHING - PUMP PANEL**

A switch shall be provided on the pump panel to turn the rear of body lights on and off.

**DRIVER SIDE OF BODY LIGHT SWITCHING - CAB**

A switch shall be provided in the cab warning light switch console to turn the driver side of body lights on and off.

**DRIVER SIDE OF BODY LIGHT SWITCHING - PUMP PANEL**

A switch shall be provided on the pump panel to turn the driver side of body lights on and off.

**OFFICER SIDE OF BODY LIGHT SWITCHING - CAB**

A switch shall be provided in the cab warning light switch console to turn the officer side of body lights on and off.

Bidder Complies	
YES	NO

**OFFICER SIDE OF BODY LIGHT SWITCHING - PUMP PANEL**

A switch shall be provided on the pump panel to turn the officer side of body lights on and off.

**GROUND LIGHTS - CAB**

One (1) TecNiq LED, 6" long ground light with stainless steel mounting bracket, shall be provided under each side cab door entrance step, four (4) total. The ground lights shall turn on automatically with each respective door jamb switch and also by a master ground light switch in the warning light switch console.

Each light shall illuminate an area at a minimum 30" outward from the edge of the vehicle.

**GROUND LIGHTS - PUMP PANEL**

One (1) TecNiq LED, 6" long ground light with stainless steel mounting bracket, shall be provided under each side pump panel running board, two (2) total. The ground lights shall be activated by a master ground light switch in the cab and shall be wired through the load management system.

**GROUND LIGHTS - REAR**

One (1) TecNiq LED, 6" long ground light with stainless steel mounting bracket, shall be provided under each rear body corner, two (2) total. The ground lights shall be activated by a master ground light switch in the cab and shall be wired through the load management system.

**ROOF MOUNT 155W LED BROW LIGHT - ABOVE WINDSHIELD**

Fire Research Spectra LED Scene Light model SPA800-Q15 contour mount light shall be installed. The mounting brackets shall attach to the bottom of the lamphead and be machined to conform to the roof radius. Wiring shall extend from a weatherproof strain relief at the rear of the lamp head.

The lamp head shall have sixty (60) ultra-bright white LEDs, 48 for flood lighting and 12 to provide a spot light beam pattern. It shall operate at 12 volts DC, draw 13 amps, and generate 15,000 lumens of light. The lamp head shall have a unique lens that directs flood lighting onto the work area and focuses the spot light beam into the distance. The lamp head shall be no more than 5 7/8" high by 14" wide by 3 1/2" deep and have a heat resistant handle. The lamp head and mounting arm shall be powder coated. The LED scene light shall be for fire service use.

The Spectra brow mounted flood light shall be located above the windshield in the center of the cab.

**LIGHT(S) ABOVE WINDSHIELD SWITCHING - CAB**

A switch shall be provided in the cab warning light switch console to turn the light(s) above windshield on and off.

\*\*\*\* BODY ELECTRICAL SYSTEM \*\*\*\*

**12 VOLT BODY ELECTRICAL SYSTEM**

All electrical lines in the body shall be protected by automatic circuit breakers, conveniently located to permit ease of service. Flashers, heavy solenoids and other major electrical controls shall be located in a central area near the circuit breakers.

All lines shall be color and function coded every 3", easy to identify, oversized for the intended loads and installed in accordance with a detailed diagram. A complete wiring diagram shall be supplied with the apparatus.

Wiring shall be carefully protected from weather elements and snagging. Heavy duty loom shall be used for the entire length. Grommets shall be utilized where wiring passes through panels.

In order to minimize the risk of heat damage, wires run in the engine compartment area shall be carefully installed and suitably protected by the installation of heat resistant shielded loom.

All electrical equipment shall be installed to conform to the latest federal standards as outlined in NFPA 1901.

**BODY ELECTRICAL JUNCTION COMPARTMENT**

A weather resistant electric junction compartment shall be provided within the body or pump enclosure, depending on vehicle configuration. This compartment shall provide an easily accessible enclosure to house all of the body wiring junction points, terminal strips, solenoids, etc. The design of this compartment shall not decrease the storage capacity area of the compartment or area in which it is located. A removable panel shall be provided for access to this compartment.

**PUMP ENCLOSURE WORK LIGHTS**

Two (2) Tecniq model #E18 lights shall be provided inside the pump enclosure providing 800 lumens each. Each light shall have their own independent switch incorporated into the light head.

**ENGINE COMPARTMENT WORK LIGHTS**

Two (2) Tecniq model #E18 LED lights shall be provided inside the engine enclosure that will provide 800 lumens each. Each light shall have their own independent switch incorporated into the light head.

**AMDOR LUMA BAR COMPARTMENT LIGHTS - LED**

Each individual, equipment storage compartment shall be equipped with the AMDOR Luma Bar LED light fixture mounted one each side of the forward (and rear) vertical door frame.

**NFPA AUDIBLE AND LIGHTING WARNING PACKAGE**

The following warning light package shall include all of the minimum warning light and actuation requirements for the current revision of the NFPA 1901 Fire Apparatus Standard. The lighting as specified shall meet the requirements for both "Clearing Right of Way" and "Blocking Right of Way" which includes disabling all white warning lights when the apparatus is in "Blocking Right of Way" mode.

**LIGHT PACKAGE ACTUATION CONTROLS**

The entire warning light package shall be actuated with a single warning light switch located on the cab switch panel. The wiring for the warning light package shall engage all of the lights required for "Clearing Right of Way" mode when the vehicle parking brake is not engaged. An automatic control system shall be provided to switch the warning lights to the "Blocking Right of Way" mode when the vehicle parking brake is engaged.

**WARNING LIGHT FLASH PATTERN**

All of the perimeter warning lights shall be set to a default NFPA compliant flash pattern as provided by the light manufacturer.

**UPPER LEVEL LIGHTING - CODE 3**

**NFPA ZONE A, UPPER**

A Code 3 RMX80NFPA1W "RMX", 80" LED cab roof warning light bar shall be furnished and rigidly mounted on top of the cab roof.

The light bar shall be equipped with the following:

Upper Level

- Red Lenses
- Six Forward Facing - REF8 LED Red Modules
- Two Side Facing - REF8 LED Red Modules

Lower Level

- Clear Lenses
- Two Forward Facing - REF8 LED White Modules
- Two Corner Facing - REF12 LED Red Modules

If equipped, the forward facing white lights shall be automatically disabled for the "Blocking Right of Way" mode.

**NFPA ZONE C, UPPER**

Two (2) Code 3 798\*BZ-75, PriZm II LED lights, shall be furnished and mounted one (1) each side at the rear, upper portion of the apparatus.

Each light head shall be equipped with red LED's and a colored lens.

The lights shall be installed with a chrome plated mounting flange.

**NFPA ZONES B & D REAR, UPPER**

Two (2) surface mounted Code 3 7912\*BZ-75 PriZm II LED light heads shall be furnished and shall be mounted one (1) each side on the upper side face, towards the rear of the body, facing to each side of the unit.

Each light head shall be equipped with red LED's and a colored lens.

The lights shall be installed with a chrome plated mounting flange.

**NFPA ZONES B & D FRONT, UPPER**

Two (2) surface mounted Code 3 7912\*BZ-75 PriZm II LED light heads shall be furnished and mounted; one (1) each side on the upper side face, towards the front of the body, facing to each side of the unit.

Each light head shall be equipped with red LED's and a colored lens.

The lights shall be installed with a chrome plated mounting flange.

**LOWER LEVEL LIGHTING - CODE 3**

**NFPA ZONE A, LOWER**

Two (2) Code 3 4612\*BZ-75 PriZm II LED light heads shall be provided and installed one (1) each side.

Each light head shall be equipped with red LED's and a colored lens.

The lights shall be installed with a chrome plated mounting flange.

The lower Zone A warning lights shall be mounted in the custom chassis headlight bezels.

**NFPA ZONE C, LOWER**

Two (2) Code 3 4612\*BZ-75 PriZm II LED light heads shall be provided and installed; one (1) each side directly below the DOT stop, tail, turn and backup lights.

Each light head shall be equipped with red LED's and a colored lens.

The lights shall be installed with a chrome plated mounting flange.

**NFPA ZONES B & D FRONT, LOWER**

Two (2) Code 3 4612\*BZ-75 PriZm II LED light heads shall be provided and installed one (1) each side.

Each light head shall be equipped with red LED's and a colored lens.

The lights shall be installed with a chrome plated mounting flange.

The lower Zone B & D warning lights shall be mounted on the sides of the custom chassis front bumper.

**NFPA ZONES B & D MIDSHIP, LOWER**

Two (2) Code 3 4612\*BZ-75 PriZm II LED light heads shall be provided and installed one (1) each side.

Each light head shall be equipped with red LED's and a colored lens.

The lights shall be installed with a chrome plated mounting flange.

**NFPA ZONES B & D REAR, LOWER**

Two (2) Code 3 4612\*BZ-75 PriZm II LED light heads shall be provided and installed one (1) each side.

Each light head shall be equipped with red LED's and a colored lens.

The lights shall be installed with a chrome plated mounting flange.

**WARNING LIGHT SYSTEM CERTIFICATION**

The warning light system(s) specified above shall not exceed a combined total amperage draw of 45 AMPS with all lights activated in either the "Clearing Right of Way" or the "Blocking Right of Way" mode.

The warning light system(s) shall be certified by the light system manufacturer(s), to meet all of the requirements in the current revision of the NFPA 1901 Fire Apparatus Standard as noted in the General Requirements section of these specifications. The NFPA required "Certificate of Compliance" shall be provided with the completed apparatus.

Any large truck as defined by NFPA shall have the lower zone warning lights mounted no higher than 62" to the optical center of the warning light from ground level.

**ALTERNATING FLASHING HEADLIGHT SYSTEM**

An alternating flashing wig-wag system, wired to the apparatus headlights, shall be installed. The wig-wag system shall be individually switched at the master light console. The alternating flashing system shall be automatically disabled during the "Blocking Right of Way" mode.

**ARROW STICK WARNING LIGHT**

One (1) Code 3 LED, "LC Stik" Model #LC839, 39" rear directional light shall be installed on the rear of the body. The light shall be equipped with eight (8) lamps. The light shall be controlled from the cab. The control module shall be conveniently located near the driver's position. The rear directional light shall be wired through the load management system of the unit.

**TRAFFIC ADVISOR - MOUNTING ON THE REAR SHEET**

The traffic advisor shall be mounted on the rear sheet.

\*\*\*\*\* AUDIBLE WARNING EQUIPMENT \*\*\*\*\*

**ELECTRIC HORN**

A single electric horn activated by the steering wheel horn button shall be furnished.

**BACK-UP ALARM**

A Code 3, model # CA278, 87dBA back-up alarm, shall be provided and installed at the rear of the apparatus under the tailboard. The back-up alarm shall activate automatically when the transmission is placed in reverse gear and the ignition is "on".

**AIR HORNS**

Two (2) chrome plated air horns shall be at the front of the vehicle. The air horns shall be mounted in full compliance with NFPA-1901. The supply lines shall be dual 1/4" lines with equal distance from each horn.

Both air horns shall be recessed in the front bumper.

The air horn(s) shall be controlled by a foot switch on the officer's side and the steering horn button on driver's side. An air horn/electric DOT horn selector switch shall be furnished on the dash for the drivers steering horn button.

**ELECTRONIC SIREN**

One (1) Power Call model DX5200, 200 watt electronic siren shall be provided featuring: electronic air horn, wail, yelp, powercall, hi-low, whoop, phaser and "Intersection" mode siren tones. A hardwired microphone shall be provided for the public address feature.

The electronic siren and speaker shall meet the NFPA required SAE certification to ensure compatibility between the siren and speaker.

Two (2) Whelen, model # SA315P composite black siren speakers, shall be provided, recessed in the front bumper and wired to the electronic siren.

**FEDERAL Q2B MECHANICAL SIREN**

One (1) Federal Model #Q2B mechanical siren shall be provided to provide audible warning.

The Q2B siren shall be pedestal mounted on top of the extended bumper on the driver's side. The siren shall be equipped with a Federal model #P, chrome housing and pedestal.

Two (2) floor mounted foot switches shall be provided, one (1) for the officer and one (1) for the driver. A siren brake button shall be provided near the driver's position.

**FIRECOM MODEL #5100D DIGITAL INTERCOM SYSTEM**

A Firecom model # 5100D digital intercom system shall be provided in the front of the cab. The system shall be capable of interfacing with a two-way radio system (note: an authorized two-way radio installer shall be responsible for interfacing the intercom system with the two-way radio).

The 5100D master station shall have the following features:

- Single radio monitor and transmit selector switch
- Touch-pad adjustable volume and squeich
- Advanced digital signal processing noise-reduction
- Single auxiliary input/output connection
- Nominal 12v power supply
- Six (6) jacks for wireless base stations and/or wired headset connections; expandable up to twelve (12) daisy-chained wired headsets

The intercom system shall include:

**DRIVERS AND OFFICERS HEADSETS & BASE STATION FOR WIRELESS FIRECOM SYSTEM**

Two (2) UHW-505 wireless under helmet radio transmit headsets, shall be furnished for the driver and officer seating locations in the cab. The headsets shall have adjustable volume, noise-canceling electric microphone, adjustable head strap, a flex-style boom which rotates for left or right dress and a charging port to connect the 12 volt charger when the headset is not in use. The sets shall also have comfortable ComLeather ear seals.

One (1) wireless base station WB505R shall be connected via a 6 conductor flat RJ-6 cable to any headset port on the Firecom 5100D series intercom. The base station will provide full duplex audio communication between the wireless headset and the intercom as well as PTT communication through the apparatus mobile radio.

Two (2) 108-0678-00 yellow, NFPA compliant, rubber coated steel headset hanger hooks shall be furnished in the front section of the cab to hold the driver and offer intercom headsets while not in use.

**FIRECOM REMOTE HEAD**

A 5100DRH remote head shall be surface mounted in the cab as directed by the fire department. The remote head shall have the same controls as the master base station.

**RADIO INTERFACE CABLE**

One (1) radio interface cable, model # 110-5101-30 and one (1) extension cable model # 108-0086-00 shall be provided and installed from the firecom base unit to the area of where the mobile radio base station shall be mounted. The end of the cable that connects to the mobile radio shall be un-terminated and shall be the responsibility of the radio installer to provide and install the correct adapter to connect the cable to the mobile radio.

**REAR JUMPSEAT HEADSETS**

Eight (8) UH-52 single-plug under helmet intercom headsets shall be furnished for eight (8) rear jump seat locations. The intercom headsets shall have adjustable volume, noise-canceling electric microphone, adjustable head strap, and a flex-style boom which rotates for left or right dress. The sets shall also have comfortable ComLeather ear seals.

Eight (8) HM-10 plug in modules shall be furnished in the rear crew area of the cab at the jump seat locations to accommodate the intercom headsets.

Eight (8) yellow, NFPA compliant, rubber coated steel headset hanger hooks shall be furnished to hold the intercom headsets while not in use.

**WEATHER BAND AM/FM/CD RADIO**

A Weather Band/AM/FM, CD, MP3, Satellite ready player with a wireless remote shall be installed in the cab overhead panel as space allows. The speakers shall be located as follows:

- (2) 6 inch mounted in the Front of the cab
- (2) 6 inch mounted in the Rear of the cab

A heavy duty flexible base antenna shall be provided on the cab.

\*\*\*\* PUMP AND PLUMBING \*\*\*\*

**PUMP**

- HALE QMAX-200
- 2000 G.P.M.
- Single Stage

The pump must deliver the percentage of rated capacity at the pressure listed below:

- 100% of rated capacity at 150 P.S.I. net pump pressure
- 100% of rated capacity at 165 P.S.I. net pump pressure
- 70% of rated capacity at 200 P.S.I. net pump pressure
- 50% of rated capacity at 250 P.S.I. net pump pressure.

**PUMP ASSEMBLY**

The pump shall be of a size and design to mount on the chassis rails of commercial and custom truck chassis, and have the capacity of 2000 gallons per minute (U.S. GPM), NFPA-1901 rated performance.

**PUMP CONSTRUCTION**

The entire pump shall be manufactured and tested at the pump manufacturer's factory.

The pump shall be driven by a drive line from the truck transmission. The engine shall provide sufficient horsepower and RPM to enable the pump to meet and exceed its rated performance.

The entire pump, both suction and discharge passages, shall be hydrostatically tested to a pressure of 600 PSI. The pump shall be fully tested at the pump manufacturer's factory to performance specs as outlined by the latest NFPA-1901. Pump shall be free from objectionable pulsation and vibration.

The pump body and related parts shall be of fine grain alloy cast iron with a minimum tensile strength of 30,000 PSI. All moving parts in contact with water shall be of high quality bronze or stainless steel. Pumps utilizing castings made of lower tensile strength cast iron are not acceptable.

Pump body shall be horizontally split, on a single plane in two sections for easy removal of entire impeller assembly including wear rings and bearings from beneath the pump without disturbing piping or the mounting of the pump in chassis.

**PUMP SHAFT**

Pump shaft to be rigidly supported by three bearings for minimum deflection. One high lead bronze sleeve bearing shall be located immediately adjacent to the impeller (on side opposite the gearbox). The sleeve bearing is to be lubricated by a force fed, automatic oil lubricated design, pressure balanced to exclude foreign material.

The pump shaft shall be heat-treated, electric furnace, corrosion resistant stainless steel to be super-finished under packing with galvanic corrosion (zinc foil separators in packing) protection for longer shaft life. Pump shaft must be sealed with double-lip oil seal to keep road dirt and water out of gearbox.

**PUMP IMPELLER**

The pump shall have one double suction impeller. The pump body shall have two opposed discharge volute cutwaters to eliminate radial unbalance. (No exceptions)

Pump impeller shall be hard, fine grain bronze of the mixed flow design; accurately machined and individually balanced. The vanes of the impeller intake eyes shall be of sufficient size and design to provide ample reserve capacity utilizing minimum horsepower.

Impeller clearance rings shall be bronze, easily renewable without replacing impeller or pump volute body, and of wrap-around double labyrinth design for maximum efficiency.

**PUMP PACKING GLAND**

The pump shaft shall have only one (1) packing gland located on inlet side of the pump. It shall be a split design for ease of repacking. The packing gland must be a full circle threaded design to exert uniform pressure on packing and to prevent cocking and uneven packing load when it is tightened. It shall be easily adjusted by hand with rod or screwdriver with no special tools or wrenches required. The packing rings shall be of a unique permanently lubricated, long life graphite composition and have sacrificial zinc foil separators to protect the pump shaft from galvanic corrosion.

**PUMP DRIVE UNIT**

The drive unit shall be completely assembled and tested at the pump manufacturer's factory.

Pump drive unit shall be of sufficient size to withstand up to 16,000 lbs. ft. of torque of the engine in both road and pump operating conditions. The drive unit shall be designed of ample capacity for lubrication reserve and to maintain the proper operating temperature.

The gearbox drive shafts shall be of heat treated chrome nickel steel and at least 2-3/4 inches in diameter on both the input and output drive shafts. They shall withstand the full torque of the engine in both road and pump operating conditions.

All gears, both drive and pump, shall be of the highest quality electric furnace chrome nickel steel. Bores shall be ground to size and teeth integrated, chrome-shaven and hardened, to give an extremely accurate gear for long life, smooth, quiet running and higher load carrying capability. An accurately cut spur design shall be provided to eliminate all possible end thrust.

**PUMP RATIO**

The pump ratio shall be selected by the apparatus manufacturer to give maximum performance with the engine and transmission selected.

The manufacturer shall supply at time of delivery copies of the pump manufacturer's certification of hydrostatic testing, the engine manufacturer's current certified brake horsepower curve.

**PUMP SHIFT CONTROL**

The drive unit shall be equipped with a power shift. The shifting mechanism shall be a heat treated, hard anodized aluminum power cylinder with stainless steel shaft. An air operated in-cab control for rapid shift shall be provided that locks in road or pump, with a neutral position for use when manual override is required.

**EMERGENCY PUMP SHIFT**

An emergency manual pump shift control shall be furnished on the left side pump panel which may be utilized if the air shift control does not operate.

A transmission, manual lock-up switch shall be furnished in the cab to ensure positive lock-up of the transmission.

**MAIN PUMP - PUMP SHIFT INDICATOR LIGHTS**

For automatic transmissions, three (3) green warning lights shall be provided to indicate to the operator(s) when the pump has completed the shift for Road to Pump position. Two (2) green lights to be located in the truck driving compartment and one (1) green light on pump operator's panel adjacent to the throttle control. For manual transmissions, one (1) green warning light shall be provided for the driving compartment. All lights to have appropriate identification/instruction plates.

**TRANSMISSION LOCK**

The automatic transmission furnished in the chassis shall have a lock-up assembly which brings the transmission to direct drive and prevents the transmission from shifting gears while in the pumping mode.

**BRAKING SYSTEM**

A positive braking system shall be provided to prevent vehicle movement during pumping operations. The air brakes furnished must satisfy this requirement.

**MAIN PUMP MOUNTS**

Extra heavy duty pump mounting brackets shall be furnished. These shall be bolted to the frame rails in such a position to perfectly align the pump so that the angular velocity of the drive line joints shall be the same on each end of the drive shaft. This shall assure full capacity performance with a minimum of vibration. Mounting hardware shall utilize Grade 8 bolts.

Pumps which are not mounted directly to the frame will not be considered. Under no circumstance shall the pump function as a frame cross member.

\*\*\*\*\* PRESSURE CONTROL & ACCESSORIES \*\*\*\*\*

**FIRE RESEARCH "IN-CONTROL" PRESSURE GOVERNOR**

The apparatus shall be equipped with a Fire Research InControl series TGA300 pressure governor and monitoring display kit shall be installed. The kit shall include a control module, intake pressure sensor, discharge pressure sensor, and cables. The control module case shall be waterproof and have dimensions not to exceed 5 1/2" high by 10 1/2" wide by 2" deep. Inputs for monitored information shall be from a J1939 databus or independent sensors. Outputs for engine control shall be on the J1939 databus or engine specific wiring.

The following continuous displays shall be provided:

- Pump discharge; shown with four daylight bright LED digits more than 1/2" high
- Pump Intake; shown with four daylight bright LED digits more than 1/2" high
- Pressure / RPM setting; shown on a dot matrix message display
- Pressure and RPM operating mode LEDs
- Throttle ready LED
- Engine RPM; shown with four daylight bright LED digits more than 1/2" high
- Check engine and stop engine warning LEDs
- Oil pressure; shown on a dual color (green/red) LED bar graph display
- Engine coolant temperature; shown on a dual color (green/red) LED bar graph display
- Transmission Temperature; shown on a dual color (green/red) LED bar graph display
- Battery voltage; shown on a dual color (green/red) LED bar graph display.
- The dot-matrix message display shall show diagnostic and warning messages as they occur. It shall show monitored apparatus information, stored data, and program options when selected by the operator. All LED intensity shall be automatically adjusted for day and night time operation.

The program shall store the accumulated operating hours for the pump and engine to be displayed with the push of a button. It shall monitor inputs and support audible and visual warning alarms for the following conditions:

- High Battery Voltage
- Low Battery Voltage (Engine Off)
- Low Battery Voltage (Engine Running)
- High Transmission Temperature
- Low Engine Oil Pressure
- High Engine Coolant Temperature
- Out of Water (visual alarm only)
- No Engine Response. (visual alarm only)

The program features shall be accessed via push buttons located on the front of the control panel. There shall be an USB port located at the rear of the control module to upload future firmware enhancements.

Inputs to the control panel from the pump discharge and intake pressure sensors shall be electrical. The discharge pressure display shall show pressures from 0 to 600 psi. The intake pressure display shall show pressures from -30 in. Hg to 600 psi.

The governor shall operate in two control modes, pressure and RPM. No discharge pressure or engine RPM variation shall occur when switching between modes. A throttle ready LED shall light when the interlock signal is recognized. The governor shall start in pressure mode and set the engine RPM to idle. In pressure mode the governor shall automatically regulate the discharge pressure at the level set by the operator. In RPM mode the governor shall maintain the engine RPM at the level set by the operator except in the event of a discharge pressure increase. The governor shall limit a discharge pressure increase in RPM mode to a maximum of 30 psi. Other safety features shall include recognition of no water conditions with an automatic programmed response and a push button to return the engine to idle.

The pressure governor, monitoring and master pressure display shall be programmed to interface with a specific engine.

**AKRON INTAKE RELIEF VALVE**

A 300 psi adjustable Akron Model 591103 intake relief valve system shall be plumbed on the suction side of the pump to comply fully with NFPA-1901 requirements. Excess pressures shall be plumbed to discharge water under the pump enclosure away from the pump operator.

**PUMP CERTIFICATION**

The pump shall be third party performance tested to meet the requirements of NFPA-1901. To ensure top quality and integrity, the test company shall be Underwriters Laboratories (UL).

**PUMP PRIMER**

The priming pump will be a Trident air primer system. A push in primer handle will open the priming valve and prime the pump.

**MASTER DRAIN VALVE**

A rotary type, 12 port master drain valve shall be provided and controlled at the lower portion of the side pump panel. The valve shall be located in pump compartment lower than the main body and connected in such a manner as to allow complete water drainage of the pump body and all required accessories. Water shall be drained below the apparatus body and away from the pump operator.

**INDIVIDUAL BLEEDERS AND DRAINS**

All lines shall drain through the master drain valve or shall be equipped with individual drain valves, easily accessible and labeled.

One (1) individual "Innovative Control" lift up drain valve shall be furnished for each 1-1/2" or larger discharge port and each 2-1/2" gated auxiliary suction.

Drain/bleeder valves shall be located at the bottom of the side pump module panels.

All drains and bleeders shall discharge below the running boards.

**SYNFLEX SUCTION, DISCHARGE, PRESSURE AND CONTROL LINES**

Small lines within the pump enclosure shall be constructed from Synflex hose. Uses include, but are not limited to such lines as priming control, gauge lines, drain lines, air control valves, pump shift, supplemental cooling, foam flush and air bleeder valves.

**PUMP MODULE**

The pump module shall be a self-supported structure mounted independently from the body and chassis cab. The design must allow normal frame deflection without imposing stress on the pump module structure or side running boards. The pump module shall be securely mounted to the chassis frame rails.

The pump module shall be a welded frame work utilizing structural steel components properly braced to withstand the rigors of chassis frame flex.

**DUNNAGE AREA**

A dunnage area shall be provided above the pump enclosure for equipment mounting and storage. This area shall be furnished with a removable 3/16" aluminum tread plate floor and shall be enclosed on the sides.

NOTE: The size of this storage area may vary when top mounted crosslays, booster reel(s), etc., are specified and located in this area.

\*\*\*\*\* PUMP SUCTIONS & AUXILIARY INLETS \*\*\*\*\*

**SUCTION INLETS**

Two (2) 6" N.S.T. suction inlets shall be provided, one on the driver side and one on the officer side pump panel. A removable strainer shall be installed on each inlet.

**PUMP SUCTION ENDS**

The main pump suction inlets shall be furnished with a short suction end, terminating with only the suction threads protruding through the side panel to minimize the distance an exterior appliance protrudes beyond the pump panel.

A 6" NST chrome plated long handle pressure vented cap shall be installed on each main inlet of the pump.

**FRONT SUCTION**

A 6" N.S.T. front suction inlet shall be provided at the front of the vehicle, plumbed from the pump.

The front inlet shall be located above the right hand side of the front bumper extension and shall terminate with a chromed brass, chickens style swivel to allow a minimum of 180 degree rotation of the inlet for suction hose attachment.

The front suction pipe shall be equipped with a chrome 6" NSTM thread adapter.

The front inlet shall be plumbed utilizing 5", schedule 10 stainless steel piping, 45 degree elbows and a limited number of 90 degree sweep elbows in an assembly from the pump to the front of the cab. A manual drain shall be provided ahead of the front wheel and a panel controlled drain shall be provided aft of the front wheel.

A minimum of two (2) grooved pipe couplings shall be furnished in this assembly to allow for flex and serviceability.

The front suction plumbing shall be fitted with a Hale Master Intake Valve (MIV), on the front suction inlet. The valve shall be in the pump enclosure area with a manual override located directly on the valve actuator. The valve body and all related components that are in contact with water shall be manufactured of fine grained, corrosion resistant bronze.

The valve housing shall incorporate a pressure relief valve, set at the pump manufacturer's facility to a rating of 125 PSI. The pressure relief valve shall provide protection for the suction hose even with the valve in the closed position. The valve shall incorporate NFPA compliance, large diameter hose air bleed valve, controlled at the operator's panel.

The front suction valve shall be operated by a twelve (12) volt DC motor, controlled from the pump operator's panel. It shall also incorporate a manual override, mounted at the valve. The electric control shall incorporate a placard with status lights to indicate whether the valve is in the closed, open or throttled position. The valve shall not be able to move from fully open to fully closed in under three (3) seconds, in compliance with NFPA-1901.

One (1) 6" NST chrome plated long handle vented cap(s) shall be installed on front suction.

**AUXILIARY SIDE SUCTION(S)**

One (1) 2-1/2" auxiliary suction shall be provided at the driver side pump panel, to the rear of the main inlet. The 2-1/2" auxiliary suction shall terminate with a removable strainer, chrome plated 2-1/2" NST female swivel with a chrome plated plug and retaining chain.

**Header Title**

Bidder Complies

YES

NO

An Akron Brass 2 1/2" Generation II Swing-Out™ Valve shall be provided for the driver's side rear auxiliary suction. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats.

A 1/4 turn swing control handle shall be provide on the driver side rear auxiliary suction valve

All side gated inlet valves shall be recess mounted behind the side pump panels or body panels.

**TANK TO PUMP**

One (1) 4" tank to pump line shall be piped through the front bulkhead of the tank with a 90 degree elbow down into the tank sump. This line shall be plumbed directly into the rear of the pump suction manifold for maximum efficiency.

A check valve shall be provided to prevent accidental pressurization of the water tank through the pump connection. Connection from the valve to the tank shall be made by using a non-collapsible flexible rubber hose.

An Akron Brass 3" Generation II Swing-Out™ Valve shall be provided between the pump suction manifold and the water tank. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats.

A push/pull control handle shall be located on the operator's panel with function plate.

**TANK FILL**

One (1) 2 1/2" gated full flow pump to tank refill line controlled at the pump panel shall be provided. A deflector shield inside the tank shall be furnished. Tank fill plumbing shall utilize 2 1/2" high pressure hose for tank connection to accommodate flexing between components.

An Akron Brass 2 1/2" Generation II Swing-Out™ Valve shall be provided between the pump discharge manifold and the water tank. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats.

A push/pull control handle shall be located on the operator's panel with function plate.

**\*\*\*\*\* DISCHARGES & ACCESSORIES - SIDE MOUNT \*\*\*\*\***

**DRIVER'S SIDE MAIN DISCHARGE #1**

A discharge shall be provided and located at the driver's side pump panel. The driver's side discharges # 1 shall terminate with NST threads, through the left panel above the main pump intake.

The main pump discharge shall be plumbed directly from the pump discharge manifold utilizing direct connect discharge valve flanges.

An Akron Brass 2 1/2" Generation II Swing-Out™ Valve shall be provided for the driver's side #1 discharge. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats.

The discharge valve shall be equipped with a straight 2 1/2" NST adapter that shall be equipped with a 2 1/2" NST, 30-degree, chrome plated elbow.

The driver's side #1 discharge cap provided as standard equipment shall be deleted.

One (1) 2-1/2" NSTF X 1-1/2" NSTM reducer with cap shall be provided on the driver's side # 1 discharge.

The driver's side # 1 discharge valve shall be controlled by a push/pull handle located on the operator's panel.

The driver's side # 1 discharge shall be equipped with a 2 1/2" diameter Innovative Controls pressure gauge. The gauge shall have a rugged corrosion free stainless steel case and clear scratch resistant molded crystals with captive O-ring seals to ensure distortion free viewing and seal the gauge. The gauge shall be filled with glycerin to dampen shock and vibration, lubricate the internal mechanisms, prevent lens condensation and ensure proper operation from -40°F to +160°F.

The gauge shall exceed ANSI B40.1 Grade A requirements with an accuracy of +/- 1.5% full scale and include a size appropriate phosphorous bronze bourdon tube with a reinforced lap joint and large tube base to increase the tube life and gauge accuracy.

A polished chrome-plated stainless steel bezel shall be provided to prevent corrosion and protect the lens and gauge case. The gauge shall have black graphics on a white background.

**DRIVER'S SIDE MAIN DISCHARGE #2**

A discharge shall be provided and located at the driver's side pump panel. The driver's side discharges # 2 shall terminate with NST threads, through the left panel above the main pump intake.

The main pump discharge shall be plumbed directly from the pump discharge manifold utilizing direct connect discharge valve flanges.

An Akron Brass 2 1/2" Generation II Swing-Out™ Valve shall be provided for the driver's side #2 discharge. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seat.

The discharge valve shall be equipped with a straight 2 1/2" NST adapter that shall be equipped with a 2 1/2" NST, 30-degree, chrome plated elbow.

The driver's side # 2 discharge cap provided as standard equipment shall be deleted.

A 2-1/2" NSTF X 1-1/2" NSTM reducer with cap shall be provided on the driver's side # 2 discharge.

The driver's side # 2 discharge valve shall be controlled by a push/pull handle located on the operator's panel.

The driver's side # 2 discharge shall be equipped with a 2 ½" diameter Innovative Controls pressure gauge. The gauge shall have a rugged corrosion free stainless steel case and clear scratch resistant molded crystals with captive O-ring seals to ensure distortion free viewing and seal the gauge. The gauge shall be filled with glycerin to dampen shock and vibration, lubricate the internal mechanisms, prevent lens condensation and ensure proper operation from -40°F to +160°F.

The gauge shall exceed ANSI B40.1 Grade A requirements with an accuracy of +/- 1.5% full scale and include a size appropriate phosphorous bronze bourdon tube with a reinforced lap joint and large tube base to increase the tube life and gauge accuracy.

A polished chrome-plated stainless steel bezel shall be provided to prevent corrosion and protect the lens and gauge case. The gauge shall have black graphics on a white background.

**OFFICER'S SIDE MAIN DISCHARGE #1**

A discharge shall be provided and located at the officer's side pump panel. The officer's side discharges #1 shall terminate with NST threads, through the officer's side panel above the main pump intake.

The main pump discharge shall be plumbed directly from the pump discharge manifold utilizing direct connect discharge valve flanges.

An Akron Brass 4" Heavy Duty Swing-Out™ Valve shall be provided for the officer's side #1 discharge. The valve shall have an all brass body with flow optimizing flat ball and dual polymer seats

The discharge valve shall be equipped with a straight 4" NST adapter.

The officer's side # 1 discharge cap provided as standard equipment shall be deleted.

A 4" NSTF X 5" Storz Kocheck SKE-R 30° adapter with cap shall be provided on the officer's side # 1 discharge.

The officer's side # 1 discharge valve shall be gated with an Akron Hand wheel controlled, inline valve. The valve shall be controlled at the pump operator's panel with a chrome plated hand wheel and mechanical valve position indicator.

The officer's side # 1 discharge shall be equipped with a 2 ½" diameter Innovative Controls pressure gauge. The gauge shall have a rugged corrosion free stainless steel case and clear scratch resistant molded crystals with captive O-ring seals to ensure distortion free viewing and seal the gauge. The gauge shall be filled with glycerin to dampen shock and vibration, lubricate the internal mechanisms, prevent lens condensation and ensure proper operation from -40°F to +160°F.

The gauge shall exceed ANSI B40.1 Grade A requirements with an accuracy of +/- 1.5% full scale and include a size appropriate phosphorous bronze bourdon tube with a reinforced lap joint and large tube base to increase the tube life and gauge accuracy.

A polished chrome-plated stainless steel bezel shall be provided to prevent corrosion and protect the lens and gauge case. The gauge shall have black graphics on a white background.

**OFFICER'S SIDE MAIN DISCHARGE #2**

A discharge shall be provided and located at the officer's side pump panel. The officer's side discharges #2 shall terminate with NST threads, through the officer's side panel above the main pump intake.

The main pump discharge shall be plumbed directly from the pump discharge manifold utilizing direct connect discharge valve flanges.

An Akron Brass 2 1/2" Generation II Swing-Out™ Valve shall be provided for the officer's side #2 discharge. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats.

The discharge valve shall be equipped with a straight 2 1/2" NST adapter that shall be equipped with a 2 1/2" NST, 30-degree, chrome plated elbow.

The officer's side #2 discharge cap provided as standard equipment shall be deleted.

A 2-1/2" NSTF X 1-1/2" NSTM reducer w/cap shall be provided on the officer's side #2 discharge.

The officer's side #2 discharge valve shall be controlled by a push/pull handle located on the operator's panel.

The officer's side #2 discharge shall be equipped with a 2 1/2" diameter Innovative Controls pressure gauge. The gauge shall have a rugged corrosion free stainless steel case and clear scratch resistant molded crystals with captive O-ring seals to ensure distortion free viewing and seal the gauge. The gauge shall be filled with glycerin to dampen shock and vibration, lubricate the internal mechanisms, prevent lens condensation and ensure proper operation from -40°F to +160°F.

The gauge shall exceed ANSI B40.1 Grade A requirements with an accuracy of +/- 1.5% full scale and include a size appropriate phosphorous bronze bourdon tube with a reinforced lap joint and large tube base to increase the tube life and gauge accuracy.

A polished chrome-plated stainless steel bezel shall be provided to prevent corrosion and protect the lens and gauge case. The gauge shall have black graphics on a white background.

**DRIVER SIDE HOSE BED DISCHARGE**

A 2 1/2" NST rear hose bed discharge shall be plumbed to the upper front body panel, extending into the front of the hose bed.

The rear hose bed discharge shall terminate just above the hosebed floor, in the driver side front of the hose bed.

The driver side hose bed discharge pipe shall be equipped with a chrome 2 1/2" NSTM thread adapter.

The driver side hose bed discharge shall be plumbed utilizing 2 1/2" schedule 10 stainless steel piping, 45 degree elbows and a limited number of 90 degree sweep elbows in an assembly from the pump to the rear of the vehicle.

A minimum of one (1) grooved pipe coupling shall be furnished in this assembly to allow for flex and serviceability.

An Akron Brass 2 1/2" Generation II Swing-Out™ Valve shall be provided for the driver's side hose bed rear discharge. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats.

The driver side hose bed discharge valve shall be controlled by a push/pull handle located on the operator's panel.

One (1) 2 1/2" NST chrome plated pressure vented cap shall be installed the driver's side hose bed discharge.

The driver's side hose bed discharge shall be equipped with a 2 1/2" diameter Innovative Controls pressure gauge. The gauge shall have a rugged corrosion free stainless steel case and clear scratch resistant molded crystals with captive O-ring seals to ensure distortion free viewing and seal the gauge. The gauge shall be filled with glycerin to dampen shock and vibration, lubricate the internal mechanisms, prevent lens condensation and ensure proper operation from -40°F to +160°F.

The gauge shall exceed ANSI B40.1 Grade A requirements with an accuracy of +/- 1.5% full scale and include a size appropriate phosphorous bronze bourdon tube with a reinforced lap joint and large tube base to increase the tube life and gauge accuracy.

A polished chrome-plated stainless steel bezel shall be provided to prevent corrosion and protect the lens and gauge case. The gauge shall have black graphics on a white background.

**OFFICER'S SIDE HOSE BED DISCHARGE**

A 2 1/2" NST rear hose bed discharge shall be plumbed to the upper front body panel, extending into the front of the hose bed.

The rear hose bed discharge shall terminate just above the hose bed floor, in the officer's side front of the hose bed.

The officer's side hose bed discharge pipe shall be equipped with a chrome 2 1/2" NSTM thread adapter.

The officer's side hose bed discharge shall be plumbed utilizing 2 1/2" schedule 10 stainless steel piping, 45 degree elbows and a limited number of 90 degree sweep elbows in an assembly from the pump to the rear of the vehicle.

A minimum of one (1) grooved pipe coupling shall be furnished in this assembly to allow for flex and serviceability.

An Akron Brass 2 1/2" Generation II Swing-Out™ Valve shall be provided for the hose bed officer's side rear discharge. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats.

The officer's side hose bed discharge valve shall be controlled by a push/pull handle located on the operator's panel.

One (1) 2 1/2" NST chrome plated pressure vented cap shall be installed the officer's side hose bed discharge.

The officer's side hose bed discharge shall be equipped with a 2 1/2 " diameter Innovative Controls pressure gauge. The gauge shall have a rugged corrosion free stainless steel case and clear scratch resistant molded crystals with captive O-ring seals to ensure distortion free viewing and seal the gauge. The gauge shall be filled with glycerin to dampen shock and vibration, lubricate the internal mechanisms, prevent lens condensation and ensure proper operation from -40°F to +160°F.

The gauge shall exceed ANSI B40.1 Grade A requirements with an accuracy of +/- 1.5% full scale and include a size appropriate phosphorous bronze bourdon tube with a reinforced lap joint and large tube base to increase the tube life and gauge accuracy.

A polished chrome-plated stainless steel bezel shall be provided to prevent corrosion and protect the lens and gauge case. The gauge shall have black graphics on a white background.

**DECK GUN DISCHARGE**

A deck gun discharge shall be plumbed from the pump to an area on top of the vehicle. The deck gun piping shall be firmly supported and braced.

The deck gun discharge shall be located in the center of the dunnage area above the pump module. A pedestal type, 1/4" steel plate support assembly shall be provided to stabilize deck gun plumbing below deck gun mount flange.

The deck gun discharge pipe shall terminate with 3" NPT threads.

To improve the operation range of the deck gun, the discharge pipe shall be outfitted with a TFT (12") Extend-A-Gun, part # XG12VL-PL. The Extend-A-Gun shall be wired to the hazard light on the cab dash.

**WARNING LIGHT - IN CAB - "DECK GUN RAISED"**

A hazzard warning light shall be installed to alert the driver, "Deck Gun Raised".

The deck gun piping shall be designed so the overall height of the deck gun in the mounted/stowed position does not exceed the tallest point on the cab/body.

The deck gun discharge shall be plumbed utilizing 3" schedule 10 stainless steel piping, 45 degree elbows and a limited number of 90 degree sweep elbows in an assembly from the pump to the deck gun location.

A minimum of one (1) grooved pipe coupling shall be furnished in this assembly to allow for flex and serviceability.

An Akron Brass 3" Generation II Swing-Out™ Valve shall be provided for the deck gun discharge. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats.

The deck gun discharge valve shall be controlled by a push/pull handle located on the operator's panel.

The deck gun discharge shall be equipped with a 2 1/2" diameter Innovative Controls pressure gauge. The gauge shall have a rugged corrosion free stainless steel case and clear scratch resistant molded crystals with captive O-ring seals to ensure distortion free viewing and seal the gauge. The gauge shall be filled with glycerin to dampen shock and vibration, lubricate the internal mechanisms, prevent lens condensation and ensure proper operation from -40°F to +160°F.

The gauge shall exceed ANSI B40.1 Grade A requirements with an accuracy of +/- 1.5% full scale and include a size appropriate phosphorous bronze bourdon tube with a reinforced lap joint and large tube base to increase the tube life and gauge accuracy.

A polished chrome-plated stainless steel bezel shall be provided to prevent corrosion and protect the lens and gauge case. The gauge shall have black graphics on a white background.

**TFT MANUAL DECK GUN**

A TFT model #XFC-52 deck gun package which shall include the Safe-Tak ground base with dual 2-1/2" inlets, the Cross Fire monitor top, one (1) set of quad stack tips, one (1) Master Stream 1000 GPM. automatic nozzle, stream straightener and a ground base compartment mounting bracket.

**DECK GUN PAINT**

The deck gun, pipe and flange shall be painted job color PPG # Job Color - \_\_\_\_\_.

**FRONT DISCHARGE**

A 1 1/2" front #1 discharge shall be plumbed to the front bumper of the vehicle.

The front #1 discharge shall terminate on the top center of the front bumper extension gravel shield with a chrome 1 1/2" NSTM chicksan swivel adapter.

The front #1 discharge shall be plumbed utilizing 2" schedule 10 stainless steel piping and/or flexible hose, 45 degree elbows and a limited number of 90 degree sweep elbows in an assembly from the pump to the front of the vehicle.

A minimum of one (1) grooved pipe coupling shall be furnished in this assembly to allow for flex and serviceability. Automatic discharge drains shall be provided at all low points in the plumbing.

An Akron Brass 2" Generation II Swing-Out™ Valve shall be provided for the front #1 discharge. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats.

The front #1 discharge valve shall be controlled by a push/pull handle located on the operator's panel.

A 1 1/2" NST chrome plated pressure vented cap shall be installed the front #1 discharge.

The front #1 discharge shall be equipped with a 2 1/2" diameter Innovative Controls pressure gauge. The gauge shall have a rugged corrosion free stainless steel case and clear scratch resistant molded crystals with captive O-ring seals to ensure distortion free viewing and seal the gauge. The gauge shall be filled with glycerin to dampen shock and vibration, lubricate the internal mechanisms, prevent lens condensation and ensure proper operation from -40°F to +160°F.

The gauge shall exceed ANSI B40.1 Grade A requirements with an accuracy of +/- 1.5% full scale and include a size appropriate phosphorous bronze bourdon tube with a reinforced lap joint and large tube base to increase the tube life and gauge accuracy.

A polished chrome-plated stainless steel bezel shall be provided to prevent corrosion and protect the lens and gauge case. The gauge shall have black graphics on a white background.

**HORIZONTAL CROSSLAY #1**

A crosslay hose bed shall be provided and plumbed from the pump in a transverse design, located above the pump enclosure for quick attack deployment. The crosslay hose bed flooring shall be designed to be removable, constructed from brushed finish, perforated aluminum material.

Crosslay #1 shall be designed to have a minimum total capacity of 3.5 cubic feet as required by NFPA -1901 to accommodate a minimum of 200 feet of 1-3/4" fire hose.

Crosslay #1 hose bed shall be designed to accommodate the fire hose in a single stack configuration.

The crosslay discharge shall terminate below the hosebed floor with a 1 1/2" NSTM chicksan swivel adapter. The crosslay hose bed floor shall be slotted to allow the swivel to extend up through the floor, allowing the pre-connected hose to be pulled off either side of the apparatus without kinking the hose at the coupling connection.

The crosslay #1 discharge shall be plumbed utilizing 2" schedule 10 stainless steel piping and/or flexible hose, 45 degree elbows and a limited number of 90 degree sweep elbows in an assembly from the pump to crosslay hose bed.

A minimum of one (1) grooved pipe coupling shall be furnished in this assembly to allow for flex and serviceability.

An Akron Brass 2" Generation II Swing-Out™ Valve shall be provided for the crosslay #1 discharge. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats.

The crosslay #1 discharge valve shall be controlled by a push/pull handle located on the operator's panel.

The crosslay #1 discharge shall be equipped with a 2 1/2" diameter Innovative Controls pressure gauge. The gauge shall have a rugged corrosion free stainless steel case and clear scratch resistant molded crystals with captive O-ring seals to ensure distortion free viewing and seal the gauge. The gauge shall be filled with glycerin to dampen shock and vibration, lubricate the internal mechanisms, prevent lens condensation and ensure proper operation from -40°F to +160°F.

The gauge shall exceed ANSI B40.1 Grade A requirements with an accuracy of +/- 1.5% full scale and include a size appropriate phosphorous bronze bourdon tube with a reinforced lap joint and large tube base to increase the tube life and gauge accuracy.

A polished chrome-plated stainless steel bezel shall be provided to prevent corrosion and protect the lens and gauge case. The gauge shall have black graphics on a white background.

**HORIZONTAL CROSSLAY #2**

A crosslay hose bed shall be provided and plumbed from the pump in a transverse design, located above the pump enclosure for quick attack deployment. The crosslay hose bed flooring shall be designed to be removable, constructed from brushed finish, perforated aluminum material.

Crosslay #2 shall be designed to have a minimum total capacity of 3.5 cubic feet as required by NFPA -1901 to accommodate a minimum of 200 feet of 1-3/4" fire hose.

Crosslay #2 hose bed shall be designed to accommodate the fire hose in a single stack configuration.

The crosslay discharge shall terminate below the hose bed floor with a 1 1/2" NSTM chicksan swivel adapter. The crosslay hose bed floor shall be slotted to allow the swivel to extend up through the floor, allowing the pre-connected hose to be pulled off either side of the apparatus without kinking the hose at the coupling connection.

The crosslay #2 discharge shall be plumbed utilizing 2" schedule 10 stainless steel piping and/or flexible hose, 45 degree elbows and a limited number of 90 degree sweep elbows in an assembly from the pump to crosslay hose bed.

A minimum of one (1) grooved pipe coupling shall be furnished in this assembly to allow for flex and serviceability.

An Akron Brass 2" Generation II Swing-Out™ Valve shall be provided for the crosslay #2 discharge. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats.

The crosslay #2 discharge valve shall be controlled by a push/pull handle located on the operator's panel.

The crosslay #2 discharge shall be equipped with a 2 1/2" diameter Innovative Controls pressure gauge. The gauge shall have a rugged corrosion free stainless steel case and clear scratch resistant molded crystals with captive O-ring seals to ensure distortion free viewing and seal the gauge. The gauge shall be filled with glycerin to dampen shock and vibration, lubricate the internal mechanisms, prevent lens condensation and ensure proper operation from -40°F to +160°F.

The gauge shall exceed ANSI B40.1 Grade A requirements with an accuracy of +/- 1.5% full scale and include a size appropriate phosphorous bronze bourdon tube with a reinforced lap joint and large tube base to increase the tube life and gauge accuracy.

A polished chrome-plated stainless steel bezel shall be provided to prevent corrosion and protect the lens and gauge case. The gauge shall have black graphics on a white background.

**HORIZONTAL CROSSLAY #3**

A crosslay hose bed shall be provided and plumbed from the pump in a transverse design, located above the pump enclosure for quick attack deployment. The crosslay hose bed flooring shall be designed to be removable, constructed from brushed finish, perforated aluminum material.

Crosslay #3 shall be designed to have a minimum total capacity of 3.5 cubic feet as required by NFPA -1901 to accommodate a minimum of 200 feet of 1-3/4" fire hose.

Crosslay #3 hosebed shall be designed to accommodate the fire hose in a single stack configuration.

The crosslay discharge shall terminate below the hose bed floor with a 1 1/2" NSTM chicksan swivel adapter. The crosslay hose bed floor shall be slotted to allow the swivel to extend up through the floor, allowing the pre-connected hose to be pulled off either side of the apparatus without kinking the hose at the coupling connection.

The crosslay #3 discharge shall be plumbed utilizing 2" schedule 10 stainless steel piping and/or flexible hose, 45 degree elbows and a limited number of 90 degree sweep elbows in an assembly from the pump to crosslay hose bed.

A minimum of one (1) grooved pipe coupling shall be furnished in this assembly to allow for flex and serviceability.

An Akron Brass 2" Generation II Swing-Out™ Valve shall be provided for the crosslay #3 discharge. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats.

The crosslay #3 discharge valve shall be controlled by a push/pull handle located on the operator's panel.

The crosslay #3 discharge shall be equipped with a 2 ½" diameter Innovative Controls pressure gauge. The gauge shall have a rugged corrosion free stainless steel case and clear scratch resistant molded crystals with captive O-ring seals to ensure distortion free viewing and seal the gauge. The gauge shall be filled with glycerin to dampen shock and vibration, lubricate the internal mechanisms, prevent lens condensation and ensure proper operation from -40°F to +160°F.

The gauge shall exceed ANSI B40.1 Grade A requirements with an accuracy of +/- 1.5% full scale and include a size appropriate phosphorous bronze bourdon tube with a reinforced lap joint and large tube base to increase the tube life and gauge accuracy.

A polished chrome-plated stainless steel bezel shall be provided to prevent corrosion and protect the lens and gauge case. The gauge shall have black graphics on a white background.

The crosslay hose bed floor will be approximately 42" above the side running board and no more than 66" above ground level.

**PUMP ENCLOSURE HOSEBED HOSE RETENTION**

A 3/16" polished aluminum tread plate cross lay cover shall be provided with a full length stainless steel hinge at the front of the cover.

Vinyl flaps shall be provided at each side of the transverse cross lay compartment secured to the tread plate cross lay cover by quarter turn fasteners, and equipped with a strap to each end.

The crosslay end flap shall be red in color.

**\*\*\*\*\* CONCENTRATE PIPING & FOAM SYSTEM \*\*\*\*\***

**FOAM PIPING - 1 INCH**

All foam concentrate plumbing from the tank or auxiliary foam inlet to the foam system components shall be stainless steel and nonferrous material.

The foam system piping shall incorporate a check valve to prevent water from entering the foam tank; the discharge piping shall also include a check valve to prevent foam solution from back feeding into the discharge side of the pump. Individual discharge piping shall be as specified for each discharge.

The complete foam system shall be tested in accordance with NFPA-1901.

**FOAMPRO FOAM INJECTION SYSTEM**

A FoamPro model 2002, electronic, fully automatic, variable speed, direct injection, discharge side foam proportioning system shall be installed in the pumping system. The system shall be capable of handling Class "A" foam concentrates and most Class "B" foam concentrates. The foam proportioning operation shall be based on direct measurement of water flows, and remain consistent within the specified flows and pressures. System must be capable of delivering accuracy to within 3% of calibrated settings over the advertised operation range when installed according to factory standards. The system shall be equipped with a digital electronic control display suitable for installation on the pump panel. Incorporated within the control display shall be a microprocessor that receives input from the system flowmeter, while also monitoring foam concentrate pump output, comparing values to ensure that the operator preset proportional amount of foam concentrate is injected into the discharge side of the fire pump.

A paddlewheel-type flowmeter shall be installed in the discharge or manifold system specified to be "foam capable".

A Full flow check valve shall be provided to prevent foam contamination of fire pump and water tank or water contamination of foam tank.

A 12 or 24-volt electric motor driven positive displacement foam concentrate pump, rated up to 5.0 GPM (18.9 L/min) with operating pressures up to 400 psi (27.6 BAR). The system shall draw a maximum of 56 amps @ 12 VDC or 30 amps @ 24 VDC. A pump motor electronic driver (mounted to the base of the pump) shall receive signals from the computer control display and power the 3/4 hp (0.56 Kw) electric motor directly coupled to the concentrate pump in a variable speed duty cycle to ensure that the correct proportion of concentrate preset by the pump operator is injected into the water stream.

The digital computer control display located on the pump operator's panel shall enable the pump operator to perform the following control and operation functions for the foam proportioning system:

- Provide push-button control of foam proportioning rates from 0.1% to 9.9%, in 0.1% increments
- Show current flow-per-minute of water
- Show total volume of water discharged during and after foam operations are completed
- Show total amount of foam concentrate consumed
- Simulate flow rates for manual operation
- Perform setup and diagnostic functions for the computer control microprocessor
- Flash a "low concentrate" warning when the foam concentrate tank(s) runs low
- Flash a "no concentrate" warning and shut the foam concentrate pump off, preventing damage to the pump, should the foam tank(s) empty

The digital computer control display shall interface with the options listed; provide dual foam calibration, and display separate totals for each foam concentrate used. If two foam tanks are required and piped to the foam concentrate pump, either an electric dual tank valve or the manual dual tank valve shall be provided.

Components of the complete proportioning system shall include:

- Operator control and display
- Paddlewheel flowmeter
- Pump and electric motor/motor driver
- Wiring harnesses
- Low-level tank switch (Switches)
- Electronic dual tank valve or manual dual tank valve (if more than one tank)
- Foam injection check valve
- Main waterway check valve

Accurate concentration proportioning can be achieved, based on the following water flows:

- |                  |                    |
|------------------|--------------------|
| • 166 GPM water  | 3.0% concentration |
| • 500 GPM water  | 1.0% concentration |
| • 1000 GPM water | 0.5% concentration |
| • 2500 GPM water | 0.2% concentration |

Note: Multiple discharges plumbed to this system may affect performance if the flow rates are exceeded by any one discharge or the totality of multiple discharges at one time!

The discharge piping shall be equipped with a properly sized flowmeter sensor, based on the systems capabilities.

The foam system shall be plumbed to the following discharge/s through the discharge piping or manifold system:

Crosslay #1 discharge.

Crosslay #2 discharge.

Crosslay #3 discharge.

Officer's side discharge #2.

The foam proportioning system shall be supplied from the foam concentrate storage tank/s. The tank/s shall be constructed of materials compatible with foam concentrates being used in the system. Tank capacity, venting, fill opening and foam outlet plumbing connections shall be in accordance with NFPA requirements. Foam tank lid shall be sealed and latched in accordance with NFPA standards. If required a provision shall be made for installation of low tank level sensors and routing of the wiring for the sensors.

**AKRON RAPID FILL - FOAM TANK REFILL SYSTEM**

The apparatus shall be equipped with an Akron Rapid Fill™ foam transfer system for refilling the on-board foam cell. The system operates by attaching a pick-up tube to a pre-plumbed panel connection using a positive seal quick connect fitting, insert the tube into the foam bucket, flip the switch to the on position and fill the tank safely from ground level.

**FOAM CONCENTRATE**

The foam system shall be capable of injecting the following foam concentrates:

- **No Class A foam selected.**
- **No Class B foam selected or Class B foam system present.**

\*\*\*\* PUMP PANEL & ACCESSORIES \*\*\*\*

**PUMP PANEL - SIDE MOUNT**

The pump operator's control panel shall be located on the driver side of the apparatus. The pump enclosure side panels shall be completely removable and designed for easy access and servicing.

**PUMP PANEL MATERIAL**

The left side operator's panel, gauge panel, right side pump panel and right side access door shall be fabricated from 12-gauge 304L stainless steel with a #4, (150/180 grit), standard brushed finish.

**HINGED GAUGE PANEL**

A full width, vertically hinged gauge access panel shall be provided at the operator's position. Chrome plated positive locks shall be provided along with chain holders to prevent the front of the gauge panel from coming in contact with other panels when open.

**VERTICALLY HINGED, SPLIT PUMP PANEL OFFICER SIDE**

The officer's side pump panel shall be split, vertically hinged, to provide complete access to the pump and plumbing on the officer side of the pump enclosure. The panels shall be equipped with stainless steel hinges and secured with push type locks to hold the panels closed. The drains located on the officer's side panel shall be fastened to the lower panel, which shall be stationary.

**PANEL FASTENERS**

Stainless steel machine screws and lock washers shall be used to hold these panels in position. The panels shall be easily removable to provide complete access to the pump for major service.

**CAPS AND ADAPTERS SAFETY TETHER**

All applicable discharge and suction caps, plugs and adapters shall be equipped with chrome plated ball chain and secured to the vehicle.

**PUMP PANEL TRIM PLATES**

A high polished trim plate shall be provided around each discharge port and suction inlet opening to allow accessibility to the respective valve for service and repairs.

**DISCHARGE GAUGE TRIM BEZELS**

Each individual discharge gauge shall be installed into a decorative chrome-plated mounting bezel that incorporates valve-identifying verbiage and color labels.

**COLOR CODED IDENTIFICATION TAGS**

Color coded identification tags shall be provided for all gauges, controls, connections, switches, inlets and outlets.

**PUMP OPERATOR'S PANEL LIGHT SHIELD AND STEP**

The pump operator's panel shall be equipped with a light shield/step that shall be full width of the control panel, and shall be positioned to cover the lights and prevent glare. The light shield shall be fabricated from aluminum tread plate, which shall also serve as a step. The step shall be a minimum of 8" deep X the width of the pump panel. (Note: On apparatus with lowered style crosslays, the light shield shall be from the back of the crosslays to the rear of the pumphouse).

The light shield shall be equipped with the following lights:

- Two (2) 20" Amdor Luma Bar H2O super bright led strip lights.

One (1) light under the operator's panel light shield shall be actuated when fire pump is engaged in addition to the pump engaged light.

**OFFICER SIDE PUMP PANEL LIGHT SHIELD AND STEP**

The officer side pump panel shall be equipped with a light shield/step that shall be full width of the panel, and shall be positioned to cover the lights and prevent glare. The light shield shall be fabricated from aluminum tread plate, which shall also serve as a step. The step shall be a minimum of 8" deep X the width of the pump panel.

The light shield shall be equipped with the following lights:

- Two (2) 20" Amdor Luma Bar H2O super bright led strip lights.

The lights shall be switched with the operator panel lights.

**PUMP OPERATOR'S PANEL**

Particular attention is to be given to functional arrangement of all controls. The pump operator's panel shall accommodate the following:

- Hinged gauge panel
- Water tank fill valve
- Auxiliary suction valve control
- All discharge valve controls
- Auxiliary engine cooler controls
- Water tank suction control valve
- Pump primer valve
- Engine throttle control
- Master compound vacuum gauge
- Master pressure gauge
- Individual discharge gauges
- Pump shift engaged indicator light
- Water tank water level indicator
- Engine tachometer
- Engine oil pressure gauge with audible alarm
- Engine water temperature gauge with audible alarm
- Low voltage light and audible alarm
- Pump panel light switch
- Speed counter (Underwriters)
- Pump performance plate (Underwriters)
- Pump serial No. plate
- Master pump drain valve
- Individual drains
- Voltmeter
- Air inlet/outlet at lower driver side panel

- Pump panel air horn actuation button labeled "EVACUATION" in white letters with a red background.
- Fire Research #TGA300 "IN CONTROL" pressure governor control.

**PUMP TEST PORTS**

The pump panel shall be equipped with Vacuum & Pressure test plugs to allow for test equipment to monitor pump pressure and vacuum levels. Chrome plugs and labels shall be provided for the test ports.

**MASTER PUMP GAUGES**

The master pump intake pressure and vacuum, and the main pump discharge pressure shall be indicated on the pressure governor display.

**PRESSURE & COMPOUND GAUGE RANGES**

All applicable pressure gauges shall have a range of 0 - 400 P.S.I., and the compound gauge shall have a range of -30" - 0 - 400 P.S.I.

**ENGINE COOLER**

An auxiliary cooler or heat exchanger shall be installed in the engine compartment between the engine and the chassis radiator. The cooler shall permit the use of water from the pump for cooling the engine. The cooling shall be done without mixing engine and pump water.

**TANK LEVEL GAUGE**

An Innovative Controls model #3030358, Ultra-Bright LED water level monitor shall be provided on the pump operator's panel. The level gauge shall contain ten (10) high intensity LED's on the display in a vertical pattern allowing the full, 3/4, 1/2, 1/4 and refill levels to be easily distinguished at a glance. The display shall use a two-dimensional, two-element lens to refract the light from the LED's to provide full 180° visibility for the level indications.

The gauge shall use a pressure transducer #3030376-01 installed near the bottom of the water tank to determine the correct volume in the tank.

**FOAM TANK LEVEL GAUGE - FOAM TANK "A"**

An Innovative Controls model #3030393-01, Ultra-Bright LED foam level monitor shall be provided on the pump operator's panel. The level gauge shall contain ten (10) high intensity LED's on the display in a vertical pattern allowing the full, 3/4, 1/2, 1/4 and refill levels to be easily distinguished at a glance. The display shall use a two-dimensional, two-element lens to refract the light from the LED's to provide full 180° visibility for the level indications.

The gauge shall use a pressure transducer installed near the bottom of the foam tank to determine the correct volume in the tank.

**WATER TANK**

The water tank shall have a capacity of 750 gallons, constructed from Poly material.

**FOAM TANK "A"**

In addition to the water capacity of the tank, a 30 gallon integral foam storage area shall be built into the water tank. The foam tank shall have a latched fill tower, properly labeled as the foam fill point. A valved drain shall be provided.

**WATER TANK CONSTRUCTION**

The Poly water tank shall be constructed of PT3 polypropylene material. This material shall be a non-corrosive stress relieved thermoplastic and UV stabilized for maximum protection. Tank shell thickness may vary depending on the application and may range from 1/2 to 1" as required. Internal baffles are generally 3/8" in thickness.

The tank shall be of a specific configuration and is so designed to be completely independent of the body and compartments. Joints and seams shall be fused using nitrogen gas as required and tested for maximum strength and integrity. The tank construction shall include PolyProSeal technology wherein a sealant shall be installed between the plastic components prior to being fusion welded. This sealing method will provide a liquid barrier offering leak protection in the event of a weld compromise. The top of the booster tank is fitted with removable lifting assembly designed to facilitate tank removal. The transverse and longitudinal swash partitions shall be manufactured of a minimum of 3/8" PT3 polypropylene. All partitions shall be equipped with vent and air holes to permit movement of air and water between compartments. The partitions shall be designed to provide maximum water flow. All swash partitions interlock with one another and are completely fused to each other as well as to the walls of the tank. All partitions and spacing shall comply with NFPA 1901. The walls shall be welded to the floor of the tank providing maximum strength as part of the tank's unique Full Floor Design. Tolerances in design allow for a maximum variation of 1/8" on all dimensions.

**WATER CAPACITY CERTIFICATION**

All tanks shall be tested and certified as to capacity on a calibrated and certified tilting scale. Each tank shall be weighed empty and full to provide precise fluid capacity. Each Poly-Tank's III is delivered with a Certificate of Capacity delineating the weight empty and full and the resultant capacity based on weight.

**WATER TANKNOLOGY TAG**

A tag shall be installed on the apparatus in a convenient location and contain pertinent information including a QR code readable by commercially available smart phones. The information contained on the tag shall include the capacity of the water and foam (s), the maximum fill and pressure rates, the serial number of the tank, the date of manufacture, the tank manufacturer, and contact information. The QR code will allow the user to connect with the tank manufacturer for additional information and assistance.

**WATER TANK ISO CERTIFICATION**

The tank must be designed and fabricated by a tank manufacturer that is ISO 9001:2000 certified in each of its locations. The ISO certification must be to the current standard in effect at the time of the design and fabrication of the tank.

**WATER TANK LID**

The tank cover shall be constructed of 1/2" thick PT3 polypropylene and UV stabilized, to incorporate a multi-piece locking design, which allows for individual removal and inspection if necessary. The tank cover(s) shall be flush or recessed 3/8" from the top of the tank and shall be fused to the tank walls and longitudinal partitions for maximum integrity. Each one of the covers shall have hold downs consisting of 2" minimum polypropylene dowels spaced a maximum of 40" apart. These dowels shall extend through the covers and will assist in keeping the covers rigid under fast filling conditions. A minimum of two lifting dowers shall accommodate the necessary lifting hardware.

**WATER TANK FILL TOWER**

The tank shall have a combination vent and manual fill tower. The fill tower shall be constructed of 1/2" PT3 polypropylene and shall be a minimum dimension of 8" x 8" outer perimeter. The fill tower shall be blue in color indicating that it is a water-only fill tower. The tower shall be located in the left front corner of the tank unless otherwise specified by the tank manufacturer to the purchaser. The tower shall have a 1/4" thick removable polypropylene screen and a PT3 polypropylene hinged cover. The capacity of the tank shall be engraved on the top of the fill tower lid. Inside the fill tower there shall be a combination vent/overflow pipe. The vent overflow shall be a minimum of schedule 40 polypropylene pipe with a minimum I.D. of that is designed to run through the tank, and shall be piped to discharge water behind the rear wheels as required in NFPA 1901 so as to not interfere with rear tire traction.

**WATER TANK OVERFLOW AND VENT PIPE**

The fill tower shall be fitted with an integral 4" I.D. schedule 40 P.V.C. combination overflow/vent pipe running from the fill tower through the tank to a 4" coupling flush mounted into the bottom of the tank to allow water to overflow behind the chassis rear axle.

**WATER TANK SUMP**

The tank sump shall be a minimum of 10" wide x 10" long x 3" deep. An anti-swirl plate shall be mounted inside the sump, approximately 1" above the bottom of the sump.

**WATER TANK SUMP CONNECTION**

The front bulkhead of the water tank shall be fitted with one (1) tank sump.

**WATER TANK 3" SUMP DRAIN**

A 3" drain plug shall be provided.

**WATER TANK FLANGES/OUTLETS - PUMPER**

There shall be two (2) standard tank outlets; one for tank-to-pump suction line which shall be a minimum of 4" coupling and one for a tank fill line which shall be a minimum of a 2" NPT coupling. All tank fill couplings shall be backed with flow deflectors to break up the stream of water entering the tank.

**WATER TANK MOUNTING ALL "T" TANKS - PUMPER**

The tank shall rest on the body cross members spaced a maximum of 22" apart, and shall be insulated from these cross members with a minimum of 3/8" nylon webbing or 1/2" rubber, 2-1/2" wide. The tank shall sit cradle-mounted using four (4) corner angles of 6 x 6 x 4 x 0.250 welded directly to the body cross members. The angles shall keep the tank from shifting left to right or front to rear. The tank is designed on the free-floating suspension principle and shall not require the use of hold downs. The tank shall be completely removable without disturbing or dismantling the apparatus body structure. The body or hose bed cross braces shall act as water tank retainers.

**APPARATUS BODY DESIGN CONSTRUCTION**

The body side and compartment assemblies shall be designed and assembled to provide maximum strength and durability under all operating conditions.

Special attention shall be taken to minimize corrosion on all fabricated parts and structural members of the body. All bolt-on components shall be provided with a dissimilar metals isolation barrier to prevent electric corrosion. The body design shall also incorporate removable panels to access spring hangers, rear body mounts and fuel tank sending units.

The body assembly shall be an all-welded configuration. The body shall be completely isolated from the cab and pump module structure.

Dimensions used in this specification shall be the general outer dimension taken from a typical line diagram of the apparatus. These dimensions shall not take into account items like material thickness, access panels, doors, and other installed options.

**COMPARTMENT TOPS**

Compartment ceilings shall be a fully welded design as part of the body construction process. Compartment designs that do not have a welded in ceiling shall not be acceptable.

**COMPARTMENT DRIP MOLDING**

Compartment doors shall have drip molding to provide protection against water runoff.

**REAR BODY PANEL**

The rear body panel shall extend the full width between the body side compartments. This panel shall be full height from the rear step to the hose bed floor. No part of the rear panel shall be attached to the booster tank. The rear body panel material shall be aluminum treadplate as standard. If Chevron striping is specified for the rear of the body then smooth aluminum shall be utilized.

**BODY AND COMPARTMENT FABRICATION - 3/16" ALUMINUM**

All compartment panels and body side sheets shall be fabricated entirely of 3/16" aluminum (5052-H32). Each side compartment assembly shall be both plug welded and stitch welded to ensure proper weld penetration on all panels while avoiding the possible warping caused by a full seam weld. The side compartments shall be welded on a fixture to ensure true body dimensions of all door openings. The side compartments and body side panels are then set into a body squaring fixture where the super structure is installed and the entire body is aligned to be completely symmetrical. The super structure is then welded to the compartment side panels and reinforcement plates are inserted which allows the compartment panels to become an integral component of the body support structure. A full seam weld shall not be used due to the applied heat which shall distort sheet metal and remove the protective coating from the perimeter of the welded area. All seams shall be caulked prior to finish paint to ensure proper compartment seal.

**SUB STRUCTURE - ALUMINUM**

The body sub structure shall be an all welded configuration utilizing a combination of 3" x 1-1/2" 6061-T6 thick walled structural tubing and 6061 structural channel.

This structure shall be designed to totally support the full length and width of the body and shall be welded to the body side compartments by use of reinforcement plates to incorporate the compartments into an integral part of the body weldment.

The sub structure shall be bolted to the sides of the chassis frame at four (4) points. The two (2) forward mounting points shall utilize a spring mount to help isolate the body from chassis deflection.

This design shall provide storage capacity in each side compartment for a minimum of 500 lbs of equipment, and a minimum of 1000 lbs of equipment in the rear step compartment.

**FIRE BODY WIDTH**

The fire body shall be 100" wide to provide the maximum amount of usable hose bed and compartment space. The side body compartments shall be 29" deep in any full depth areas, and 14" deep in any split depth areas.

**BODY FENDER**

The body fender shall be 64" long, this shall allow for the suspension and related components to be contained within the fender, preventing any intrusion into the body compartment storage area. Bodies with notches in the front and/or rear compartment for suspension components are not acceptable.

**DRIVER SIDE - FRONT SECTION OF FENDER**

A storage compartment shall be inserted into the fender to provide a storage area for three (3) customer supplied SCBA cylinders (or fire extinguishers of similar size). The storage area shall be sized as tall and wide as possible in the fender (minimum of 14" wide x 15" tall with an angled floor by fender radius), and shall be 26" deep. The compartment shall have a non-abrasive lined cradle storage area for each of the three (3) devices.

This storage compartment shall provide a minimum of 2.3 cubic feet of storage space.

**DRIVER SIDE - REAR SECTION OF FENDER**

A storage compartment shall be inserted into the fender to provide a storage area for two (2) customer supplied SCBA cylinders (or fire extinguishers of similar size). The storage area shall be sized as tall and wide as possible in the fender (minimum of 15" wide x 7-3/4" tall), and shall be 26" deep. The compartment shall have a non-abrasive lined cradle storage area for each of the devices.

This storage compartment shall provide a minimum of 1.6 cubic feet of storage space.

**OFFICER SIDE - FRONT SECTION OF FENDER**

A slide out absorbent bin shall be installed in this fender position. The storage bin shall be constructed of smooth aluminum and shall be sized to store a minimum of 40 lbs of absorbent material. The bin shall be installed on sliding locking tracks that allow the bin to extend out of the body fender for dumping/filling. There shall be a hinged lid on top of the storage bin to add material to the bin, and a spring loaded valve at the bottom to dispense material out of the bin.

**Header Title**

Bidder Complies	
YES	NO

Absorbent bins that are built into the fender and do not provide a means for sliding the bin out for loading and dispensing shall not be acceptable due to the difficulty in loading/unloading.

**OFFICER SIDE - REAR SECTION OF FENDER**

A storage compartment shall be inserted into the fender to provide a storage area for three (3) customer supplied SCBA cylinders (or fire extinguishers of similar size). The storage area shall be sized as tall and wide as possible in the fender (minimum of 14" wide x 15" tall with an angled floor by fender radius), and shall be 26" deep. The compartment shall have a non-abrasive lined cradle storage area for each of the three (3) devices.

This storage compartment shall provide a minimum of 2.3 cubic feet of storage space.

**FENDER STORAGE DOORS**

The fender storage area(s) shall be enclosed by a hinged door fabricated from mirror finish stainless steel. The back side of the door shall have a section of nylatron installed to protect the door surface from the items stored in the compartment. Each door shall be tied into the compartment door ajar/do not move apparatus warning system.

**DRIVER SIDE BODY COMPARTMENTATION**

One full height/full depth compartment shall be provided forward of the rear wheels. The compartment dimensions shall be 35" wide x 68" tall x 29" deep.

One high side compartment shall be provided above the rear wheels. The compartment dimensions shall be 64" wide x 37" high x 29" deep.

One full height/full depth compartment shall be provided behind the rear wheels. The compartment dimensions shall be 56" wide x 68" tall x 29" deep.

The driver side compartments shall provide approximately 144 cubic feet of storage space.

**OFFICER SIDE BODY COMPARTMENTATION**

One full height/split depth compartment shall be provided forward of the rear wheels. The compartment dimensions shall be 35" wide x 68" tall x 29" deep in the lower 30" tall area, and 14" deep in the upper 38" tall area.

One high side compartment shall be provided above the rear wheels. The compartment dimensions shall be 64" wide x 37" high x 14" deep.

One full height/split depth compartment shall be provided behind the rear wheels. The compartment dimensions shall be 56" wide x 68" tall x 29" deep in the lower 30" tall area, and 14" deep in the upper 38" tall area.

The officer side compartments shall provide approximately 95 cubic feet of storage space.

**REAR STEP COMPARTMENT**

An equipment storage compartment shall be provided on the rear of the body at the rear step area. The rear step compartment shall be 42" Wide x 40" High x 29" Deep.

The rear step compartment shall provide approximately 28 cubic feet of storage space.

The rear step compartment shall have full side panels which shall isolate this storage area from the side body compartments.

The rear step compartment shall be equipped with a rollup style door.

**RECESSED REAR STEP**

The rear step shall be a total of 16" deep, with 12" recessed and 4" extended.

The recessed area of the step shall be 12" deep, recessed between the rear portion of the rear side compartments. The step shall be 42" wide in the recessed area, and 100" wide in the extended area. The step shall be fabricated from 3/16" polished aluminum treadplate, and shall be rigidly reinforced.

The recessed design of the rear step shall not affect the compartment depth.

The rear edge of the step shall be designed to accommodate the rear clearance lights, recessed for protection in the step reinforcement channel. The step shall be bolted into place with a minimum 1/2" clearance gap between the step and rear body panel.

**BEAVERTAILS**

The rear body beavertail area shall be furnished with a squared off appearance to maximize the available compartment area, while providing added support to the rear step support structure. The beavertail panels shall be assembled in conjunction with the rear body corner panels. This assembly shall provide a vertical mounting surface for tail lights at the rear most portion of the body and additional storage space.

The inside of the beavertails shall be furnished with polished aluminum tread plate overlays.

**HOSE BED (94" WIDE)**

The hose bed shall be located directly above the booster tank and shall be free from all sharp objects such as bolts, nuts, etc., to avoid damage to fire hose.

For added strength, the hose bed side walls shall be approximately 3" thick, this shall provide a mounting surface for devices like warning lights and scene lights. The inner hosebed side walls shall be brushed aluminum panels, which shall prevent damage to painted surfaces when deploying hose. The front wall shall be flanged inward 2" with a 1" downward return to provide additional rigidity to the front wall.

**HOSE BED CAPACITY**

The hose bed shall be designed with enough storage capacity to carry the following customer specified hoseload:

- 1,300 Feet of 5" supply hose
- 1,000 Feet of 3" supply hose
- 250 Feet of 2-1/2" attack hose
- 250 Feet of 2-1/2" attack hose

**HOSE BED FLOORING**

Flooring to be constructed from extruded aluminum and be properly spaced for ventilation. The flooring shall be smooth and free from sharp edges to avoid hose damage. The hose bed floor shall be removable to provide access to inner body framework.

**HOSE BED PARTITION**

Three (3) fully adjustable 1/4", aluminum hose bed partition shall be provided. Partition shall be easily adjustable by means of channels located at the front and rear of the hose bed. Partition shall be removable for access to the booster tank.

**VINYL HOSE BED COVER - 1/4 TURN FASTENERS**

A hose bed cover shall be provided and installed. The cover shall be made from 22 ounce; heavy-duty vinyl coated polyester fabric (TXN 226). The cover shall be sewn with ultraviolet resistant thread and shall have 2" wide nylon webbing sewn around the perimeter to provide additional strength.

The cover shall be secured to the top front body flange with quarter-turn fasteners. The cover shall be secured to the side body flanges with quarter-turn fasteners. A weighted flap shall be furnished on the rear of the cover with two (2) bungee cords.

The Hypalon material shall be red in color.

**ROLL-UP DOORS**

Roll-up doors shall be provided on all compartments. The roll-up doors shall be constructed from aluminum extruded slats which shall have a flexible seal between each slat for proper sealing of the door.

A synthetic rubber seal shall be provided at each side, top and bottom edge of the door to prevent entry of dirt into the compartment.

The door shall be equipped with a lift bar style latch mechanism which shall latch at the bottom of the door mounting extrusion.

The roll-up door assembly shall be furnished with a spring-loaded, counter balance assembly to assist in door actuation.

All running board and high side compartments shall be equipped with roll-up doors.

**AMDOR ROLL-UP DOORS**

The roll-up doors shall be Amdor brand roll-up doors, equipped with a satin finish, with a dual durometer slat seal. The slats shall be made from 1" double-wall aluminum with a continuous ball and socket hinge joint. The interior of the door shall use a smooth interior door curtain to prevent equipment hang-ups. The bottom panel flange shall have a stainless steel lift bar latching system with cut-outs for ease of access with gloved hands.

**SWEEP-OUT COMPARTMENT FLOORS**

Compartment floors shall be welded to the compartment walls and have a sweep out design for easy cleaning.

Compartments with hinged doors shall have the door opening flanges bend down to produce the sweep-out design.

Compartments with roll-up style doors shall have the external floor flange stepped down, 1/2" high x 2" deep, to produce a sealing surface for the roll-up doors below the compartment floor. The sweep out design shall also permit easy cleaning.

**COATED FASTENERS**

All exterior fasteners shall be coated stainless steel screws. Screw threads shall be coated with reusable, self-locking, sealing material to provide vibration resistance. Screw heads shall be coated with a sealing element to prevent galvanic corrosion between dissimilar metals. Non-coated screws shall only be provided as part of vendor supplied component installations.

**COMPARTMENT LOUVERS**

Ventilation between compartments to atmosphere shall be provided and located to avoid water entry into compartments.

**ACCESS PANELS**

Removable access panels shall be provided (if applicable) to access fuel tank sender, electrical junction compartment and rear body mounts.

Protective panels shall be located in the rear compartments providing access to the lights and associated wiring. The covers shall also serve as protective covers to prevent inadvertent damage to lights or wiring from tools or equipment located in the compartment.

**BODY PROTECTION PANELS**

The front face of the side compartments, next to the driver and officer pump panels shall be overlaid with full height aluminum tread plate protection panels. The overlays shall cover the front face of the compartments only, they shall not wrap around to the door opening.

**BODY RUB RAILS**

Sacrificial aluminum tread plate rub rails shall be mounted at the base of the body, extend outward a minimum 3/4", downward 2" and flange inward 1". The rub rails shall extend the full length of the main body and extend to the rear step or wrap around the rear body corners. Rub rails shall be designed to bolt to the body from the bottom side of the compartment area, so as not to damage the body side panels on initial impact and to provide for ease of replacement.

**RUNNING BOARD STEPS**

The driver and officer running board steps shall be fabricated of 3/16" polished aluminum tread plate. The outside edge on each step shall be fabricated with a double break, return flange. The steps shall be rigidly reinforced with a heavy duty support structure. The running boards shall not form any part of the compartment design, and shall be bolted into place with a minimum 1/2" clearance gap between any panel to facilitate water runoff.

**OFFICER SIDE RUNNING BOARD STORAGE WELL - FLOATING**

A floating storage well, constructed of 1/8" aluminum, shall be recessed into the officer's side running board. The storage well shall measure 9" deep x 9" wide x as long as possible between the running board support members. Drain holes shall be located in the bottom corners to allow water to drain from the storage well. The front and rear bottom corners of the well shall have an angled face to help the well slide up if it strikes an object. The entire well shall be a "floating" style that can easily shift up if an object is struck.

The officer's side running board hose well shall be furnished with Velcro straps to secure the hose stored in the well. The straps shall be attached to each side of the hose well with stainless steel footman loops.

**DRIVER SIDE RUNNING BOARD STORAGE WELL - FLOATING**

A floating storage well, constructed of 1/8" aluminum, shall be recessed into the driver's side running board. The storage well shall measure 9" deep x 9" wide x as long as possible between the running board support members. Drain holes shall be located in the bottom corners to allow water to drain from the storage well. The front and rear bottom corners of the well shall have an angled face to help the well slide up if it strikes an object. The entire well shall be a "floating" style that can easily shift up if an object is struck.

The driver's side running board hose well shall be furnished with Velcro straps to secure the hose stored in the well. The straps shall be attached to each side of the hose well with stainless steel footman loops.

**GRAB RAILS**

All hand rails shall be 1-1/4" outer diameter, knurled bright anodized aluminum extrusion, designed to meet NFPA 1901 requirements.

Molded gaskets shall be installed between the handrail stanchion castings and body surfaces to prevent electrolytic reaction between dissimilar metals and to protect paint.

**GRAB RAIL LOCATIONS:**

Grab rails shall be provided at the following specified locations. Additional grab rails shall be provided adjacent to any additional steps specified to comply with NFPA 1901.

Two (2) vertical rails shall be mounted on the rear edge of the body, one (1) each side.

One (1) horizontal, full width handrail shall be installed on the rear, below the level of the hose bed.

Two (2) vertical handrails shall be mounted above each pump panel, (1) each side.

**FOLDING STEP(S) - BODY FRONT DRIVER SIDE**

Cast Products model SP4401-1-CH-A-BL LED lighted large folding step(s) with RG0005 gasket, with a textured chrome plate finish shall be provided on driver side body front to provide NFPA compliant access (maximum 18" height between steps) to an upper horizontal walking surface (compartment cap, dunnage area, fabricated step, or upper body compartments).

Each step shall have an LED light at the top and bottom of each step to illuminate the stepping areas.

**FOLDING STEP(S) - BODY FRONT OFFICER SIDE**

Cast Products model SP4401-1-CH-A-BL LED lighted large folding step(s) with RG0005 gasket, with a textured chrome plate finish shall be provided on officer side body front to provide NFPA compliant access (maximum 18" height between steps) to an upper horizontal walking surface (compartment cap, dunnage area, fabricated step, or upper body compartments).

Each step shall have an LED light at the top and bottom of each step to illuminate the stepping areas.

**FOLDING STEP(S) - BODY REAR DRIVER SIDE**

Cast Products model SP4401-1-CH-A-BL LED lighted large folding step(s) with RG0005 gasket, with a textured chrome plate finish shall be provided on driver side body rear to provide NFPA compliant access (maximum 18" height between steps) to an upper horizontal walking surface (compartment cap, dunnage area, fabricated step, or upper body compartments).

Each step shall have an LED light at the top and bottom of each step to illuminate the stepping areas.

**FOLDING STEP(S) - BODY REAR OFFICER SIDE**

Cast Products model SP4401-1-CH-A-BL LED lighted large folding step(s) with RG0005 gasket, with a textured chrome plate finish shall be provided on officer side body rear to provide NFPA compliant access (maximum 18" height between steps) to an upper horizontal walking surface (compartment cap, dunnage area, fabricated step, or upper body compartments).

Each step shall have an LED light at the top and bottom of each step to illuminate the stepping areas.

**SAFETY SIGN(S) AT REAR STEP AND CROSS WALKWAY(S)**

Safety sign(s) shall be located on the vehicle at the rear step, and at any cross walkway(s), to warn personnel that riding in or on these areas while the vehicle is in motion is prohibited.

**REAR WHEEL WELL LINERS**

Fully removable, one piece, bolt-in, aluminum rear wheel well liner and fenderette will be provided. The wheel well liners will be natural metal finish and will protect the front and rear compartments and main body supports from damage. Wheel well liners and fenderettes which are welded in place or are only partially removable shall not be considered.

**REAR MUD FLAPS**

Heavy duty mud flaps shall be provided behind the rear wheels.

**REAR TOW EYES**

Two (2) painted tow eyes shall be furnished on the rear of the vehicle. The tow eyes shall be made from plate steel and shall be bolted directly to the chassis frame rails with grade 8 bolts and shall extend below the body. The tow eyes shall be smooth and free from sharp edges, and have a minimum eyelet hole of 2-1/2". The tow eyes shall be painted.

\*\*\*\* COMPARTMENT ACCESSORIES \*\*\*\*

**ADJUSTABLE SHELVING**

Compartment shelving shall be constructed of 3/16" brush finish aluminum with a 2" upward bend at front and rear, and side supports. Shelving shall be vertically adjustable with spring nuts in aluminum strut channel.

Adjustable shelves shall be located as follows:

Six (6) adjustable shelf(s) shall be provided and mounted as directed by the fire department.

**ADJUSTABLE ROLL-OUT TRAYS**

Roll out adjustable compartment shelving shall be constructed of 3/16" brush finish aluminum with a 2" upward bend at front and rear, and side supports attached to 250# rated slides. Slide out adjustable shelving shall be vertically adjustable with spring nuts in aluminum strut channel. Slide out adjustable shelving shall have gas springs to hold in and out.

The adjustable roll-out trays shall be located as follows:

One (1) in the driver side front compartment

One (1) in the officer side front compartment

Two (2) in the driver side rear compartment

One (1) in the officer side rear compartment

One (1) in the rear step compartment

**VERTICAL DIVIDERS**

Full height, fixed mounted, vertical compartment dividers shall be fabricated from 3/16" brushed aluminum material. The dividers shall extend the full depth of the specified compartment from the floor to the compartment ceiling.

Full height, vertical dividers shall be located as follows:

One (1) full height fixed divider(s) shall be located as directed by the fire department

**SWING OUT TOOL BOARDS**

The tool boards shall be constructed of PAC TRAC Dual Faced 7040 series aluminum extrusion allowing mounting of equipment on the interior and exterior of the tool boards. The tool boards shall be installed with a Performance Advantage Company PM-1000 Swing-Out Module Kit. Aluminum angles shall attach the hinge to Unistrut tracking to allow depth adjustments. A heavy duty thumb latch shall be provided to secure the tool boards in the closed position.

Swing out tool boards shall be located as follows:

One (1) in the driver side over the wheel high side compartment

**VERTICAL PULL OUT TOOL BOARDS**

Vertical, pull out tool boards shall be provided. Each tool board shall be constructed of vertically mounted dual sided PAC-TRAC 7040 series allowing mounting of equipment on both sides of the tool board. Each tool board shall be attached to 250# roller bearing slides at the top and bottom of the tool board. 3/16" aluminum angles shall be located at the top of the tool board to guide the tool board. A gas shock shall be used to secure each tool board in the stored and deployed position. Each tool board will be attached to tracking to allow horizontal adjustment of the tool board.

Vertical pull out tool boards shall be located as follows:

One (1) in the driver side rear compartment

\*\*\*\*120/240 VOLT A.C. ELECTRICAL AND GENERATOR SECTION \*\*\*\*

**120/240 VOLT ELECTRICAL SYSTEM TESTING**

All line voltage wiring and permanently connected devices and equipment shall be subjected to a dielectric voltage withstand test of 900 volts for one minute. The test shall be conducted between live parts and the neutral conductor and between live parts and the vehicle frame with any switches in the circuits closed. The test shall be conducted after all bodywork has been completed. The dielectric tester shall have a minimum 500 VA transformer with a sinusoidal output voltage that can be verified.

Electrical polarity verification shall be made of all permanently wired equipment and receptacles to determine that connections have been properly made.

**OPERATIONAL TESTING**

The apparatus manufacturer shall perform the following operation test and shall certify that the power source and any devices that are attached to the line voltage electrical system are properly connected and in working order.

The generator shall be started from a cold start condition and the line voltage electrical system shall be loaded to 100 percent of the nameplate voltage rating.

The following items shall be monitored and documented every 15 minutes:

- The cranking time until the generator starts and runs.
- The voltage, frequency, and amperes at continuous full rated load.
- The generator oil pressure, water temperature, transmission temperature, hydraulic temperature, and the battery rate charge, as applicable.
- The ambient temperature and altitude.

The generator shall operate at 100 percent of its nameplate wattage for a minimum of two (2) hours.

**HYDRAULIC GENERATOR**

Smart Power 10 kW Heavy Rescue Series Hydraulic Generator

A Smart Power, model HR-10, 10000 watt hydraulic generator shall be provided.

The generator system shall come with a standard 5 year/1,000 hour fully transferable warranty from the manufacturer.

The unit shall come equipped with: generator tray assembly (which includes the generator, hydraulic motor, cooler, fan, electronics package, 10 micron spin-on fluid filter and reservoir), axial piston hydraulic pump with pressure compensated control, and Command and Control Center (CCC) display with all required wiring harnesses. The CCC shall be an interactive operator control center, equipped with smart touch solid state buttons, with displays for voltage, frequency, amperage, hour meter, service reminders, operator warnings, system faults and diagnostics. Standard electronics package shall include smart start engagement to reduce mechanical stress, precise voltage and frequency control, cold start system, automatic load and temperature compensation, integrated diagnostics system, and other automated control features to protect system, vehicle and operator.

The generator tray assembly shall be delivered with the cooler/fan assembly mounted such that the hot air is exhausted straight up, through an NFPA approved walking grate.

The body of the generator tray assembly (including reservoir) shall be 32" long x 13.5" wide x 17" high, weighing approximately 220 pounds. The hydraulic pump shall be driven by a chassis transmission mounted power take off (PTO).

The wiring from the generator to the breaker box shall be type SO with suffix WA flexible cable.

**Ratings and Capacity\***

- Rating: 12000 watts peak - 10000 watts continuous
- Volts: 120/240 volts
- Phase: Single, 4 wire
- Frequency: 60 Hz
- Amperage: 83 amps @ 120 volts or 42 amps @ 240 volts
- Engine speed at engagement: Standard soft start feature allows for any speed engagement
- Operation range: 850 to 3240 RPM

**Testing**

The generator shall be tested in accordance with all current NFPA 1901 standards.

**Notes**

\*All ratings and capacities shall be derived utilizing current NFPA 1901 test parameters.

**GENERATOR PTO**

A hot shift PTO shall be provided on the transmission for the Smart Power generator. The PTO shall be controlled from the cab. The control shall include a PTO engagement switch and a PTO engaged indicator light.

**GENERATOR WARRANTY**

The specified generator shall have a five (5) year or one thousand (1000) hour warranty as provided by the generator manufacturer. A copy of the generator warranty shall be provided at time of delivery.

**LINE VOLTAGE ELECTRICAL SYSTEM CERTIFICATION**

When the unit successfully meets all the requirements outlined in NFPA 1901, 2016 Edition, UL shall issue a Certificate of Automotive Fire Apparatus Examination and Test stating the unit's compliance with the required line voltage section of NFPA.

**GENERATOR LOCATION**

The generator shall be mounted above the pump enclosure on the officer side.

Locating the generator greater than 144" from the main breaker panel may require the installation of an additional power disconnecting means.

**120/240 VOLT LOAD CENTER**

The generator output line conductors shall be wired from the generator output connections to a Square D, model #QO112L125G breaker panel. The breaker panel shall be equipped with a properly sized main breaker using two (2) of the twelve (12) spaces which leaves a total of ten (10) available spaces.

The generator output conductors shall be sized to 115% of the main breaker rating and shall be installed as indicated in the wiring section.

Six (6) appropriately sized, 120 volt, circuit breakers shall be provided.

Two (2) appropriately sized, 240 volt, circuit breakers shall be installed in place of four (4) standard 110 volt circuit breakers.

The breaker panel shall be located on the rear wall of the driver side front compartment.

**120/240 VOLT WIRING METHODS**

Wiring/conduit shall not be attached to any chassis suspension components, water or fuel lines, air or air brake lines, fire pump piping, hydraulic lines, exhaust system components or low voltage wiring.

All wiring shall be installed at a minimum of 12 inches away from any exhaust piping and a minimum of 6 inches from any fuel lines.

All wiring shall be securely clamped within 6 inches of any junction box and at a minimum of every 24 inches of run. All supports shall be of nonmetallic material or corrosion protected metal. All supports shall not cut or abrade conduit or cable and shall be mechanically fastened to the vehicle.

All power supply assembly conductors, including neutral and grounding conductors, shall have an equivalent amperage rating and shall be sized to carry not less than 115% of the main breaker rating.

All Type SO or Type SEO cable not installed in a compartment shall be installed in wire loom. Where Type SO or Type SEO cable penetrates a metal surface, a rubber or plastic grommet or bushing shall be provided.

The installation of all 120/240 wiring shall meet the current NFPA-1901 Standards .

**120/240 VOLT WIRING IDENTIFICATION**

All line voltage conductors located inside the main breaker panel box shall be individually and permanently identified. When pre-wiring for future power wiring installations, the non-terminated ends shall be labeled showing function and wire size.

**120/240 VOLT GROUNDING**

The neutral conductor of the power source shall be bonded to the vehicle frame only at the power source.

The grounded current carrying conductor (neutral) shall be insulated from the equipment grounding conductors and from the equipment enclosures and other grounded parts. The neutral conductor shall be colored white or gray.

In addition to the bonding required for the lower voltage return current, each body and driving/crew compartment enclosure shall be bonded to the vehicle frame by a copper conductor. The conductor shall have a minimum amperage rating of 115 percent of the name plate current rating of the power source specification label.

**120/240 VOLT CIRCUIT BREAKER / RECEPTACLE INSTALLATION**

The system shall be installed by highly qualified electrical technicians to assure the required level of safety and protection to the fire apparatus operators. When multiple circuit are required, the circuits shall be wired to the breaker panel in a staggered configuration to minimize electrical loads on each breaker or generator (leg) circuit. The wiring, electrical fixtures and components shall be to the highest industry quality standards available on the domestic market. The equipment shall be the type as designed for mobile type installations subject to vibration, moisture and severe continuous usage.

**120/240 VOLT RECEPTACLE INSTALLATIONS**

Any receptacle installed in a wet location must be a minimum of 24 inches above the ground and provided with an approved wet location cover. Wet receptacles may not be

**Header Title**

Bidder Complies	
YES	NO

mounted at more than 45 degrees from vertical, nor can they be mounted in a face-up position.

One (1) 120 volt, NEMA L5-15, 15 amp, duplex twist-lock receptacle with a grey thermoplastic, corrosion resistant, weatherproof cover shall be installed adjacent to the circuit breaker panel.

This receptacle shall require one (1) 15 amp, 120 volt circuit breaker to be installed in the load center.

**ELECTRIC CORD REELS (220 VOLT)**

Two (2) Hannay Model #ECR-1618-17-18, with 4 conductor collector assembly for 240 volts, with electric rewind cord reels shall be provided and wired to the breaker panel. The reels shall be securely mounted and equipped with a rewind control adjacent to each reel.

The cord reels shall be mounted in the hosebed with one (1) on the driver side and one (1) on the officer side.

The circuit breaker used to protect any device attached to the cord reel shall be sized to the smallest electrical connection used.

One (1) reel rewind switch(s) shall be provided on the compartment wall

One (1) Hannay 4-way stainless steel roller assembly shall be provided. The roller assembly opening shall be the full width of the reel drum.

One (1) cable ball stop(s) shall be installed on the cable to keep the end from passing through the roller assembly.

**ELECTRIC CABLE**

Two hundred (200) feet of Type SO yellow 10/4 heavy duty electric cable, wired for 240 volt, shall be provided on each of the cord reels.

One (1) NEMA L14-20R, 20 amp, four prong twist-lock receptacle shall be provided on the end of the cable.

**JUNCTION BOX(ES)**

Two (2) Akron Model EJB-GFCI, four (4) outlet junction box(es) with one (1) NEMA 5-20R GFCI rated straight blade receptacle and three (3) NEMA L5-20R twist-lock receptacles with 12" pigtail with a NEMA L14-20P twist-lock plug with wire strain relief and rubber feet shall be provided.

The junction box(es) shall be wired such that the four (4) outlets provide 120 VAC.

Two (2) holder(s) constructed from 1/8" aluminum tread plate shall be provided for each cord reel(s) junction box. The location of the holder shall be adjacent to the cord reel roller assembly or as directed by the fire department.

**LIGHTING (TRI-POD) - AS DIRECTED**

Two (2) Fire Research Spectra, model #SPA600, pull up tripod lighting stand, shall be provided and installed on the exterior body as directed by the Fire Department. The lighting stand shall be UL listed for fire service use. The tripod stand shall rise to a total height of 12 feet and shall be locked in place by a "twist lock" (concentric ring) tightening mechanism. The use of a knob or latch to release the pole in order to raise and lower the telescoping portion of the pole shall not be accepted. The stand shall incorporate an "air braking" mechanism that allows the floodlight to lower slowly on a cushion of air. The floodlight shall be covered by a metal grate in accordance with UL requirements.

The lights shall be mounted on the body as directed by the fire department, one (1) each side. Wiring used for the lighting shall be a minimum of 16 gauge three (3) wire cable that is properly supported and protected from damage.

Each Fire Research light shall be equipped with sixty (60) ultra-bright white LEDs, 48 for flood lighting and 12 to provide a spot light beam pattern. It shall operate at 120 volts AC, draw 2 amps, and generate 20,000 lumens of light. The lamphead shall have a unique lens that directs flood lighting onto the work area and focuses the spot light beam into the distance. The lamphead angle of elevation shall be adjustable at a pivot in the mounting arm and the position locked with a round knurled locking knob. The lamphead shall be no more than 5 7/8" high by 14" wide by 3 1/2" deep and have a heat resistant handle. The lamphead and mounting arm shall be powder coated. The LED scene light shall be for fire service use.

The tripod lights shall be equipped with a pig tail cord equipped with an L5-15 120V plug and a weatherproof "on-off" switch on the light head.

One (1) 120V, L5-15 amp receptacle shall be provided and installed near the mounting position of each tripod light for a total of two (2) receptacles. Both receptacles shall require one (1) 20 amp, 120V circuit breaker to be installed in the load center.

The tri-pod lights shall be controlled from the following location(s):

- Cab dash, with 12 volt switch
- Pump panel, with 12 volt switch
- At breaker panel, with breaker

**WILL-BURT VERTICAL LIGHT TOWER**

A Will-Burt, model 5.4-17, VRT-920 SPC, vertical mast light tower shall be provided and mounted as specified.

The light tower shall be equipped with four (4) 230-watt, 120-volt Spectra LED spot/flood light fixtures to provide a total of 920 watts and 80,000 lumens of lighting. The light tower uses an RCP (Remote Control Positioner) attached to the end of the mast to allow full rotation and independent tilt (Dual Tilt) of the right and left light banks at any vertical height to ensure total scene coverage in two separate directions. The light tower extends to a maximum height of seventeen feet (17') from the mounting base and auto stows to a maximum height of 76.5" from the mounted surface. A 12 volt vertical look-up light shall be provided on the light tower to automatically illuminate the operational envelope of the mast.

The four (4) 230-watt light heads shall require one (1) 120-volt, two pole 15-amp circuit breaker.

The light towers functions including "auto stow," are operated by a pistol grip remote control. The light tower control shall be mounted in the proximity of the electrical breaker panel.

**Header Title**

Bidder Complies

YES

NO

An emergency stop button shall be integrated into the wired hand held control for added safety.

The light tower shall be mounted in the dunnage area.

**LADDER STORAGE**

The ground ladders shall be stored vertically next to the water tank, behind the side body compartments, on the officer side of the apparatus.

To secure the ground ladders, a hinged rear access door shall be provided and tied into the "Do Not Move Apparatus" warning system.

**GROUND LADDERS**

The following Alco-Lite ground ladder complement shall be provided:

- One (1) Alco-Lite model PEL-24; 24', aluminum, two (2) section extension ladder shall be provided.
- One (1) Alco-Lite model PRL-14; 14', aluminum, straight roof ladder with folding hooks shall be provided.
- One (1) Alco-Lite model FL-10; 10', folding, aluminum, attic ladder shall be provided.

\*\*\*\* PIKE POLES AND HOLDERS \*\*\*\*

**PIKE POLE STORAGE**

Four (4) pike pole tube(s) shall be provided. Each holder shall be accessible from the rear of the apparatus. Each pike pole holder shall be labeled to indicate the pike pole length.

The pike pole tube(s) shall be mounted in the ladder storage compartment.

- One (1) 6' Fire Hooks Unlimited fiberglass handled pike pole(s) shall be provided.
- One (1) 8' Fire Hooks Unlimited fiberglass handled pike pole(s) shall be provided.
- One (1) 10' Fire Hooks Unlimited fiberglass handled pike pole(s) shall be provided.
- One (1) 12' Fire Hooks Unlimited fiberglass handled pike pole(s) shall be provided.

**SUCTION HOSE STORAGE**

The suction hoses shall be located beneath the hose bed, one (1) on the driver side and one (1) on the officer side. The hose storage area shall be accessed from the rear of the apparatus. The storage area shall be enclosed with a hinged door on the rear of the body that shall be tied into the "Do Not Move Apparatus" warning system.

Note: On bodies with rollup style doors this storage area shall be behind the roll of the door and will not affect usable compartment space. On bodies with hinged style doors this storage area shall be in the top corner of the compartment.

**SUCTION HOSE**

Two (2) 10' sections of six (6) inch Kocheck (PVC) suction hose with lightweight hard coat couplings shall be furnished. Couplings shall include a long handle, female swivel on one end and a rocker lug male on the other end. All threads shall be six (6) inch N.S.T.

NOTE: All PVC suction hoses are strictly drafting hoses and must not be used on hydrants or in pressure applications, as serious personal injury or death may occur.

**STRAINER**

One (1) 6" NST, Red Head 140-60001 barrel type strainer(s) shall be provided to attach to the suction hose. A compartment mounting bracket shall also be provided to store the strainer(s) when not in use.

**HYDRANT ADAPTER**

A double female swivel hydrant adapter shall be provided along with a screw base mounting bracket. One end shall attach to the suction hose and the other end to be 4-1/2" N.S.T. thread.

**ADDITIONAL ITEMS SUPPLIED WITH THE VEHICLE**

- 1 - Pint of touch up paint for each color
- 1 -Bag of assorted stainless steel nuts and bolts

**LOOSE EQUIPMENT**

The following items shall be provided and shipped loose with the completed apparatus at the time of delivery:

**WHEEL CHOCKS**

**Header Title**

**Bidder Complies**

YES NO

Two (2) ZICO #SAC-44 folding wheel chocks shall be mounted forward of the rear wheels on the driver side below the side running board compartments.

\*\*\*\* PAINT SECTION \*\*\*\*

**PAINT, PREPARATION AND FINISH**

The PPG Delta, Low V.O.C., polyurethane finishing system, or equal, shall be utilized. A "Clear Coat" paint finish shall be supplied to provide greater protection to the quality of the exterior paint finish.

All removable items, such as brackets, compartment doors, etc. shall be painted separately to insure finish paint behind mounted items. All compartment unwelded seams exposed to high moisture environments shall be sealed using permanent pliable caulking prior to finish paint.

**BODY PRIMER & PREPARATION**

All exposed welds shall be ground smooth for final finishing of areas to be painted. The compartments and doors are totally degreased and phosphatized. After final body work is completed, grinding (36 and 80 grit), and finish sanding shall be used in preparation for priming.

**BODY FINISH PAINT**

The body shall be finish sanded and prepared for final paint. Upon completion of final preparation, the body shall be painted utilizing the highest quality, state of the art, low V.O.C., polyurethane base paint. Finish paint shall be applied in multiple coats to ensure proper paint coverage with a high gloss finish.

The entire body shall be buffed and detailed.

**BODY PAINT**

The inside and underside areas of the complete body assembly shall be painted black using a PPG Delta System, prior to the installation of the body on the chassis or torque box.

**COMPARTMENT PAINT**

The interior of the body compartments shall be painted with Line-X material.

The Line-X coating shall be light gray in color.

**BODY PAINT**

The body paint finish shall be PPG Delta System in a single color, to match customer furnished paint codes and requirements.

**PUMP / PIPING PAINT**

The pump enclosure and pump/plumbing within the pump enclosure shall be painted black.

**FENDER STORAGE COMPARTMENT PAINT**

The interior of the fender storage compartments (if fender compartments are specified) shall be finish painted with Light Gray Line-X paint to provide a protective finish.

**CAB PRIMER & PREPARATION**

The cab primer shall be a two (2) stage process. First stage shall be a coating with a two part component, self etching, corrosion resistant primer to chemically bond the surface of the metal for increased adhesion. Second stage shall be multiple coats of a catalyzed, two component polyurethane, primer applied for leveling of small imperfections and top coat sealing.

**CAB FINISH PAINT**

The entire cab shall be finish sanded and prepared for final paint. Upon completion of final preparation, the cab shall be painted utilizing the highest quality, state of the art, low V.O.C., polyurethane base paint. Finish paint shall be applied in multiple coats to ensure proper paint coverage with a high gloss finish.

The cab exterior shall be painted with PPG Delta system to match purchaser's furnished paint codes. A two-tone paint finish shall be provided with the two-tone break line located approximately 3" below the cab side windows.

The entire exterior finish of the cab shall be buffed and detailed.

**CAB INTERIOR PAINT**

The interior metal surfaces of the cab shall be painted using black Line-X material.

**CHASSIS PAINT**

The chassis frame rails, suspension and axles shall be painted black with a Polyurethane base paint prior to installation of any air lines or electric systems to ensure proper serviceability.

**WHEEL PAINT**

The chassis wheels and hubs shall be provided as painted by the original wheel and axle manufacturers.

**PAINT CODES**

The paint shall match customer furnished paint code(s) and layout. The paint code(s) shall be as indicated below:

• **PRIMARY PAINT COLOR**

Single Color: TBD Paint Code# TBD

• **SECONDARY PAINT COLOR**

Two/Tone Color: TBD Paint code# TBD

**TOUCH-UP PAINT**

One (1) pint of each exterior color paint for touch-up purposes shall be supplied when the apparatus is delivered to the end user.

**FINALIZATION & DETAILING**

Prior to delivery the vehicle, the interior and exterior be cleaned and detailed. The finalization process detailing shall include installation of NFPA required labels, checking fluid levels, sealing and caulking required areas of the cab and body, rust proofing, paint touch-up, etc.

**RUST PROOFING**

The entire unit shall be thoroughly rust proofed utilizing rustproof and sound deadening materials applied in manufacturer recommended application procedures. Rust proofing shall be applied during the assembly process and upon completion to insure proper coverage in all critical areas.

\*\*\*\* LETTERING AND STRIPING \*\*\*\*

**COMPUTER GENERATED LETTERING**

The lettering and striping shall be custom designed utilizing state of the art computer software and computerized cutting machines. The manufacturer shall employ a full time artist / designer to generate all lettering, decals, and striping to meet the requirements of the Fire Department. The artwork for the lettering and striping shall be kept on record by the apparatus manufacturer to allow for ease in duplication for the Fire Department.

**FRONT CAB DOOR LETTERING**

Gold leaf, "Sign Gold", with drop shadow lettering shall be provided on the cab driver's and officer's doors per the fire department requirements. The design of the lettering on the cab doors shall be designed to fit in the 496 sq. inches available.

Lettering provided on the driver's and officer's cab doors shall be 3" high.

**REAR CAB DOOR LETTERING**

Gold leaf, "Sign Gold", with drop shadow lettering shall be provided on the cab crew doors per the fire department requirements. The design of the lettering on the cab doors shall be designed to fit in the 496 sq. inches available.

Lettering provided on the crew cab doors shall be 3" high.

**REAR BODY LETTERING**

Gold leaf, "Sign Gold", with drop shadow lettering shall be provided on the rear body panel per the fire department requirements. The design of the lettering on the rear of the body shall be designed to fit in the 167 sq. inches available.

Lettering provided on the rear body panel shall be 3" high.

**BODY SIDE SHEET LETTERING**

Gold leaf, "Sign Gold", with drop shadow lettering shall be provided on the body side sheet per the fire department requirements. The design of the lettering on the body side sheet shall be designed to fit in the 2500 sq. inches available.

Lettering provided on the body side sheet shall be 6" high.

**LETTERING FONT**

The lettering shall be designed and cut with a basic block type font:

"BLOCK TYPE FONT"

**STANDARD MALTESE CROSS DESIGN 1**

A pair of standard Maltese crosses shall be computer generated and will be no larger than the 496 sq. inches available.

The standard logo shall be printed on Gold leaf, "Sign Gold", with two computer generated printed colors.

The Maltese cross shall be located as directed by the Fire Department.

**BODY ACCENT STRIPING**

Accent striping shall be provided on each side of the body, around the perimeter of the compartments as directed by the Fire Department.

The body perimeter accent striping shall be made with "Sign Gold" gold leaf material, which shall be 1/2" wide with a black border.

**CAB PAINT BREAK ACCENT STRIPING**

Accent striping shall be provided on each side of the cab at the cab paint break line.

The cab paint break accent striping shall be made with "Sign Gold" gold leaf material, which shall be 1/2" wide with a black border.

**CORNER SCROLLS**

Custom designed corner scrolls shall be provided and installed on the apparatus as directed by the Fire Department.

A total of four (4) scrolls shall be provided and made with "Sign Gold" gold leaf material, which shall be equipped with a black border.

**\*\*\*\* NFPA REQUIRED SCOTCH-LITE STRIPING \*\*\*\***

**SCOTCH-LITE STRIPE**

A six (6) inch high "Scotch-Lite" stripe shall be provided. The stripe shall be applied on a minimum of 60 percent of each side of the unit, 60 percent on the rear of the unit and 40 percent on the front of the unit. The Scotch-Lite stripe layout shall be determined by the Fire Department.

The Scotch-Lite shall be white in color.

A six (6) inch custom fold shall be incorporated into the Scotch-Lite scheme on the body. Final layout of this configuration shall be determined by the Fire Department.

**SCOTCH-LITE ACCENT STRIPES**

A 1" high Scotch-Lite material accent stripe shall be incorporated into the Scotch-Lite scheme to border the primary Scotch-Lite stripe on the top and bottom edges. Final layout of this configuration shall be determined by the Fire Department.

**REAR CHEVRON STRIPING**

The entire rear of the truck shall be covered with alternating strips of reflective striping.

The striping shall be 6" Diamond Grade Scotch-Lite.

The Diamond Grade Scotch-Lite shall be Red and Fluorescent Yellow Green in color.

\*\*\*\* WARRANTIES & REQUIRED INFORMATION \*\*\*\*

**WARRANTY, STARTING ON DELIVERY DATE**

Warranty coverage by the manufacturer shall begin on the date of delivery to the customer.

**WARRANTY - CUSTOM CHASSIS**

The specified vehicle shall include a one (1) year new vehicle warranty, upon delivery and acceptance of the vehicle. The warranty shall ensure that the vehicle has been manufactured to the proposed contract specifications and shall be free from defects in material and workmanship that may appear under normal use and service within the warranty period. The warranty may be subject to different time and mileage limitations for specific components and parts. This warranty is issued to the original purchaser of the vehicle.

The warranty shall not apply to tires, batteries, or other parts or components that are warranted directly by their manufacturers. The warranty shall not apply to routine maintenance requirements as described in the service and operators manual. No warranty whether express, implied, statutory or otherwise including, but not limited to any warranty of merchantability or fitness for purpose shall be imposed.

**OVERALL UNIT AND CUSTOM CHASSIS**

All components and parts of the vehicle are warranted for a period of one (1) year from acceptance of the vehicle, unless excluded elsewhere in this warranty or described as having longer time limitations.

**WARRANTY - ENGINE**

The specified fire service rated engine shall be provided with a five (5) year engine manufacturer's warranty. A copy of the manufacturer's warranty shall be supplied to define additional details of the warranty provisions.

**WARRANTY - TRANSMISSION**

The specified Allison transmission shall be provided with a five (5) year warranty. A copy of the Allison transmission warranty shall be supplied to the purchaser to define additional details of the warranty provisions.

**WARRANTY - COOLING SYSTEM - CUSTOM CHASSIS**

The manufacturer warrants all Cooling System Equipment components used in the construction of the manufacturer's fire apparatus against defects and workmanship provided the apparatus is used in a normal and reasonable manner. This warranty is extended only to the original user-purchaser for a period of three (3) years from the date of delivery / acceptance to the original user-purchaser, which ever occurs first.

This warranty applies to both purchased and fabricated, manufacturer supplied, coolant system components, and is not provided in lieu of any Vendor provided warranties. All coolant system components provided by the engine manufacturer are covered by the engine manufacturer's warranty only.

**WARRANTY - CUSTOM CHASSIS FRAME RAILS**

The purchaser requires that the custom chassis frame shall be warranted for the lifetime of the vehicle

**CROSSMEMBERS WARRANTY**

A lifetime warranty shall be provided on all chassis frame cross members.

**WARRANTY - STEERING UNIT**

The proposed Sheppard steering gear shall be warranted for a period of three (3) years from the first date of service or 150,000 miles (241,401 kilometers), whichever occurs first. The product shall be free from defects in material and workmanship under normal use in applications approved in advance by Sheppard.

**WARRANTY - FRONT AXLE**

The Meritor axle/s shall be furnished with a two (2) year parts and labor warranty. The wheel seals, gaskets and wheel bearings shall have a one (1) year warranty. A copy of the manufacturer's warranty shall be supplied to define additional details of the warranty provisions.

**WARRANTY - REAR AXLE**

The Meritor axle/s shall be furnished with a two (2) year parts and labor warranty. The wheel seals, gaskets and wheel bearings shall have a one (1) year warranty. A copy of the manufacturer's warranty shall be supplied to define additional details of the warranty provisions.

**WARRANTY - CAB STRUCTURE**

The cab shall be warranted against structural defects for a period of ten (10) years from the date of acceptance of the unit. Details of warranty coverage, limitations and exclusions are included in the specific warranty document.

**WARRANTY - BODY STRUCTURE**

The body shall be warranted against structural defects for a period of ten (10) years from the date of acceptance of the unit. Details of warranty coverage, limitations and exclusions are included in the specific warranty document.

**WARRANTY - CORROSION**

The cab and body shall be warranted against rust-through or perforation, due to corrosion from within, for a period of ten (10) years. Perforation is defined as a condition in which an actual hole occurs in a sheet metal panel due to rust or corrosion from within. Surface rust or corrosion caused by chips or scratches in the paint is not covered by this warranty.

**WARRANTY - PAINT**

The paint finish will be warranted for a period of seven (7) years from the date of acceptance of the unit. Details of warranty coverage, limitations and exclusions are included in the specific warranty document.

**WARRANTY - LETTERING**

The apparatus manufacturer will provide a five (5) year warranty against defects in material and workmanship for all graphic processes. Any valid claims must be made in writing within 15 days of the determination of any defects to the manufacturer's fire apparatus. The manufacturer will at its option make any necessary repairs either at a local authorized service center or at the factory, if required. The manufacturer will make the final decision as to where the repairs are to be made and any transportation cost are the owners responsibility. The manufacturer will at its option, repair or replace any verified defects in workmanship or materials at no cost to the owner provided all the requirements of this warranty have been met.

The manufacturer will not be liable to the original purchaser or anyone else for consequential, incidental, special or direct damages, including, but not limited to, any claims for loss of profits, down time, loss of use or inconvenience. THE COMPANY MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, AND SPECIFICALLY, DISCLAIMS ANY IMPLIED WARRANTY INCLUDING THE WARRANTY OF MERCHANTABILITY.

The manufacturer continually strives to improve its products and therefore, reserves the right to make improvements or changes without incurring any obligations to make such changes or additions on equipment previously sold.

**WARRANTY - BRIGHTWORK**

The manufacturer warrants all bright finish components used in the construction of their apparatus against defects and workmanship provided the apparatus is used in a normal and reasonable manner. This warranty is extended only to the original user-purchaser for a period of one (1) year from the date of delivery / acceptance to the original user-purchaser, whichever occurs first.

The expressed warranty excludes corrosion or degradation of bright finished components caused by damage to the component.

**WARRANTY - STAINLESS STEEL PLUMBING WARRANTY**

The stainless steel plumbing shall be warranted for a period of ten (10) years from the date of acceptance of the unit. Details of warranty coverage, limitations and exclusions are included in the specific warranty document.

**WARRANTY - REAR SUSPENSION**

The manufacturer hereby warrants to the original Buyer, that leaf spring products installed shall be free of defects in material and workmanship for one (1) year. The "Warranty Period" commences on the date the original Buyer takes delivery of the product from the manufacturer.

**WARRANTY - WATER TANK**

The water tank shall be warranted by the water tank manufacturer for the "Lifetime" of the unit. A copy of the manufacturer's warranty shall be supplied to define additional details of the warranty provisions.

**WARRANTY - FIRE PUMP**

Hale Products, Incorporated ("Hale") hereby warrants to the original buyer that products manufactured by Hale shall be free of defects in material and workmanship for a period of five (5) years from the date product is first placed into service or five and one-half (5 1/2) years from date of shipment by Hale, whichever period shall be first to expire. Within this warranty period Hale will cover parts and labor for the first two (2) years and parts only for years three (3) through five (5).

**WARRANTY - FOAM SYSTEM**

The liability of FoamPro under the foregoing warranty shall be limited to the repair or replacement at FoamPro's option without charge for labor or materials of any parts upon return of the entire pump, system or other product or of the particular part to the FoamPro factory within the warranty period, at the sole expense of the purchaser, which part shall upon examination appear to FoamPro's satisfaction to have been defective in material and workmanship.

**WARRANTY - CLASS 1 - PRODUCTS**

Class 1 warrants that any equipment of our own manufacture (or manufactured for us pursuant to our specifications) found to have defects in material or workmanship during normal use and service, shall be repaired or replaced (at our opinion) free of charge, provided that written notice of such defect is received by us within two (2) years, (three 3 years on liquid filled gauges) after initial shipment.

**WARRANTY - AKRON PRODUCTS**

The limited warranty set forth here against defective materials or workmanship for a period of five (5) years shall be given by Akron Brass Co. with respect to Akron Brass Co. products purchased and used in the United States and Canada respectively. All Akron valves are warranted for 10 years.

**WARRANTY - HEAVY DUTY VALVES**

Akron Brass warrants Heavy Duty Swing-Out Valves for a period of ten (10) years after purchase against defects in material or workmanship. Akron Brass shall repair or replace any Heavy Duty Swing Out Valve which fails to satisfy this warranty.

**WARRANTY - SEATING**

HO Bostrom shall warrant each new seat manufactured, to be free from defects in materials and workmanship when delivered to the original purchaser for a period of five (5) years.

Labor to remove or reinstall and transportation of defective items will not be covered by, or any allowance made for said cost under this warranty.

**WARRANTY - GENERATOR**

The specified generator shall have a five (5) year or one thousand (1,000) hour warranty, all parts and labor, as provided by the generator manufacturer. A copy of the generator warranty shall be provided at time of delivery.

**NFPA REQUIRED LOOSE EQUIPMENT, PROVIDED BY FIRE DEPARTMENT**

The following loose equipment as outlined in NFPA 1901, 2016 edition in accordance with the applicable requirements unless supplied by the manufacturer or sales rep organization, will be provided by the fire department. All loose equipment will be installed on the apparatus before placed in emergency service, unless the fire department waives NFPA section 4.21.

**Section 5.7 Equipment.**

It is the responsibility of the purchaser to ensure that all required equipment has been supplied and installed on the apparatus in order to achieve compliance with the standard prior to placing it in service.

**5.7.1 Ground Ladders.**

5.7.1.1 All fire department ground ladders carried on the apparatus shall meet the requirements of NFPA 1931, Standard for Manufacturer's Design of Fire Department Ground Ladders, except as permitted by 5.7.1.3 and 5.7.1.4.

5.7.1.2 At a minimum, the following fire department ground ladders shall be carried on the apparatus:

- (1) One straight ladder equipped with roof hooks
- (2) One extension ladder
- (3) One folding ladder

5.7.1.3 Stepladders and other types of multipurpose ladders meeting ANSI A14.2, Ladders - Portable Metal- Safety Requirements, or ANSI A14.5, Ladders - Portable Reinforced Plastic Safety Requirements, with duty ratings of Type IA or IAA shall be permitted to be substituted for the folding ladder required in 5.7.1.2(3).

5.7.1.4 Stepladders and other types of multipurpose ladders shall be permitted to be carried in addition to the minimum fire department ground ladders specified in 5.7.1.2 provided they meet either ANSI A14.2 or ANSI A14.5 with duty ratings of Type 1A or 1AA.

**Section 5.7.2 Suction Hose or Supply Hose.**

It is the responsibility of the purchaser to ensure that all required equipment has been supplied and installed on the apparatus in order to achieve compliance with the standard prior to placing it in service.

5.7.2.1 A minimum of 20 ft (6 m) of suction hose or 15 ft (4.5 m) of supply hose shall be carried.

5.7.2.1.1 Where suction hose is provided, a suction strainer shall be furnished.

5.7.2.1.2 Where suction hose is provided, the friction and entrance loss of the combination suction hose and strainer shall not exceed the losses listed in Table 16.2.4.1 (b) or Table 16.2.4.1(c).

5.7.2.1.3 Where supply hose is provided. It shall have couplings compatible with the local hydrant outlet connection on one end and the pump intake connection on the other end.

5.7.2.2 Suction hose and supply hose shall meet the requirements of NFPA 1961, Standard on Fire Hose.

**Section 5.8 Minor Equipment.**

It is the responsibility of the purchaser to ensure that all required equipment has been supplied and installed on the apparatus in order to achieve compliance with the standard prior to placing it in service.

5.8.2 Fire Hose and Nozzles. The following fire hose and nozzles shall be carried on the apparatus:

- (1) 800 ft (240 m) of 2 1/2 in. (65 mm) or larger fire hose
- (2) 400 ft (120 m) of 1 1/2 in. (38 mm), 1 3/4 in. (45 mm), or 2 in. (52 mm) fire hose
- (3) One handline nozzle. 200 gpm (750 L/min) minimum
- (4) Two handline nozzles. 95 gpm (360 L/min) minimum
- (5) One playpipe with shutoff and 1 in. (25 mm), 1 1/8 in. (29 mm), and 1 1/4 in. (32 mm) tips

5.8.3 Miscellaneous Equipment. The following additional equipment shall be carried on the apparatus:

- (1) One 6 lb (2.7 kg) flathead axe mounted in a bracket fastened to the apparatus
- (2) One 6 lb (2.7 kg) pickhead axe mounted in a bracket fastened to the apparatus
- (3) One 6 ft (2 m) pike pole or plaster hook mounted in a bracket fastened to the apparatus
- (4) One 8 ft (2.4 m) or longer pike pole mounted in a bracket fastened to the apparatus
- (5) Two portable hand lights mounted in brackets fastened to the apparatus
- (6) One approved dry chemical portable fire extinguisher with a minimum 80-B:C rating mounted in a bracket fastened to the apparatus
- (7) One 2 1/2 gal (9.5 L) or larger water extinguisher mounted in a bracket fastened to the apparatus
- (8) One self-contained breathing apparatus (SCBA) complying with NFPA 1981, Standard on Open-Circuit Self Contained Breathing Apparatus (SCBA) for Emergency Services, for each assigned seating position. But not fewer than four, mounted in brackets fastened to the apparatus or stored in containers supplied by the SCBA manufacturer
- (9) One spare SCBA cylinder for each SCBA carried, each mounted in a bracket fastened to the apparatus or stored in a specially designed storage space
- (10) One first aid kit
- (11) Four combination spanner wrenches mounted in brackets fastened to the apparatus
- (12) Two hydrant wrenches mounted in brackets fastened to the apparatus
- (13) One double female 2 1/2 in. (65 mm) adapter with National Hose (NH) threads, mounted in a bracket fastened to the apparatus
- (14) One double male 2 1/2 in. (65 mm) adapter with NH threads, mounted in a bracket fastened to the apparatus
- (15) One rubber mallet, suitable for use on suction hose connections, mounted in a bracket fastened to the apparatus
- (16) Two salvage covers each a minimum size of 12 ft x 14 ft (3.7 m x 4.3 m)
- (17) Two or more wheel chocks. Mounted in readily accessible locations, that together will hold the apparatus. When loaded to its GVWR or GCWR, on a hard surface with a 20 percent grade with the transmission in neutral and the parking brake released
- (18) One traffic vest for each seating position, each vest to comply with ANSI/ISEA 207, Standard for High-Visibility Public Safety Vests, and have a five-point breakaway feature that includes two at the shoulders, two at the sides, and one at the front
- (19) Five fluorescent. orange traffic cones not less than 28 in. (711 mm) in height, each equipped with a 6 in. (152 mm) retroreflective white band no more than 4 in. (102 mm) from the top of the cone, and an additional 4 in. (102 mm) retroreflective white band 2 in. (51 mm) below the 6 in. (152 mm) band
- (20) Five illuminated warning devices such as highway flares, unless the live fluorescent orange traffic cones have illuminating capabilities
- (21) One automatic external defibrillator (AED)

5.8.3.1 If the supply hose carried does not use sexless couplings, an additional double female adapter and double male adapter, sized to fit the supply hose carried, shall be carried mounted in brackets fastened to the apparatus.

- 5.8.3.2 If none of the Pump intakes are valved, a hose appliance that is equipped with one or more gated intakes with female swivel connection(s) compatible with the supply hose used on one side and a swivel connection with pump intake threads on the other side shall be carried. Any intake connection larger than 3 in. (75 mm) shall include a pressure relief device that meets the requirements of 16.6.6.
- 5.8.3.3 If the pumper is equipped with an aerial device with a permanently mounted ladder, four ladder belts meeting the requirements of NFPA 1983, Standard on Life Safety Rope and Equipment for Emergency Services shall be provided.
- 5.8.3.4 If the apparatus does not have a 2 1/2 in. intake with NH threads, an adapter from 2 1/2 in. NH female to a pump intake shall be carried, mounted in a bracket fastened to the apparatus if not already mounted directly to the intake.
- 5.8.3.5 If the supply hose carried has other than 2 1/2 in. NH threads, adapters shall be carried to allow feeding the supply hose from a 2 1/2 in. NH thread male discharge and to allow the hose to connect to a 2 1/2 in. NH female intake, mounted in brackets fastened to the apparatus if not already mounted directly to the discharge or intake.

14.1.8.4 Fire Helmet.

It is the responsibility of the purchaser to ensure that "Fire helmets shall not be worn by persons riding in enclosed driving and crew areas any time the apparatus is placed in service.

- 14.1.8.4.1 A location for helmet storage shall be provided.
- 14.1.8.4.2 If helmets are to be stored in the driving or crew compartment, the helmets shall be secured in compliance with 14.1.11.2.

14.1.10 SCBA Mounting.

It is the responsibility of the purchaser to ensure that any SCBA equipment has been supplied and installed on the apparatus in order to achieve compliance with the standard prior to placing it in service.

- 14.1.10.1 Where SCBA units are mounted within a driving or crew compartment, a positive latching mechanical means of holding the SCBA device in its stowed position shall be provided such that the SCBA unit cannot be retained in the mount unless the positive latch is engaged.
- 14.1.10.2 The bracket holding device and its mounting shall retain the SCBA unit when subjected to a 9 G force and shall be installed in accordance with the bracket manufacturer's requirements.
- 14.1.10.3 If the SCBA unit is mounted in a seatback, the release mechanism shall be accessible to the user while seated.

14.1.11 Equipment Mounting.

It is the responsibility of the purchaser to ensure that any equipment installed on the apparatus by them or their subcontractor meets the following requirements prior to placing it in service.

- 14.1.11.1 All equipment required to be used during an emergency response shall be securely fastened.
- 14.1.11.2 All equipment not required to be used during an emergency response, with the exception of SCBA units, shall not be mounted in a driving or crew area unless it is contained in a fully enclosed and latched compartment capable of containing the contents when a 9 G force is applied in the longitudinal axis of the vehicle or a 9G force is applied in any other direction, or the equipment is mounted in a bracket(s) that can contain the equipment when the equipment is subjected to those same forces.

Section 15.9.3 Reflective Striping.

It is the responsibility of the purchaser to ensure that Reflective Striping has been supplied and installed on the apparatus in order to achieve compliance with the standard prior to placing it in service.

15.9.3.1" A retroreflective stripe(s) shall be affixed to at least 50 percent of the cab and body length on each side, excluding the pump panel areas, and at least 25 percent of the width of the front of the apparatus.

15.9.3.1.1 The stripe or combination of stripes shall be a minimum of 4 in. (100 mm) in total width.

15.9.3.1.2 The 4 in. (100 mm) wide stripe or combination of stripes shall be permitted to be interrupted by objects (i.e., receptacles, cracks between slats in roll up doors) provided the full stripe is seen as conspicuous when approaching the apparatus.

15.10 Hose Storage.

It is the responsibility of the purchaser to ensure that any hose storage area includes a positive means to prevent unintentional deployment in order to achieve compliance with the standard prior to placing it in service.

15.10.7 Any hose storage area shall be equipped with a positive means to prevent unintentional deployment of the hose from the top, sides, front, and rear of the hose storage area while the apparatus is underway in normal operations.